## LUMINAIRE SCHEDULE

SYMBOL	IMAGE	DESCRIPTION
Goe Note 1	D	Thorlux 20w LED Clara 90 wall mounted uplighter.
B See Note 1		Thorlux 43w LED Kanby EVO luminaire. Low glare version. To be complete with dimmable control gear to link to the Casamby lighting system.
C See Note 1		Thorlux 22w LED Kanby EVO luminaire. Low glare version. C/W SmartScan and integral movement sensor.
D Gas Fizze 1		Thorlux 30w LED Jubilee luminaire. Opal version. C/W SmartScan.
F Gas Note 1		Thorlux 36w LED Kanby EVO luminaire. Opal version. C/W SmartScan.
FL See Note 1		Thorlux 36w LED Kanby EVO luminaire. Low glare version. C/W SmartScan.
G Sisso Note 1		Thorlux 43w LED Kanby PRO luminaire. Low glare version. C/W SmartScan.
H See Note 1		Thorlux Primalette 360.16W. complete with the Smartscan Radar.
H/E See Note 1		Thorlux SS.Primalette 360.16W.Radar. C/W Smartscan Radar.
J See Note 1	1	Thorlux SkyGlo - Recessed - 24W - IP40 - 4000K
K See Note 1	1	Thorlux SkyPro - Pendant - 34W - IP40 - 4000K
	Co	30w Thorlux LED 1500mm Thoroproof anti-corrosive luminaire. IP65. C/W SmartScan.
LE	c	30w Thorlux LED 1500mm Thoroproof anti-corrosive luminaire. IP65. C/W SmartScan and 3hr Emergency control gear.
M		31w Thorlux "Lightline Individual" LED 1500mm suspended luminaire. C/W SmartScan and dimmable ballast.
(E)	-0	Thorlux "Firefly Plus" SmartScan LED maintained emergency. Standard Version.
E1↓ See Nate 1	XII	Thorlux "LEXI" SmartScan LED maintained emergency Exit Sign. c/w arrow down ISO 7010 legend panel.
E2	9	Thorlux "Celo" surface wall mounted LED SmartScan emergency light. Standard version. c/w control module.
Gen Note 1		Thorlux "Firefly Plus" surface LED SmartScan emergency downlighter. Standard version. c/w control module.
E4		Thorlux "Firefly" surface LED SmartScan emergency downlighter. Area version. c/w control module.
E5		Thorlux "Firefly" surface LED SmartScan emergency downlighter. Corridor version. c/w control module.
E6		Thorlux "Firefly" surface LED SmartScan emergency downlighter. Standard version. c/w control module.
See Nate 1		Thorlux "REALTA MICRO" surface IP65 external LED SmartScan emergency downlighter. Standard version. c/w control module.
т —		Concord Sylvania "LYTESPAN" 3 Circuit standard track with Dali circuit to allow Casmbi control of the luminaires.

his Drawing is protected by Copyright. It may not be reproduced in any form or any means for any purpose without the written consent of ference Services Desig Ltd. Do not scale: All Dimensions to be cheated on Sile and verified prior to commencing Works / Marufacture, Any discrepancies to the explored to Kenno Services Design Ltd. These Drawings reflect the layouts for the purposes of desigonly. The Cortactor shall be responsible for producing their com Working and Co-ordination drawings prior to commencing their installations. If these drawing are use for Construction purposes it does not self-contractor's fisk.

Scale Bar: 1:100
0 1 2 3 4 5 6

 1
 18/09/2023
 Tender Issue
 MA
 CC
 M.

 ev
 Date
 Revision
 Dm
 Chk
 Apr



Tel: 07464 605683 email: info@kernowservicesdesign.co.uk website: www.kernowservicesdesign.co.uk

ROYAL CORNWALL MUSEUM

Project Name:

ROYAL CORNWALL MUSEUM TRURO, CORNWALL

Drawing Tit

LUMINAIRE SCHEDULE

Scale at A3:

NTS

Status: Tender Issue

Drawing No: Revision: 1107-KSD-DR-E10-001 T1