

Specification of works to resurface the hard tennis courts, replace the boundary fencing and install new tennis posts and nets at Guldrey Lane, Sedbergh LA10 5DS

Site preparation:

Storage area for materials and equipment to be established on existing car park area adjacent to the courts in advance of the contract starting.

Works required:

Resurface 2 No. existing porous macadam tennis courts

- Moss treat existing courts surface as required. Clean existing court surface using a high pressure washer.
- Prepare existing court surface as required to ensure effective drainage.
- Supply and install 1 No. new recessed inspection chamber cover set to the height of the new proposed playing surface.
- Weed control strip – to be installed between the courts and the fencing. Precise details to be agreed.
- Supply and install new perimeter kerb edgings, laid flat and haunched to the court perimeter.
- Sockets – excavate existing tennis post sockets and centre ground plungers and dispose from site. Supply and install 2 No. sets of heavy duty galvanised hinged tennis post sockets. Supply and install 2 No. new ground anchors.
- Apply a bitumen emulsion tack coat to the area prior to resurfacing.
- Supply and install open textured macadam surfacing in accordance with LTA and SAPCA standards.
- Apply temporary line markings until permanent paint can be applied.
- Apply two coats of Acrylic Sports Coating in two tone dark and light green to provide a slip resistant and UV stable colour coated surface, plus lining for 2 No. courts.

Tennis posts and nets

- Supply and install 2 No. sets of new 75mm square, green nylon coated tennis posts with brass winders and lacing bars.
- Supply 2 No. black 3.5mm braided knotted polyethylene tennis nets, with polyester headband, vinyl sides and base 3mm steel coated headline with loop and pin.

Fencing

- Remove existing chain link fencing and dispose off site.
- Supply and install new 2.75m high, 3.15/2.24 gauge dark green pvc coated 50x50 mesh chain link fencing, with top rail and heavy duty posts. (Sample to be agreed).
- Chain link supported on 42.1 x 2.5mm circular hollow section posts and 60.3 x 3.2mm corner posts, all galvanised and dark green powder coated.
- 2 No. 1.2m wide access gates (suitable for wheel-chair access) in positions to be agreed.
- Include line wires and all necessary fixings.
- New fencing to surround courts, pavilion and grass area as existing.

Reinstatement:

The site to be left in a clean and tidy condition and all waste material removed.