



Appendix C

Sam Hagley: 0080B

Attention: Paul Williams

Date: 5/1/18

Prepared by Sam Hagley Specification Manager

**PROJECT: HORNIMAN MUSEUM**

## **K32 PANEL CUBICLES/ DUCT AND WALL LININGS/ SCREENS**

To be read with Preliminaries/General conditions.

### **120/01 PANEL CUBICLES - UNFRAMED**

Drawing reference(s):Cubicles

Manufacturer and reference: Venesta Washroom Systems, Chartwell Court, West Mill, Imperial Business Park, Gravesend, Kent. DA11 0DL. Tel 01474 353333.

Product: 'Award HPL' range.

Board/panel type: 680kg/m<sup>3</sup> furniture grade moisture resistant Chipboard faced each side with High Pressure Laminate (HPL).

Thickness: 18mm nominal.

Edge treatment: 0.6mm matching PVC.

Depth: 2000mm maximum recommended from face of back wall or rear ducting.

Floor Clearance: 100mm.

Overall height: 2100mm overall from FFL.

Door Height: Standard: 2000mm - 2100mm from FFL to top of door including 100mm ground clearance

Colour/Finish - Panels/Doors: From the Venesta standard Award colour range.

Headrail: Powder coated aluminium channel (light or dark grey) with insert at door opening.

Hinges: Powder coated aluminium safety hinge (light or dark grey).

Pedestals: Adjustable, to pilasters and/or partitions.

Indicator bolt and keep: Easy grip sliding bolt with emergency release facility and concealed fixings.

Cleats: with concealed fixings.

Colour/Finish – Frame/Fittings: Light or Dark Grey ABS (Acrylonitrile Butadiene Styrene).

Accessories: Venesta Toilet Roll Holder (NBS Clause N13/462); Venesta Coat Hook (NBS Clause N13/429); Document M 2004 Compliant grab rails and door pulls (NBS Clause N13/436).

## 140/01

### DUCT/ WALL LININGS – PANELS ONLY

- Drawing reference(s):
- Manufacturer and reference: Venesta Washroom Systems, Chartwell Court, West Mill, Imperial Business Park, Gravesend, Kent. DA11 0DL. Tel 01474 353333.
- Product: **'Rapiduct SGL', Compact laminate, wall lining system.**
- Panel: High Density Solid Grade laminate (SGL) with decorative face both sides.
- Panel Thickness: 13mm nominal.
- Edge treatment: radiused and polished.
- Background/Support framing: By others.  
Support frame facings/flashgaps: 13mm High density solid grade (SGL) laminate with decorative face both sides.
- Colour/Finish: From the Venesta's standard colour range.
- Method of fixing panels: Concealed plastic clips fixed to edge of flashgap strips and reverse of facing panels.
- Joint treatment: Nominal 25mm wide flashgap between each panel section (Nominal 70mm wide where flashgap is to accommodate cubicle partition).
- Components/Accessories: Venesta MFC flashgap system and fixing clips, sanitary appliances as specified in section N13.
- Included features: Removable access panels.