

Please price to supply & install:

1 x single entry run of 5 bays of library shelving, each bay 1994mm high (1594mm to top picking level) x 1100mm wide x 350mm deep. Bays have back stops on every shelf and 4 storage levels plus a slanted display shelf.

1 x static wall-mounted mesh panel nominally 3.4m wide x 2320mm high fitted with raised legs.

1 x static wall-mounted mesh panel nominally 6.6m wide x 2320mm high fitted with raised legs.

4 x double entry runs of mobile shelving each run consisting of 5 x 1m wide x 450mm deep x 2354mm high bays fitted with 5 shelves per bay (no top shelf)

1 x double entry run of mobile shelving each run consisting of 5 x 1m wide x 300mm deep on one side and 450mm deep on the other x 2354mm high bays fitted with 5 shelves per bay (no top shelf)

1 x double entry run of mobile shelving each run consisting of 1 x 900mm wide bay & 3 x 1200mm wide bays x 300mm deep x 2354mm high bays fitted with 5 shelves per bay (no top shelf)

1 x single entry run of static shelving consisting of 1 x 900mm wide bay & 3 x 1200mm wide bays x 300mm deep x 2354mm high bays fitted with 5 shelves per bay (no top shelf)

All runs are to have solid single skin sides with open intermediate uprights and open cross braced backs. Manually assisted mobile shelving with "Terrazzo" infill floor and 200mm low profile aluminium entry face ramp.

1 run of pigeon slot art storage racking, 2074mm high x 870mm deep x 300mm wide slots (12 slots wide x 4 high = 48 locations) Art slots 500mm pitch double skinned uprights

Uprights: Solid uprights to ends of runs with open intermediate uprights for maximum airflow

Backs: Open braced allowing maximum air circulation & "through-storage" in most bays

Shelf: Triple folded safe edge shelves designed to an assumed average load of 83kgs UDSWL

Adjustment: Shelves shall be adjusted on a 20mm pitch in the upright height – no shelf clips are shared offering true independent shelf adjustment.

Label Holders: A4 card holders fitted to all drive ends (1 per single & 2 per double rack end)

Mobile Base: Heavy duty steel bases 150mm high to conform to BS4971 fitted with aisle safety locks

Drive: Direct drive to allow multiple base movements without system or operator strain

Rails & Floor: Steel rails, guide & plain laid within a hard wearing "Terrazzo" styled finished infill floor walking surface.

Ramps: Low profile, aluminium type fitted to entry face as denoted

Colour: White Smoke RAL9002 shelving on Jet-Black bases.