












Rev T01

No.	Manufacturer	Model	Image	Description	Lamp	Notes
L1	OptaLED	Avathis 2 R		Low-profile Recessed LED downlight, IP20, Fixed Output Ø180x27(H)mm	15W 1410 lumens 94 lm/W 4000K	White Finish
L1E	OptaLED	Avathis 2 R with emergency battery conversion kit		Low-profile Recessed LED downlight, IP20, Fixed Output Ø180x27(H)mm Supplied with OptaLED emergency conversion kit including 3hr battery pack	15W 1410 lumens 94 lm/W 4000K	White Finish
L2	OptaLED	Icon 50 suspended linear track system		Suspended luminaire, DALI dimmable 1430(L)x50(W)x84(H)mm	30W 3481lumens 116 lm/W 4000K	White Finish
L2E	OptaLED	Icon 50 suspended linear track system with integral emergency		Suspended luminaire, DALI dimmable with 3hr integral battery pack 1430(L)x50(W)x84(H)mm	30W 3481lumens 116 lm/W 4000K	White Finish


Rev T01

L3E	OptaLED	Avathis 2 R		Low-profile Recessed LED downlight, IP65, Fixed Output Ø180x27(H)mm	15W 1410 lumens 94 lm/W 4000K	White Finish
L4E	OptaLED	Asteri 1 R with emergency battery conversion kit		Circular surface mounted luminaire, fixed output. Ø170x62(H)mm Supplied with OptaLED emergency conversion kit including 3hr battery pack	15W 1410 lumens 94 lm/W 4000K	ASTERI 1
L5E	Diva Lighting	Tupoli 70-360		Suspended Feature tubular LED, Vertical Mounting Ø70x1074(H)mm	16W 1648 lumens 109 lm/W 4000K	Suspension mounting kit
L6E	Glamox Lighting	A15-S280 LED		Wall mounted LED fitting, with fixed output and integral 3hr emergency battery pack Ø280x75(H)mm	22W 1760 lumens 80 lm/W 4000K	Wall mounted fixings with side spigots

Rev T01

L7	OptaLED	Icon 50 suspended linear track system		Suspended continuous pendant feature light with illuminated corners and direct/indirect lighting. DALI dimmable 1710x50(W)x84(H)mm	36W LED 4177 lumens 116 lm/W 3000K	Black Finish
L7E	OptaLED	Icon 50 suspended linear track system with integral emergency		Suspended continuous pendant feature light with illuminated corners and direct/indirect lighting. DALI dimmable. 3hr intergral emergency battery 1710x50(W)x84(H)mm	36W LED 4177 lumens 93 lm/W 3000K	Black Finish
L8E	Thorn Lighting	CESAR WALL		Surface Mounted Linear LED, Fixed Output, IP67. Two sided, Medium Beam distribution To be installed with remote emergency 3hr battery pack Ø140x450(H)mm	32W 1756 lumens 55 lm/W 3000K	Linked to photocell and timeclock in series

Rev T01

EXIT	OptaLED	EX1 Suspended		<p>Suspended emergency exit sign with 3hr battery back-up.</p> <p>Dali Self-test facility</p> <p>337x40x189mm</p>		EX1/S/DE/AD
------	---------	---------------	---	---	--	-------------