



Not to scale - for illustrative purposes only

TREATMENT KEY:

- 50mm inlay TSCS (Do Min)
- Fill and overbanding repair system for crack exceeding 5mm but not exceeding 10mm wide (Do Min)
- Deep repair/ inlay (Do Something)

Notes

- 1) Dimensions are approximate and have been based on the most up-to-date AVIS video data
- 2) Only overhead power lines shown on the treatment plans. For other utilities please refer to the C2 plans for the area
- 3) Due to the potential inaccuracy of AVIS data regarding exact chainages, where Core locations are within the vicinity of a Gully, coring Contractor to adjust the location to avoid potential coring into/through carrier pipes

LOCATION:
 M5 J25-24 NB MP 201.7-196.6
 DRAWING No.
 583 Defect Treatment Plan Sheet 1 of 6
 DRAWN: FS DATE: 22/06/2020
 DESIGN: FS DATE: 22/06/2020
 CHECKED: CC DATE: 25/06/2020

Notes:

<p>DEFECTS KEY</p> <ul style="list-style-type: none"> Core crack depth(mm) Transverse crack minor Transverse crack major Long. crack minor Long. crack major Photo Plug joint Loops Fattening Open long. joint Const. joint Patch Failed patch Rutting Mechanical joint Mud pumping Minor fretting Major fretting Minor surface deterioration Major surface deterioration Depression Minor crazing Major crazing Pothole Core location (tar) Core location (No Tar) Settlement Nodes Ironwork Gully Structure/ Bridge Trafficked Lane Existing HFS New HFS Site to be cored SCRIM Deficiency Texture < 0.8mm
--