

World Museum Liverpool Street Carpets

19 December 2017

Table of Contents

Title		Page
M	Surface finishes	3
M50	Rubber/ plastics/ cork/ lino/ carpet tiling/ sheeting	5

M

Surface finishes

M50

Rubber/ plastics/ cork/ lino/ carpet tiling/ sheeting

M50 Rubber/ plastics/ cork/ lino/ carpet tiling/ sheeting

15 CARPET TILING To Street Areas

- Base: Existing screed finish..
 - Preparation: Remove existing floor tiles and any adhesive.
- Fabricated underlay: Screed.
- Carpet tiles to BS EN 1307: 146 Loop pile.
 - Manufacturer: Paragon A Division of National Floorcoverings Ltd, Farfield Park, Manvers, Wath-upon-Deane, Rotherham S63 5DB. Tel: 0845 601 0431, Fax: 0800 731 4521. Email: sales@paragon-carpets.co.uk Web: www.paragon-carpets.co.uk .
 - Product reference: Grey Fusion contract colourway 2619 Plasma Strobe .
 - Recycled content: None permitted.
 - Size: 500 x 500 mm.
 - Colour/ pattern: plasma.
- Method of laying: Fully adhere every tile with a release adhesive recommended by tile manufacturer Consult Paragon Installation Guide . Paragon recommend the use of Styccobond F41 adhesive for securing their carpet tiles- see F Ball & Co Ltd NBS PLUS page for details.

..

15A CARPET TILING To World Cultures

- Base: Existing screed finish..
 - Preparation: Remove existing carpet and any adhesive including there carpet is under display cabinets.
- Fabricated underlay: Screed.
- Carpet tiles to BS EN 1307: 146 Loop pile.
 - Manufacturer: Tapibel nv. Industrielaan 4 - b - 3900 Overpelt
 - Product reference: Incanti Atlantic 57620 & 57630 .
 - Recycled content: None permitted.
 - Size: 500 x 500 mm.
 - Colour/ pattern: Atlantic.
 - Method of laying: Fully adhere with adhesive recommended by tile manufacturer ..

45 EXISTING FLOOR COVERING REMOVED

- Substrate: Clear of covering and as much adhesive as possible. Skim with smoothing compound to give smooth, even surface.

60 SETTING OUT TILES

- Method: Set out from centre of area/ room so that wherever possible:
 - Tiles along opposite edges are of equal size.
 - Edge tiles are more than 50% of full tile width.

65 LAYING COVERINGS

- Base/ substrate condition: Rigid, dry, smooth, free from grease, dirt and other contaminants.
- Use a primer where recommended by adhesive manufacturer. Allow to dry thoroughly.
- Adhesive: As specified, as recommended by covering manufacturer or, as approved.
- Conditioning of materials prior to laying: As recommended by manufacturer.
- Environment: Before, during and after laying, provide adequate ventilation and maintain temperature and humidity approximately at levels which will prevail after building is occupied.
- Finished coverings: Accurately fitted, tightly jointed, securely bonded, smooth and free from air bubbles, rippling, adhesive marks, stains, trowel ridges and high spots.

70 EDGINGS AND COVER STRIPS

- Manufacturer: Gradus .
 - Product reference: As specified .
- Material/ finish: Aluminium .
- Fixing: Secure (using matching fasteners where exposed to view) with edge of covering gripped.

75 STAIR NOSINGS AND TRIMS

- Manufacturer: Gradus XT Range .
 - Product reference: As specified .
- Material/ finish: Aluminium .
- Fixing: Secure, level with mitred joints. Adjusted to suit thickness of covering with continuous strips of hardboard or plywood. Packing strips and nosings bedded in gap-filling adhesive.
 - Screw fixing with matching plugs: required .

85 WASTE

- Spare covering material: Retain suitable material for patching. On completion submit pieces for selection. Hand over selected pieces to Employer.