

Emitter	Radiator output watts @ 50°C	Number of Sections	Width	Height	Depth
	Carron The victorian Column				
R1	1682	14	874	740	220
R2	2764	23	1414	740	220
R3	2283	19	1174	740	220
R4	1682	14	874	740	220
R5	1682	14	874	740	220
R6	1442	12	754	740	220
R7	2403	20	1234	740	220
R8	2644	22	1354	740	220
R9	3725	31	1894	740	220
R10	1081	9	574	740	220
R11					

Emitter	Radiator output watts @ 50°C	Number of Sections	Width	Height	Depth
	Carron The victorian Column				
R12	3605	30	1834	740	220
R13	2283	19	1174	740	220
R13	2283	19	1174	740	220
R12	3605	30	1834	740	220
R16	2403	20	1234	740	220
R16	2403	20	1234	740	220
R14	2283	19	1174	740	220
R15	2644	22	1354	740	220
R16	2403	20	1234	740	220
R17	1442	12	754	740	220
R18	1442	12	754	740	220
R19	2283	19	1174	740	220
R20	1442	12	754	740	220
R21	2644	22	1354	740	220
R22	1442	12	754	740	220
R23	2764	23	1414	740	220
R24	1682	14	874	740	220
R25	2644	22	1354	740	220
R26	3485	29	1774	740	220
R27	2644	22	1354	740	220
R28	2403	20	1234	740	220
R29	3485	29	1774	740	220
R30	4085	34	2074	740	220
R31	2644	22	1354	740	220
R32	1081	9	574	740	220

Emitter	Radiator output watts @ 50°C	Number of Sections	Width	Height	Depth
	Stelrad				
LST1	1953	K2	1650	750	132
LST2	1395	K2	1250	750	132
LST3	837	K2	850	750	132
LST4	837	K2	850	750	132
LST5	1674	K2	1450	750	132
LST6	2511	K2	2050	750	132
LST7	1953	k2	1650	750	132
LST8	2511	K2	2050	750	132
LST9	1953	k2	1650	750	132
LST10	837	k2	850	750	132
LST11	558	k2	650	750	132
LST12	837	K2	800	750	132
LST13	2511	k2	2050	750	132
	SPC Coil				
SPC1	24372	SPR 60	1000	700	235
SPC2	5912	SPR 40	800	700	235