

This drawing is protected by copyright. No part of this document may be reproduced, altered, or transmitted in any form or by any means without permission.

Do not scale these drawings for construction purposes. If any discrepancies are found, please contact PIVCR.

242° M12 9.00E
8.8 BOLT5

This period

REINFORCE TEAMS CONNECTIONS
(REFER TO DETAILS 1+7)

EXY JOINT

6mm PLATES (both
PDS of 1st & 2nd)
- 1st & 2nd plates 8.8
Bolts

THIS LOWER PUELYND SUPPORTED ON
NEW 100x200 124 BEAM 4" AT
CEILING KEVL VIA 1005R
STANDARD OTHER SIDE OF
LINK

Exfoliating disks, tapered endcours and roof to be removed.

Form new endcourse in existing position using 125500 treated $\frac{1}{2}$ gneod oak. Membr top ply to both decks and covered externally with Sarnell single ply membrane as manufacturers' details from former over to existing roof detailing. 125500 2x4's, minimum 4'x8' with max 22mm gap. Ply sheath and covered with Sarnell membrane as before - all to manufacturers' details.

Steel wall built off existing up joists, resisted not to existing joists.

key

* (with water)
Provide additional 50 x 150 cat litters @ 400% to support alien activity

20 DRAFT

1:100

0 1 2 3 4 5