

Where legislation does not explicitly restrict or limit the use of lead containing coatings it is the responsibility of the client to inform International Paint in writing of their specific requirements

Technical Specification

Interspeed 6400

SEARCHER

UK Customs & Excise

Other Ports, United Kingdom

05-Sep-2019

GBMG1-3CGP-7G9Y/1

Matthew Goodall

matthew.goodall@akzonobel.com

Tel: 01489775060

Mob: 07798845297

Marine Coatings

Unless otherwise agreed in writing, all products supplied and technical advice given by us are subject to our standard terms and conditions of sale. Please note that a surcharge may be applied to the prices listed, in which case this will be notified to you by your International Paint representative. In the event that supplies are made and technical advice is given by one of our associated companies then such supplies and technical advice shall be subject to the standard terms of sale of that company, a copy of which is available upon request

GBMG1-3CGP-7G9Y/1

05-Sep-2019

1

SEARCHER

Main Schemes		
Area	Description	Area (m ²)
Underwater Hull	An Intershield 300 abrasion resistant epoxy underwater scheme, using Intergard 263 as a tar free tie coat to the subsequent antifouling scheme. An Interspeed 6400 tin free antifouling scheme for an in service period of 36 months at <3,000 seamiles per month.	150
Boottop	An Intershield 300 abrasion resistant epoxy underwater scheme, using Intergard 263 as a tar free tie coat to the subsequent antifouling scheme.	50
Below Water Marking		5
Topsides	An Intershield 300 abrasion resistant epoxy scheme	150
Above Water Markings		25
Superstructure	An Intershield 300 abrasion resistant epoxy scheme	250
External Decks	An Intershield 300 tar free high solids epoxy anticorrosive scheme with an Intershield 851 epoxy non skid finish coat.	200
Deck Fittings and Equipment	An Intershield 300 abrasion resistant epoxy scheme	50
Freshwater Tanks	An Interline 925, high performance epoxy scheme certified for the carriage of potable water.	20
Sewage Tank Repairs	An Intershield 300 abrasion resistant epoxy scheme	20
Thinners		

Marine Coatings

Unless otherwise agreed in writing, all products supplied and technical advice given by us are subject to our standard terms and conditions of sale. Please note that a surcharge may be applied to the prices listed, in which case this will be notified to you by your International Paint representative. In the event that supplies are made and technical advice is given by one of our associated companies then such supplies and technical advice shall be subject to the standard terms of sale of that company, a copy of which is available upon request

GBMG1-3CGP-7G9Y/1
05-Sep-2019
2
SEARCHER



Underwater Hull [150 m²]

An Intershield 300 abrasion resistant epoxy underwater scheme, using Intergard 263 as a tar free tie coat to the subsequent antifouling scheme.

An Interspeed 6400 tin free antifouling scheme for an in service period of 36 months at <3,000 seamiles per month.

Surface Preparations

Hydro blasting to Wa 2½M ISO 8501-4 (International Paint HB2½M standard, Sa2½ equivalent with moderate flash rusting).

Surfaces should be dry and free of all contamination (oil, grease, salt etc).

Product	Colour	Coats	% Loss factor	DFT (µm)	WFT (µm)	PSR (m ² /lt)	Hard Dry 5°C	Overcoating 5°C		Thinner	Cleaner	Volume (lt)
								Min	Max			
Intershield 300	Bronze	FC	30	175	292	2.40	8hrs	9hrs	14days	GTA220	GTA220, GTA822	62.5
Intergard 263	Light Grey	FC	30	75	132	5.32	24hrs	24hrs	8days	GTA220	GTA220, GTA822	28.2
Interspeed 6400	Red	FC	30	125	208	3.36		12hrs	6mths	GTA007	GTA007	44.6
				375	632							135.3

Marine Coatings

Unless otherwise agreed in writing, all products supplied and technical advice given by us are subject to our standard terms and conditions of sale. Please note that a surcharge may be applied to the prices listed, in which case this will be notified to you by your International Paint representative. In the event that supplies are made and technical advice is given by one of our associated companies then such supplies and technical advice shall be subject to the standard terms of sale of that company, a copy of which is available upon request

GBMG1-3CGP-7G9Y/1
05-Sep-2019
3
SEARCHER

AkzoNobel

Boottop [50 m²]

An Intershield 300 abrasion resistant epoxy underwater scheme, using Intergard 263 as a tar free tie coat to the subsequent antifouling scheme.

Surface Preparations

Hydro blasting to Wa 2½M ISO 8501-4 (International Paint HB2½M standard, Sa2½ equivalent with moderate flash rusting).

Surfaces should be dry and free of all contamination (oil, grease, salt etc).

Product	Colour	Coats	% Loss factor	DFT (µm)	WFT (µm)	PSR (m ² /lt)	Hard Dry 5°C	Overcoating 5°C		Thinner	Cleaner	Volume (lt)
								Min	Max			
Intershield 300	Bronze	FC	30	175	292	2.40	8hrs	9hrs	14days	GTA220	GTA220, GTA822	20.8
Intergard 263	Light Grey	FC	30	75	132	5.32	24hrs	24hrs	8days	GTA220	GTA220, GTA822	9.4
Trilux 33	Black	FC	30	125	278	2.52		24hrs	4wks	GTA007	GTA007	19.8
				375	702							50.0

Below Water Marking [5 m²]

Surface Preparations

Hydro blasting to Wa 2½M ISO 8501-4 (International Paint HB2½M standard, Sa2½ equivalent with moderate flash rusting).

Surfaces should be dry and free of all contamination (oil, grease, salt etc).

Product	Colour	Coats	% Loss factor	DFT (µm)	WFT (µm)	PSR (m ² /lt)	Hard Dry 5°C	Overcoating 5°C		Thinner	Cleaner	Volume (lt)
								Min	Max			
Trilux 33	White	FC	30	125	278	2.52		24hrs	4wks	GTA007	GTA007	2.0
				125	278							2.0

Marine Coatings

Unless otherwise agreed in writing, all products supplied and technical advice given by us are subject to our standard terms and conditions of sale. Please note that a surcharge may be applied to the prices listed, in which case this will be notified to you by your International Paint representative. In the event that supplies are made and technical advice is given by one of our associated companies then such supplies and technical advice shall be subject to the standard terms of sale of that company, a copy of which is available upon request

GBMG1-3CGP-7G9Y/1
05-Sep-2019
4
SEARCHER

Topsides [150 m²]

An Intershield 300 abrasion resistant epoxy scheme

Surface Preparations

Hydro blasting to Wa 2½M ISO 8501-4 (International Paint HB2½M standard, Sa2½ equivalent with moderate flash rusting).

Surfaces should be dry and free of all contamination (oil, grease, salt etc).

Product	Colour	Coats	% Loss factor	DFT (µm)	WFT (µm)	PSR (m ² /lt)	Hard Dry 5°C	Overcoating 5°C		Thinner	Cleaner	Volume (lt)
								Min	Max			
Intershield 300	Bronze	FC	30	150	250	2.80	8hrs	9hrs	5days	GTA220	GTA220, GTA822	53.6
Interthane 990	Lt Wthr wrk Grey	FC	40	50	88	6.84	24hrs	24hrs	ext.	GTA056, GTA713, GTA733	GTA056, GTA713, GTA733	21.9
Interthane 990	Lt Wthr wrk Grey	FC	40	50	88	6.84	24hrs	24hrs	ext.	GTA056, GTA713, GTA733	GTA056, GTA713, GTA733	21.9
				250	426							97.4

Above Water Markings [25 m²]

Surface Preparations

Fresh water wash to remove all dirt and contamination, as necessary. Degrease according to SSPC-SP1 solvent cleaning. Ensure area is clean and dry prior to application.

Only for areas of less than 0.5 square metres.

Prepare bare areas of steel to a minimum of St2 ISO 8501-1 (SSPC-SP2). Feather or chip back surrounding area to a sound edge.

Product	Colour	Coats	% Loss factor	DFT (µm)	WFT (µm)	PSR (m ² /lt)	Hard Dry 5°C	Overcoating 5°C		Thinner	Cleaner	Volume (lt)
								Min	Max			
Interthane 990	Black	FC	40	50	88	6.84	24hrs	24hrs	ext.	GTA056, GTA713, GTA733	GTA056, GTA713, GTA733	3.7
				50	88							3.7

Marine Coatings

Unless otherwise agreed in writing, all products supplied and technical advice given by us are subject to our standard terms and conditions of sale. Please note that a surcharge may be applied to the prices listed, in which case this will be notified to you by your International Paint representative. In the event that supplies are made and technical advice is given by one of our associated companies then such supplies and technical advice shall be subject to the standard terms of sale of that company, a copy of which is available upon request

GBMG1-3CGP-7G9Y/1
05-Sep-2019
5
SEARCHER

Superstructure [250 m²]

An Intershield 300 abrasion resistant epoxy scheme

Surface Preparations

Fresh water wash to remove all dirt and contamination, as necessary. Degrease according to SSPC-SP1 solvent cleaning. Ensure area is clean and dry prior to application.

Spot mechanically prepare the surface using an aluminium oxide abrasive disk (24-30 grit) to give a heavily scored surface profile of 50-75 microns (2-3 mils). Ensure the area is clean and dry and apply initial coat within 6-8 hours.

Feather or chip back surrounding area to a sound edge. Overlap onto existing sound coatings by 2-3 cms.

Product	Colour	Coats	% Loss factor	DFT (µm)	WFT (µm)	PSR (m ² /lt)	Hard Dry 5°C	Overcoating 5°C		Thinner	Cleaner	Volume (lt)
								Min	Max			
Intershield 300	Bronze	5% TU	30	150	250	2.80	8hrs	9hrs	5days	GTA220	GTA220, GTA822	4.5
Interthane 990	Lt Wthr wrk Grey	5% TU	40	50	88	6.84	24hrs	24hrs	ext.	GTA056, GTA713, GTA733	GTA056, GTA713, GTA733	1.8
Interthane 990	Lt Wthr wrk Grey	FC	40	50	88	6.84	24hrs	24hrs	ext.	GTA056, GTA713, GTA733	GTA056, GTA713, GTA733	36.5
				250	426							42.8

Marine Coatings

Unless otherwise agreed in writing, all products supplied and technical advice given by us are subject to our standard terms and conditions of sale. Please note that a surcharge may be applied to the prices listed, in which case this will be notified to you by your International Paint representative. In the event that supplies are made and technical advice is given by one of our associated companies then such supplies and technical advice shall be subject to the standard terms of sale of that company, a copy of which is available upon request

GBMG1-3CGP-7G9Y/1
05-Sep-2019
6
SEARCHER

AkzoNobel

External Decks [200 m²]

An Intershield 300 tar free high solids epoxy anticorrosive scheme with an Intershield 851 epoxy non skid finish coat.

Surface Preparations

Fresh water wash to remove all dirt and contamination, as necessary. Degrease according to SSPC-SP1 solvent cleaning. Ensure area is clean and dry prior to application.

Slurry blasting to International Paint SB2½M standard (Sa2½ equivalent with moderate flash rusting).

Ensure all surfaces are clean, dry and free of contamination prior to the application of each coat of the specified paint scheme.

Product	Colour	Coats	% Loss factor	DFT (µm)	WFT (µm)	PSR (m²/lit)	Hard Dry 5°C	Overcoating 5°C		Thinner	Cleaner	Volume (lt)
								Min	Max			
Intershield 300	Bronze	FC	30	150	250	2.80	8hrs			GTA220	GTA220, GTA822	71.4
Intershield 851	Extra Dk Sea Grey	FC	30	300	390	1.80				GTA220	GTA220	111.1
Intershield 851	Extra Dk Sea Grey	FC	30	300	390	1.80				GTA220	GTA220	111.1
				750	1,030							293.6

Marine Coatings

Unless otherwise agreed in writing, all products supplied and technical advice given by us are subject to our standard terms and conditions of sale. Please note that a surcharge may be applied to the prices listed, in which case this will be notified to you by your International Paint representative. In the event that supplies are made and technical advice is given by one of our associated companies then such supplies and technical advice shall be subject to the standard terms of sale of that company, a copy of which is available upon request

GBMG1-3CGP-7G9Y/1
05-Sep-2019
7
SEARCHER

AkzoNobel

Deck Fittings and Equipment [50 m²]

An Intershield 300 abrasion resistant epoxy scheme

Surface Preparations

Fresh water wash to remove all dirt and contamination, as necessary. Degrease according to SSPC-SP1 solvent cleaning. Ensure area is clean and dry prior to application.

Spot mechanically prepare the surface using an aluminium oxide abrasive disk (24-30 grit) to give a heavily scored surface profile of 50-75 microns (2-3 mils). Ensure the area is clean and dry and apply initial coat within 6-8 hours.

Feather or chip back surrounding area to a sound edge. Overlap onto existing sound coatings by 2-3 cms.

Product	Colour	Coats	% Loss factor	DFT (µm)	WFT (µm)	PSR (m ² /lt)	Hard Dry 5°C	Overcoating 5°C		Thinner	Cleaner	Volume (lt)
								Min	Max			
Intershield 300	Bronze	5% TU	30	150	250	2.80	8hrs	9hrs	5days	GTA220	GTA220, GTA822	0.9
Interthane 990	Lt Wthr wrk Grey	5% TU	40	50	88	6.84	24hrs	24hrs	ext.	GTA056, GTA713, GTA733	GTA056, GTA713, GTA733	0.4
Interthane 990	Lt Wthr wrk Grey	FC	40	50	88	6.84	24hrs	24hrs	ext.	GTA056, GTA713, GTA733	GTA056, GTA713, GTA733	7.3
				250	426							8.6

Marine Coatings

Unless otherwise agreed in writing, all products supplied and technical advice given by us are subject to our standard terms and conditions of sale. Please note that a surcharge may be applied to the prices listed, in which case this will be notified to you by your International Paint representative. In the event that supplies are made and technical advice is given by one of our associated companies then such supplies and technical advice shall be subject to the standard terms of sale of that company, a copy of which is available upon request

GBMG1-3CGP-7G9Y/1
05-Sep-2019
8
SEARCHER

AkzoNobel

Freshwater Tanks [20 m²]

An Interline 925, high performance epoxy scheme certified for the carriage of potable water.

Surface Preparations

Fresh water wash to remove all dirt and contamination, as necessary. Degrease according to SSPC-SP1 solvent cleaning. Ensure area is clean and dry prior to application.

Only for areas of less than 0.5 square metres.

Prepare bare areas of steel to a minimum of St2 ISO 8501-1 (SSPC-SP2). Feather or chip back surrounding area to a sound edge.

Product	Colour	Coats	% Loss factor	DFT (µm)	WFT (µm)	PSR (m²/lit)	Hard Dry 5°C	Overcoating 5°C		Thinner	Cleaner	Volume (lt)
								Min	Max			
Interline 925	White	25% TU	30	300	300	2.33					GTA415, GTA822	2.1
				300	300							2.1

Sewage Tank Repairs [20 m²]

An Intershield 300 abrasion resistant epoxy scheme

Surface Preparations

Fresh water wash to remove all dirt and contamination, as necessary. Degrease according to SSPC-SP1 solvent cleaning. Ensure area is clean and dry prior to application.

Spot mechanically prepare the surface using an aluminium oxide abrasive disk (24-30 grit) to give a heavily scored surface profile of 50-75 microns (2-3 mils). Ensure the area is clean and dry and apply initial coat within 6-8 hours.

Feather or chip back surrounding area to a sound edge. Overlap onto existing sound coatings by 2-3 cms.

Product	Colour	Coats	% Loss factor	DFT (µm)	WFT (µm)	PSR (m²/lit)	Hard Dry 5°C	Overcoating 5°C		Thinner	Cleaner	Volume (lt)
								Min	Max			
Intershield 300	Bronze	5% TU	40	150	250	2.40	8hrs	9hrs	6mths	GTA220	GTA220, GTA822	0.4
Intershield 300	Bronze	5% TU	40	150	250	2.40	8hrs	9hrs	6mths	GTA220	GTA220, GTA822	0.4
				300	500							0.8

Marine Coatings

Unless otherwise agreed in writing, all products supplied and technical advice given by us are subject to our standard terms and conditions of sale. Please note that a surcharge may be applied to the prices listed, in which case this will be notified to you by your International Paint representative. In the event that supplies are made and technical advice is given by one of our associated companies then such supplies and technical advice shall be subject to the standard terms of sale of that company, a copy of which is available upon request

GBMG1-3CGP-7G9Y/1
05-Sep-2019
9
SEARCHER

AkzoNobel

Thinners			
Product	Colour	Sales Code	Volume (lt)
International		GTA007	25.0
International		GTA220	25.0
International		GTA713	10.0
Total			60.0

Marine Coatings

Unless otherwise agreed in writing, all products supplied and technical advice given by us are subject to our standard terms and conditions of sale. Please note that a surcharge may be applied to the prices listed, in which case this will be notified to you by your International Paint representative. In the event that supplies are made and technical advice is given by one of our associated companies then such supplies and technical advice shall be subject to the standard terms of sale of that company, a copy of which is available upon request

GBMG1-3CGP-7G9Y/1
05-Sep-2019
10
SEARCHER

Product List				
Product	Colour	Sales Code	Volume Solids (%)	Volume (lt)
Intergard 263	Light Grey	FAJ034/FAA262	57	40.0
Interline 925	White	THA125/THA127	100	2.1
Intershield 300	Bronze	ENA300/ENA303	60	227.5
Intershield 851	Extra Dk Sea Grey	ADA172/ADA174	77	230.0
Interspeed 6400	Red	BQA644	60	60.0
Interthane 990	Black	PHY999/PHA046	57	5.0
Interthane 990	Lt Wthr wrk Grey	PHZ684/PHA046	57	100.0
Trilux 33	Black	YBA067	45	20.0
Trilux 33	White	YBA068	45	5.0
Total				689.6

Thinners				
Product	Colour	Sales Code	Volume Solids (%)	Volume (lt)
International		GTA007	—	25.0
International		GTA220	—	25.0
International		GTA713	—	10.0
Total				60.0

Total volume (lt): 749.6

Marine Coatings

Unless otherwise agreed in writing, all products supplied and technical advice given by us are subject to our standard terms and conditions of sale. Please note that a surcharge may be applied to the prices listed, in which case this will be notified to you by your International Paint representative. In the event that supplies are made and technical advice is given by one of our associated companies then such supplies and technical advice shall be subject to the standard terms of sale of that company, a copy of which is available upon request

GBMG1-3CGP-7G9Y/1
05-Sep-2019
11
SEARCHER

AkzoNobel

Application Notes

The dry film thickness of coatings specified can be achieved by Airless spray. Brushing, rolling and conventional spray application may require multiple coats to achieve the specified thickness.

Quantities and costs shown here are estimates and should only be taken as a guide. Paint consumption in practice will vary according to the actual film thickness applied and the loss factor incurred. These will be affected by wastage, surface profile and surface complexity.

Thinning of products is not recommended without prior consultation with International representatives.

NB: When using any type of paint in confined spaces, forced ventilation is required; for further information, please contact International representatives.

Marine Coatings

Unless otherwise agreed in writing, all products supplied and technical advice given by us are subject to our standard terms and conditions of sale. Please note that a surcharge may be applied to the prices listed, in which case this will be notified to you by your International Paint representative. In the event that supplies are made and technical advice is given by one of our associated companies then such supplies and technical advice shall be subject to the standard terms of sale of that company, a copy of which is available upon request

GBMG1-3CGP-7G9Y/1
05-Sep-2019
12
SEARCHER

Terms and Conditions

This confidential document is for the use of the above named client and its contents should not be reproduced or transmitted without prior written permission from International Paint. The information is given in good faith and attention to the following statement :

The information given in this report is not intended to be exhaustive and any person using any products for any purpose other than that specifically recommended in this report without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. Any warranty, if given, or specific Terms & Conditions of Sale are contained in International Paints Terms and Conditions of Sale, a copy of which can be obtained on request. Whilst we endeavour to ensure that all advice we give about the product (whether in this report or otherwise) is correct we have no control over either the quality or condition of the substrate or the many factors affecting the use and application of this product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever for howsoever arising for the performance of our products or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of the product. The information contained in this report is liable to modification from time to time in the light of experience and our policy of continuous product development.

It is the user's responsibility to check that upto date product data sheets are obtained prior to using the products and that local environmental controls that may be in force are observed when using any of our products.

Health & Safety

Products referred to in this report are intended for use only by professional applicators in industrial situations in accordance with the advice given on our Technical Datasheetst, the Material Safety Data Sheet and the container(s), and should not be used without reference to the Material Safety Data Sheet (MSDS).

All work involving the application and use of this product should be performed in compliance with all relevant national Health, Safety & Environment standards and regulations.

In the event welding or flame cutting is performed on metal coated with this product, dust and fumes will be emitted which will require the use of appropriate personal protective equipment and adequate local exhaust ventilation.

If in doubt regarding the suitability of use of this product, consult International Paint for further advice.

Marine Coatings

Unless otherwise agreed in writing, all products supplied and technical advice given by us are subject to our standard terms and conditions of sale. Please note that a surcharge may be applied to the prices listed, in which case this will be notified to you by your International Paint representative. In the event that supplies are made and technical advice is given by one of our associated companies then such supplies and technical advice shall be subject to the standard terms of sale of that company, a copy of which is available upon request

GBMG1-3CGP-7G9Y/1
05-Sep-2019
13
SEARCHER

Terms and Conditions of Sale

1. **SCOPE:** "AkzoNobel" means the AkzoNobel entity identified above; "Buyer" means the purchaser of Products from AkzoNobel and "Products" means any and all goods sold by AkzoNobel to Buyer. Unless a detailed product sales agreement is in place between AkzoNobel and Buyer covering the sale of the Products, all Products sold or otherwise provided by AkzoNobel are sold or provided exclusively on the basis of these Terms and Conditions of Sale. No differing or supplemental terms or conditions shall be applicable unless expressly agreed to by AkzoNobel in writing.
2. **OFFER / ACCEPTANCE:** A quotation from AkzoNobel does not constitute an offer but an invitation to Buyer to make an offer. In all cases Buyer's offer shall be deemed based on these Terms and Conditions of Sale. An agreement comes into effect only when AkzoNobel accepts Buyer's offer.
3. **DELIVERY / TRANSFER OF RISK:** Delivery terms shall be interpreted in accordance with the latest INCOTERMS valid at the date the order is accepted. Unless otherwise agreed to by AkzoNobel in writing the delivery term is EXW and risk of loss in the Products will transfer to Buyer upon tender of the Products to Buyer or the carrier at AkzoNobel's shipping facility.
4. **QUANTITY VARIATIONS:** Buyer will pay for the quantity delivered and may not reject any delivery of Product on the grounds of variation of quantity where such variation is not more than 10% of the quantity ordered.
5. **PRICE AND PAYMENT:** Unless otherwise agreed by the Parties, the price for the Products will be the price quoted by AkzoNobel. All prices quoted by AkzoNobel are exclusive of value added tax and any other tax that may apply in respect of the Products. AkzoNobel will issue invoices to Buyer for all Products sold to Buyer. Buyer shall pay these invoices within 30 days from the invoice date in the currency indicated on the invoice at the address of AkzoNobel indicated on the invoice. Buyer may not withhold payment of any amount due to AkzoNobel because of any set-off, counter-claim, abatement or similar deduction. Upon demand Buyer will immediately reimburse AkzoNobel for any and all costs including fees for collection agencies and attorneys incurred or expended by AkzoNobel to collect any amounts due from Buyer. Late payments shall automatically and without prior notice, bear interest at an annual rate equivalent to the applicable to the prime lending rate of the central bank authority of the country where the document has been created in for the relevant period, calculated from the due date, then and without prejudice to the exercise of any other rights or remedies which may be available to it and without incurring any penalties or liabilities. AkzoNobel shall be entitled to suspend performance of its obligations under the contract, following written notification to the Buyer, until payment in full of the outstanding amounts in respect of the supply of the Products actually delivered and rendered and not paid for.
6. **RETENTION OF TITLE:** Risk of loss will transfer to the buyer in accordance with the delivery terms. If permitted under applicable law, AkzoNobel retains a security interest in all products delivered to buyer to secure payment in full of all amounts due to AkzoNobel. In such a case title to products passes to buyer (subject to AkzoNobel's security interest) at the time risk of loss passes to buyer. In all other cases title in products will remain vested with AkzoNobel and until payment in full is made by Buyer, the Buyer will hold the products in trust for AkzoNobel and AkzoNobel will have the right to enter the premises of Buyer to collect any products to which it holds title pursuant to this section 6. In either case Buyer may sell the products in the ordinary course of its business but may not pledge, mortgage or otherwise encumber products prior to payment in full of the purchase price.
7. **WARRANTY / BUYER'S RIGHTS:** AkzoNobel warrants to Buyer that at the time of transfer of risk of loss the Products conform to AkzoNobel's standard Product specifications or such other specifications as AkzoNobel and Buyer have expressly agreed to in writing (the "Specifications"). THIS WARRANTY IS THE SOLE WARRANTY GIVEN BY AKZONOBEL. AKZONOBEL MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, ORAL OR WRITTEN, WITH RESPECT TO THE PRODUCTS, THE APPLICATION OR USE THEREOF, OR OTHERWISE, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT, EACH OF WHICH IS SPECIFICALLY DISCLAIMED. In the event Products do not comply with the foregoing warranty, AkzoNobel will, at its option, repair or replace such Products or refund the Price of the Products and, having done so, will have no further liability. Buyer must notify AkzoNobel of any claim Products do not comply with the foregoing warranty within seven (7) days after Buyer becomes aware of such claim but in no event later than thirty (30) days after delivery of the Product to Buyer. Buyer's failure to notify AkzoNobel of any such claim within the time set out in the preceding sentence will constitute a waiver by Buyer of such claim. AkzoNobel makes no warranty of any kind with respect to any services provided to Buyer and shall have no liability with respect to such services.
8. **LIMITATION OF LIABILITY:** AkzoNobel will not be liable for any loss or damage caused by Buyer's failure to exercise effective quality control or the failure to store, use or otherwise handle the Products as advised or in accordance with instructions provided by AkzoNobel or industry standards. AKZONOBEL WILL NOT BE LIABLE TO BUYER, WHETHER IN CONTRACT, TORT (INCLUDING NEGLIGENCE), BREACH OF STATUTORY DUTY OR OTHERWISE FOR ANY LOSS OF PROFIT, LOSS OF BUSINESS, DIMINUTION IN VALUE, OR DEPLETION OF GOODWILL OR ANY INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, PUNITIVE, OR CONSEQUENTIAL LOSS OR DAMAGE. AKZONOBEL'S AGGREGATE LIABILITY TO BUYER IN RESPECT OF ALL LOSSES ARISING UNDER OR IN CONNECTION WITH THE SUPPLY OF

Marine Coatings

Unless otherwise agreed in writing, all products supplied and technical advice given by us are subject to our standard terms and conditions of sale. Please note that a surcharge may be applied to the prices listed, in which case this will be notified to you by your International Paint representative. In the event that supplies are made and technical advice is given by one of our associated companies then such supplies and technical advice shall be subject to the standard terms of sale of that company, a copy of which is available upon request

GBMG1-3CGP-7G9Y/1
05-Sep-2019
14
SEARCHER



Terms and Conditions of Sale

PRODUCTS WILL IN NO WAY EXCEED THE PRICE OF THE PRODUCTS PURCHASED, OR €1.000,000, WHICHEVER IS LOWER. Nothing in this section will limit or exclude AkzoNobel's liability for any matter in respect of which it is unlawful for AkzoNobel to exclude or restrict its liability.

9. **FORCE MAJEURE:** AkzoNobel will not be liable in any respect for failure to perform its obligations if hindered or prevented, directly or indirectly by war (declared or undeclared), national emergency, inadequate transportation facilities, machinery or equipment failure, AkzoNobel's inability to secure materials, supplies, fuel or power for the manufacture of Product on terms and conditions that are acceptable to AkzoNobel, fire, flood, windstorm or other act of God, strike, lockout or other labour dispute, order or act of any government, whether foreign, national or local, whether valid or invalid, or any other cause of like or different kind beyond the reasonable control of AkzoNobel (each a "Force Majeure"). AkzoNobel shall have no obligation to procure any Products from other sources and may allocate its available supply of Products among the members of the AkzoNobel Group (including itself) and their customers, buyers, distributors and resellers on whatever basis AkzoNobel may deem fair and practical. In the event that the duration of a Force Majeure exceeds six (6) months or is reasonably expected to exceed 6 months, AkzoNobel is entitled to withdraw from any obligation it may have to supply the Products to Buyer without the Buyer having any right to compensation.
10. **EXPORT CONTROL:** Buyer will not sell, export, re-export, license, transmit, divert or otherwise transfer, directly or indirectly, any Product or any information or technology related to the Product except in accordance with applicable laws and regulations, including without limitation applicable UN, US and EU export control laws and regulations and the laws and regulations of the country where Buyer is resident. Buyer acknowledges that it will (i) take all steps necessary to comply with the above laws and regulations, including obtaining export and other licenses if necessary and (ii) not take any actions that would cause AkzoNobel to be in violation of the above laws.
11. **TERMINATION:** An agreement with Buyer to deliver Products on the basis of these Terms and Conditions will not oblige AkzoNobel for the future to take further orders. AkzoNobel will at all times be entitled to end the relationship. Such termination will never entitle Buyer to compensation.
12. **LAW AND DISPUTE RESOLUTION.** These Terms and Conditions and all disputes between AkzoNobel and Buyer are governed by the laws of the country and, if applicable, state or province, in which AkzoNobel's address is located, excluding the United Nations Convention of Contracts for the International Sale of Goods and any choice of law rules that direct the application of the law of any other jurisdiction. Any dispute between AkzoNobel and Buyer that the parties are unable to resolve by agreement will be resolved exclusively in the courts having jurisdiction over the subject matter of the dispute located in the city in which AkzoNobel's address is located (or if no such courts exist in such city in such courts as are located closest to such city) and those courts having appellate level review over the decisions and rulings of such courts. Each party consents and agrees to the jurisdiction and venue of such courts.

Marine Coatings

Unless otherwise agreed in writing, all products supplied and technical advice given by us are subject to our standard terms and conditions of sale. Please note that a surcharge may be applied to the prices listed, in which case this will be notified to you by your International Paint representative. In the event that supplies are made and technical advice is given by one of our associated companies then such supplies and technical advice shall be subject to the standard terms of sale of that company, a copy of which is available upon request

GBMG1-3CGP-7G9Y/1
05-Sep-2019
15
SEARCHER