


## Notes

- 1. Batten Roof 25 x 50mm Roofing batten
- 2. Batten Treated 45mm x 45mm Painted Black S/S Fixing @ 400 Centres
- 3. Batten Treated Counter 45mm x 45mm Painted Black S/S Fixing @ 400 Centres
- 4. Cladding Timber 20x65mm with 10mm gaps between boards Larch Vertical
- 5. Finish Ceiling Wood Fibre Acoustic Ceiling 25 mm Heradesign
- 6. Insulation warmcel blown in cellulose
- 7. Insulation Wood Fibre Pavatex Isolair T&G Board 60mm
- 8. Roof 13/3 0.7 Thick PVC Plastisol Coated Barge Flashing 150mm x 150mm
- 9. Roof 13/3 Corrugated 0.7 Thick PVC Plastisol Coated Roof Sheet
- 10.Timber Frame I-Joist 300mm
- 11.Timber Frame M+E Service Void 25mm
- 12.Timber Frame Medite Smartply Airtight Sheathing Board
- 13. Timber Frame Sheathing Medite Smartply Airtight 12.5mm
- 14.Timber Frame LVL STEICOwall 300x45mm

## **MEMBRANES KEY:**

All membranes are to be fully taped and lapped with proprietary tape as per the Architectural Specification and manufacturers standards and guidance.





300 mm

copyright Kast Architects Limited - all rights reserved

Do not scale this drawing for construction purposes. Check all dimensions on site. If in doubt ask.