

## Project name

**Leybourne Village Hall West Malling****As designed****Date:** Mon Oct 08 10:40:57 2018**Administrative information****Building Details****Address:** Leybourne Village Hall, Little Market Row, West Malling, ME19 5QL, ME19 5QL**Owner Details****Name:** -**Telephone number:** -**Address:** -, -, -**Certification tool****Calculation engine:** Apache**Calculation engine version:** 6.4.0.15**Interface to calculation engine:** IES Virtual Environment**Interface to calculation engine version:** 6.4.0.15**BRUKL compliance check version:** v4.1.g.0**Certifier details****Name:** Miquel Garcia**Telephone number:** 0114 228 3300**Address:** 81 Burton Road, Sheffield, Postcode**Criterion 1: The calculated CO<sub>2</sub> emission rate for the building should not exceed the target**

1.1	CO <sub>2</sub> emission rate from the notional building, kgCO <sub>2</sub> /m <sup>2</sup> .annum	22.6
1.2	Target CO <sub>2</sub> emission rate (TER), kgCO <sub>2</sub> /m <sup>2</sup> .annum	22.6
1.3	Building CO <sub>2</sub> emission rate (BER), kgCO <sub>2</sub> /m <sup>2</sup> .annum	22.6
1.4	Are emissions from the building less than or equal to the target?	BER ≤ TER
1.5	Are as built details the same as used in the BER calculations?	Separate submission

**Criterion 2: The performance of the building fabric and the building services should achieve reasonable overall standards of energy efficiency****2.a Building fabric**

Element	U <sub>a</sub> -Limit	U <sub>a</sub> -Calc	U <sub>i</sub> -Calc	Surface where the maximum value occurs*
Wall**	0.35	0.17	0.17	RM00001A:Surf[0]
Floor	0.25	0.16	0.16	RM000002:Surf[6]
Roof	0.25	0.18	0.18	RM00001A:Surf[2]
Windows***, roof windows, and rooflights	2.2	2	2	RM000002:Surf[1]
Personnel doors	2.2	1.6	1.6	RM00000D:Surf[1]
Vehicle access & similar large doors	1.5	-	-	No Vehicle access doors in building
High usage entrance doors	3.5	-	-	No High usage entrance doors in building
U <sub>a</sub> -Limit = Limiting area-weighted average U-values [W/(m <sup>2</sup> K)] U <sub>a</sub> -Calc = Calculated area-weighted average U-values [W/(m <sup>2</sup> K)] U <sub>i</sub> -Calc = Calculated maximum individual element U-values [W/(m <sup>2</sup> K)] * There might be more than one surface where the maximum U-value occurs. ** Automatic U-value check by the tool does not apply to curtain walls whose limiting standard is similar to that for windows. *** Display windows and similar glazing are excluded from the U-value check. N.B.: Neither roof ventilators (inc. smoke vents) nor swimming pool basins are modelled or checked against the limiting standards by the tool.				

Air Permeability	Worst acceptable standard	This building
m <sup>3</sup> /(h.m <sup>2</sup> ) at 50 Pa	10	15*
* Buildings with less than 500 m <sup>2</sup> total useful floor area may avoid the need for a pressure test provided that the air permeability is taken as 15 m <sup>3</sup> /(h.m <sup>2</sup> ) at 50 Pa.		

## 2.b Building services

The building services parameters listed below are expected to be checked by the BCO against guidance. No automatic checking is performed by the tool.

Whole building lighting automatic monitoring & targeting with alarms for out-of-range values	NO
Whole building electric power factor achieved by power factor correction	<0.9

1- Heating gas boiler - Nat.Vent

Heating seasonal efficiency	Cooling nominal efficiency	SFP [W/(l/s)]	HR seasonal efficiency
0.91	-	0	-
Automatic monitoring & targeting with alarms for out-of-range values for this HVAC system			NO

2- Heating gas boiler - local extract fan

Heating seasonal efficiency	Cooling nominal efficiency	SFP [W/(l/s)]	HR seasonal efficiency
0.91	-	0	-
Automatic monitoring & targeting with alarms for out-of-range values for this HVAC system			NO

3- Heating gas boiler - zonal extract fan

Heating seasonal efficiency	Cooling nominal efficiency	SFP [W/(l/s)]	HR seasonal efficiency
0.91	-	0	-
Automatic monitoring & targeting with alarms for out-of-range values for this HVAC system			NO

"No HWS in project, or hot water is provided by HVAC system"

### Local mechanical ventilation and exhaust

Zone	Supply/extract SFP [W/(l/s)]	HR seasonal efficiency	Exhaust SFP [W/(l/s)]
z0-A02 Kitchen	-	-	0.4
z0-A19 WC/Dis	-	-	0.4
z0-A20 WC/Male	-	-	0.4
z0-A21 WC/Female	-	-	0.4
z0-A22 WC/Female	-	-	0.4

### General lighting and display lighting

Zone	General lighting [W]	Display lamps efficacy [lm/W]
z0-A01 Small Hall/Meeting Room	330	-
z0-A02 Kitchen	90	-
z0-A03 Corridor	20	-
z0-A03b Corridor	10	-
z0-A04 Stage/Main Hall	250	-
z0-A05 Bar	100	-
z0-A17 Corridors/Small Hall	60	-
z0-A18 Store bar	10	-
z0-A19 WC/Dis	20	-
z0-A20 WC/Male	30	-
z0-A21 WC/Female	10	-
z0-A22 WC/Female	10	-
z0-A23 Store	10	-
z0-A24 Store	20	-

### Criterion 3: The spaces in the building should have appropriate passive control measures to limit solar gains

Zone	Solar gain limit exceeded? (%)	Internal blinds used?
z0-A01 Small Hall/Meeting Room	NO (-42.9%)	NO
z0-A04 Stage/Main Hall	N/A	N/A
z0-A05 Bar	N/A	N/A

### Criterion 4: The performance of the building, as built, should be consistent with the BER

Separate submission

### Criterion 5: The necessary provisions for enabling energy-efficient operation of the building should be in place

Separate submission

### EPBD (Recast): Consideration of alternative energy systems

Were alternative energy systems considered and analysed as part of the design process?	NO
Is evidence of such assessment available as a separate submission?	NO
Are any such measures included in the proposed design?	NO

# Technical Data Sheet (Actual vs. Notional Building)

## Building Global Parameters

	Actual	Notional
Area [m <sup>2</sup> ]	257.4	257.4
External area [m <sup>2</sup> ]	743.6	743.6
Weather	LON	LON
Infiltration [m <sup>3</sup> /hm <sup>2</sup> @ 50Pa]	15	5
Average conductance [W/K]	165.53	260.43
Average U-value [W/m <sup>2</sup> K]	0.22	0.35
Alpha value* [%]	11.08	10

\* Percentage of the building's average heat transfer coefficient which is due to thermal bridging

## Building Use

### % Area Building Type

A1/A2 Retail/Financial and Professional services  
A3/A4/A5 Restaurants and Cafes/Drinking Est./Takeaways  
B1 Offices and Workshop businesses  
B2 to B7 General Industrial and Special Industrial Groups  
B8 Storage or Distribution  
C1 Hotels  
C2 Residential Inst.: Hospitals and Care Homes  
C2 Residential Inst.: Residential schools  
C2 Residential Inst.: Universities and colleges  
C2A Secure Residential Inst.  
Residential spaces  
D1 Non-residential Inst.: Community/Day Centre  
D1 Non-residential Inst.: Libraries, Museums, and Galleries  
D1 Non-residential Inst.: Education  
D1 Non-residential Inst.: Primary Health Care Building  
D1 Non-residential Inst.: Crown and County Courts  
**100 D2 General Assembly and Leisure, Night Clubs and Theatres**  
Others: Passenger terminals  
Others: Emergency services  
Others: Miscellaneous 24hr activities  
Others: Car Parks 24 hrs  
Others - Stand alone utility block

## Energy Consumption by End Use [kWh/m<sup>2</sup>]

	Actual	Notional
Heating	64.1	50.24
Cooling	0	0
Auxiliary	3.82	2.83
Lighting	13.85	20.54
Hot water	4.05	4.19
Equipment*	16.86	16.86
<b>TOTAL **</b>	<b>85.82</b>	<b>77.8</b>

\* Energy used by equipment does not count towards the total for calculating emissions.

\*\* Total is net of any electrical energy displaced by CHP generators, if applicable.

## Energy Production by Technology [kWh/m<sup>2</sup>]

	Actual	Notional
Photovoltaic systems	0	0
Wind turbines	0	0
CHP generators	0	0
Solar thermal systems	0	0

## Energy & CO<sub>2</sub> Emissions Summary

	Actual	Indicative Target
Heating + cooling demand [MJ/m <sup>2</sup> ]	187.38	150.79
Primary energy* [kWh/m <sup>2</sup> ]	121.11	123.77
Total emissions [kg/m <sup>2</sup> ]	22.6	22.6

\* Primary energy is net of any electrical energy displaced by CHP generators, if applicable.

HVAC Systems Performance										
System Type	Heat dem MJ/m2	Cool dem MJ/m2	Heat con kWh/m2	Cool con kWh/m2	Aux con kWh/m2	Heat SSEFF	Cool SSEER	Heat gen SEFF	Cool gen SEER	
[ST] Central heating using water: radiators, [HS] LTHW boiler, [HFT] Natural Gas, [CFT] Electricity										
Actual	277.8	0	95	0	2.5	0.81	0	0.91	0	
Notional	0	0	0	0	0	0	0	----	----	
[ST] Central heating using water: radiators, [HS] LTHW boiler, [HFT] Natural Gas, [CFT] Electricity										
Actual	33.7	0	11.5	0	29.4	0.81	0	0.91	0	
Notional	220.9	0	73.6	0	1.2	0.83	0	----	----	
[ST] Central heating using water: radiators, [HS] LTHW boiler, [HFT] Natural Gas, [CFT] Electricity										
Actual	545.3	0	186.5	0	22.4	0.81	0	0.91	0	
Notional	27.7	0	9.2	0	27.1	0.83	0	----	----	
[ST] No Heating or Cooling										
Actual	0	0	0	0	0	0	0	0	0	
Notional	462.5	0	154.1	0	19.3	0.83	0	----	----	

## Key to terms

Heat dem [MJ/m2]	= Heating energy demand
Cool dem [MJ/m2]	= Cooling energy demand
Heat con [kWh/m2]	= Heating energy consumption
Cool con [kWh/m2]	= Cooling energy consumption
Aux con [kWh/m2]	= Auxiliary energy consumption
Heat SSEFF	= Heating system seasonal efficiency (for notional building, value depends on activity glazing class)
Cool SSEER	= Cooling system seasonal energy efficiency ratio
Heat gen SSEFF	= Heating generator seasonal efficiency
Cool gen SSEER	= Cooling generator seasonal energy efficiency ratio
ST	= System type
HS	= Heat source
HFT	= Heating fuel type
CFT	= Cooling fuel type

# Key Features

The BCO can give particular attention to items with specifications that are better than typically expected.

## Building fabric

Element	U <sub>i-Typ</sub>	U <sub>i-Min</sub>	Surface where the minimum value occurs*
Wall	0.23	0.17	RM00001A:Surf[0]
Floor	0.2	0.16	RM000002:Surf[6]
Roof	0.15	0.18	RM00001A:Surf[2]
Windows, roof windows, and rooflights	1.5	2	RM000002:Surf[1]
Personnel doors	1.5	1.6	RM00000D:Surf[1]
Vehicle access & similar large doors	1.5	-	No Vehicle access doors in building
High usage entrance doors	1.5	-	No High usage entrance doors in building
U <sub>i-Typ</sub> = Typical individual element U-values [W/(m²K)]		U <sub>i-Min</sub> = Minimum individual element U-values [W/(m²K)]	
* There might be more than one surface where the minimum U-value occurs.			

Air Permeability	Typical value	This building
m³/(h.m²) at 50 Pa	5	15