

Fires Stratergy - Level 0

1:100

Revision	Date	Drawn by	Checked by
Р3	20/06/17	SOC	SOC
	ving site walk aroud		
Revision	Date	Drawn by	Checked by
P2	15/05/17	SOC	SOC
Notes updated			
Revision	Date	Drawn by	Checked by
P1	09/05/17	SOC	SOC
First issue			
Amendment			
Purpose of Issu	ie		
Prelimina	ary		
Project			
Mace			
DVSA Re	location		
Tyneside	House		
Drawing			
-	egy - Level 0	0	
riie su ai		-	
rii e Sti at	0,		
riie Strat	0,		
Drawing No.	<i></i>		

The use of this data by the recipient acts as an agreement of the following statements. Do

The controlled version of this drawing should be viewed in DWF or PDF format not DWG or

Where this drawing has been based upon Ordnance Survey data, it has been reproduced under the terms of Ryder Licence No. 100000144. Reproduction of this drawing in whole or

Do not scale the drawing. Use figured dimensions in all cases. Check all dimensions on

All drawings are based upon site information supplied by third parties and as such their accuracy cannot be guaranteed. All features are approximate and subject to clarification by a detailed topographical survey, statutory service enquiries and confirmation of the

not use this data if you do not agree with any of the following statements:-

other formats. All prints of this drawing must be made in full colour.

in part is prohibited without the prior permission of Ordnance Survey.

site. Report any discrepancies in writing to Ryder before proceeding.

Developed inline with information recieved from Environment Agency 5

Information on these drawings is limited and further investigation on site will be

Required Fire Compartmentation 30 minutes, opening up works required

Assumed existing Fire Compartmentation 60, opening up works required to

Existing assumed fire rated construction following site walk around. Any penetraions through fire rated compartments to be appropriately fire stopped. Inspection and opening up of partition required to determine fire rating of construction and any remdial works required to made good to ensure fire

Rockwool Ablative Batts and Rockwool Acoustic Intumescent Sealant

Cast iron/metal pipework penetrations through FR partitions

Ductwork penetrations through FR partitions - 60min compartment walls, 30min sub-compartment walls, 30min fire hazard room walls to be fire stopped with

(60min compartment walls, 30min sub-compartment walls, 30min fire hazard room

December 2016 -Existing Fire and Rescue Service drawings.

rating and intergity is maintained.

required to determine Proposed Fire Stratergy.

to verify fire rating.

verify fire rating.

Fire Stratergy:

info@ryderarchitecture.com www.ryderarchitecture.com

1:100

SOC

2788-01



SO P2