

8219 GREEN FIELDS PLAYING FIELDS, SAWTRY EXTENSION AND INTERNAL ALTERATIONS

Room Data Sheets

Revision A	First issue	230810



Contents Players Access / Corridor / Public Access 3 Kitchen 6 Female WC 10 Male WC 15 DDA WC 21 Store 26 Club Room 31 Plant Room External 34 Plant Room Internal 35 Team Changing / WC / Shower 38

44

50

NOTE: Security & Locking - To be confirmed by client.

Officials Changing / WC / Shower

Changing Places WC



Players Access / Corridor / Public Access

Location	Finish	Image / Product
Walls	All boards to have taped and filled joints ready to receive decoration. New walls Plastered/dry lined and fully sealed, Existing walls new skim coat. Paint all walls, including services and fittings with two coats vinyl matt emulsion and one mist coat on suitable undercoat / sealer. Colour: TBC by client ICI Dulux Paints.	
Floor		
	Polyflor Polysafe Hydro PUR R11 2mm vinyl. Colour: H4940 Tempered steel	
	Coved Skirtings 100mm upstand to match floor.	
	Internal and external corners to be mitred.	
	With a mastic sealant finish, colour to match sheet flooring	
	Gradus Esplanade 8500 barrier matting with black double wipers and	
	black anodised aluminium scraper linking strips to Player access (1240W x 1500 L) Public Access (1700 W x 1380 L) Supplied with edging strips, spacer strips and divider bars sized to suite.	
	ELAR950 transition profile colour Lead (LRV: 12.77) refer gradus.com/elar950	
Ceiling	15mm British Gypsum Wallboard TEN and skim where indicated. Moisture resistant boards to be used.	
	All boards to have taped and filled joints ready to receive decoration.	
	One mist and two full coats matt emulsion paint; Allow for redecoration where corridor meets new lobby Pure brilliant white (1013V) - colour subject to client agreement.	



Players Access / Corridor / Public Access

Location	Finish	Image / Product
Door	Premdor solid core ash veneered faced flush doors, hardwood lippings, stainless steel ball race butt hinges. MDF door frame and stop. to meet door fire certificate requirement. Frame and stop finished with one coat primer, two coats undercoat and one coat high gloss white, ICI Dulux Paint. Please refer to project door schedule.	
Joinery	Skirting: 100 x 19 MDF skirting with round edge profile. Finished with one coat primer, two coats undercoat and one coat high gloss white. ICI Dulux Paint.	
	Please note that all internal and external joints are to be mitred	
	Architraves: 70 x 18mm MDF architraves with round edge profile. Architraves and trims are to be sanded down, knot, stop. Finished with with one coat primer, two coats undercoat and one coat high gloss white ICI Dulux Paint.	
	Please note that all internal and external joints are to be mitred	
	Window Board: Painted MDF with round edge profile. Size to suit opening on site. Finished with one coat primer, two coats undercoat and one coat high gloss white. ICI Dulux Paint.	
Fixtures, Fittings		
& Ironmongery	Pull Handles – A-Spec 22mm Bolt Fix Pull Handle - 250mm Centres - 316 Satin Stainless Steel, installed 1500mm from FFL to centre of handle. Ironmongery Direct Ref: 849641	
	Butt Hinges – Enduro Radius twin ball bearing c/w hinge plates, satin stainless steel, 3 x 76 x 102mm, Ironmongery Direct ref: 298935	

4



Players Access / Corridor / Public Access

Location	Finish	Image / Product
F: F:::::		1
Fixtures, Fittings & Ironmongery continued		
	Kick Plates – Satin Anodised Aluminium, 825mm (to both sides), TP Ref: 523494	
	Push Plate – Satin anodised aluminium, 300 x 73mm, TP Ref: 802531	PUSH
	Fire Door Keep Shut sign, satin anodised aluminium, 75mm dia., Wickes Ref: 229112	Fire door keep shut
	Fire Door Keep Clear sign, satin anodised aluminium, 75mm dia., Direct Signs, Ref: PA11-SAA, or similar and approved.	Fire door Keep clear
	Door Stop – Oval satin anodised aluminium, TP Ref: 802541	



Kitcher

Location	Finish	Image / Product
Walls	15mm British Gypsum Wallboard TEN and skim where indicated. Moisture resistant boards to be used. One mist and two full coats vinyl silk emulsion paint; Chalk Blush 4 (Off white 50YR 83/010) - colour subject to client agreement.	
	Glasroc H Tilebacker board. Wet areas in kitchen;	
	Splash back over all benching Brick effect tile to be 200 x 100 and taken 500mm high. Colour subject to client agreement - see adjacent colour suggestion. tile trim, to all leading edges; extent to full width/length of worktops and sinks. splashback;	
	Tile edgings to be Durosol Aluminium Natural tile edging. Grout colour to be white	
Floor	Vinyl Sheet flooring; Polyflor Apex – colour 'Breccia', 4204 (LRV: 18) Colour subject to client agreement. Internal and external corners to be mitred.	
	With a mastic sealant finish, colour to match sheet flooring Gradus SO100 skirting or similar. Colour 'Mist' (LRV: 58.74), subject to client agreement – must have 30pt colour contrast.	
Calling	15 years Dritish Course was Wellle a good TEN and deline	
Ceiling	15mm British Gypsum Wallboard TEN and skim where indicated. Moisture resistant boards to be used. All boards to have taped and filled joints ready to receive decoration. One mist and two full coats matt emulsion paint; Pure brilliant white (1013V) - colour subject to client agreement.	



Kitchen

Location	Finish	Image / Product
Doors	Premdor solid core ash veneered faced flush doors, hardwood lippings, stainless steel ball race butt hinges. MDF door frame and stop. to meet door fire certificate requirement. Frame and stop finished with one coat primer, two coats undercoat and one coat high gloss white, ICI Dulux Paint. Please refer to project door schedule.	
Joinery	Architraves: 70 x 18mm MDF architraves with round edge profile. Architraves and trims are to be sanded down, knot, stop. Finished with with one coat primer, two coats undercoat and one coat high gloss. Please note that all internal and external joints are to be mitred	
	Window Board: Painted MDF with round edge profile. Size to suit opening on site. Finished with one coat primer, two coats undercoat and one coat high gloss white. ICI Dulux Paint.	
Fixtures, Fittings & Ironmongery	Kitchen base units, worktop, sink and taps all subject to client agreement. Kitchen worktop – 38 x 600mm mm laminated worktop. Colour: Patmos. TP Ref: 531643	
	Kitchen wall and base units – TP Dakota range. Colour: White. Base Sink Unit 1000mm. Ref: 743434 Base Units 500mm. Ref: 355301 Wall Units 500mm. Ref: 743509	
	TP Eclipse 1.0B LH stainless steel sink. TP Ref: 478911	



Kitcher

Location	Finish	Image / Product
Fixtures, Fittings & Ironmongery	Iflo Lever Deck Mixer tap. Finish: Chrome. TP Ref: 604579	Da
	T Bar, stainless steel handles.	
	600 Under-mounted electric fan oven to client spec.	
	600 Counter top hob to client spec.	
	600 Ducted extract hood to client spec.	
	Refer to indicative kitchen schedule.	
	Dishwasher, under counter drinks fridge, fridge, cooker, hob and hood subject to client agreement.	
	Please refer to door detail information.	
	Handle & digital lock to be interlinked with fire alarm system.	
	Kick Plates – Satin Anodised Aluminium, 825mm (to both sides), TP Ref: 523494	



Kitcher

Location	Finish	Image / Product
Fixtures,		
Fittings & Ironmongery	Butt Hinges – Enduro Radius twin ball bearing c/w hinge plates, satin stainless steel, 3 x 76 x 102mm, Ironmongery Direct ref: 298935	
	Overhead Closer – Rutland TS9205 satin nickel, Ironmongery Direct ref: 448049	
	Push Plate – Satin anodised aluminium, 300 x 73mm, TP Ref: 802531	PUSH
	Fire Door Keep Shut sign, satin anodised aluminium, 75mm dia., Wickes Ref: 229112	Fire door keep shut
	Fire Door Keep Clear sign, satin anodised aluminium, 75mm dia., Direct Signs, Ref: PA11-SAA, or similar and approved.	Fire door Keep clear
	Door Stop – Oval satin anodised aluminium, TP Ref: 802541	
	MDF panel painted white with 6 no coat hooks. TP 4Trade coat hook, satin anodised aluminium, TP Ref: 796125	

9



Location	Finish	Image / Product
Walls	15mm British Gypsum Wallboard TEN and skim where indicated. Moisture resistant boards to be used.	
	Glasroc H Tilebacker board.	
	Solus 'Revolution' range porcelain tiles - to cover full height of all walls. Colour 'Evolutionary'. 300 x 600 x 9mm Natural R10 Product code: 2KAN102.	
	Tile edgings to be Durosol Aluminium Natural tile edging.	7775
	Grout colour to be white	
	IPS Panelling: Duct panel and frame set, to be full height. By Cubicle Systems, Premier Full Height (SGL) Access panels: SGL 13mm, with routered edges and black core.	
	Colours to be: Cloud, VEN351 LRV 58 Pacific, VEN353 LRV 20	
	Surrounds: SGL 13mm, , with routered edges and black core.	
Floor		
	Polyflor Safety - Polysafe Quattro PUR. Colour: 'Coastal Flint'. Colour subject to client agreement.	
	Internal and external corners to be mitred.	
	With a mastic sealant finish, colour to match sheet flooring	
	Gradus SO 100 skirting or similar. Colour Colour: 'Coastal Flint'. subject to client agreement – must have 30pt colour contrast.	



Location	Finish	Image / Product
Ceiling	15mm British Gypsum Wallboard TEN and skim where indicated. Moisture resistant boards to be used. All boards to have taped and filled joints ready to receive decoration. One mist and two full coats matt emulsion paint; Pure brilliant white (1013V) - colour subject to client agreement.	
Doors, continued	Premdor solid core ash veneered faced flush doors, hardwood lippings, stainless steel ball race butt hinges. MDF door frame and stop. to meet door fire certificate requirement.	
	Frame and stop finished with one coat primer, two coats undercoat and one coat high gloss Gris Perle RAL 7040 (BS 18 B 19). ICI Dulux Paint.	
	Please refer to project door schedule.	
Joinery	Architraves: 70 x 18mm MDF architraves with round edge profile. Architraves and trims are to be sanded down, knot, stop. Finished with with one coat primer, two coats undercoat and one coat high gloss Gris Perle RAL 7040 (BS 18 B 19). ICI Dulux Paint.	
	Please note that all internal and external joints are to be mitred	
Fixtures, Fittings & Ironmongery	700x450mm acrylic mirrors with chrome dome headed screws above each wash hand basin.	
	1 no Pro Coat Hook per cubicle, satin anodised aluminium, by Ironmongery Direct or similar and approved, Ref: 357529	

11



Location	Finish	Image / Product
Fixtures, Fittings & Ironmongery continued	Biodryer Biolite Eco hand dryer – Colour: White. By M&E subcontractor.	
	i.life A Back To Wall Toilet With RimLS+ Technology, Ideal Standard Ref: E2474(01) (white)	
	Palm push button pneumatic, stainless steel for 31mm maximum thickness partition	,
	Connect Air 54cm Short Projection Vanity Washbasin, 1 taphole with overflow. Ideal Standard Ref: E0296(01)	
	By M&E subcontractor.	
	Venesta HPL double vanity unit or similar	
	Taps - 2 no. SCBW113 Sanceram Thermostatic Mixing Valves Recommended safe hot water temperature for washbasin - maximum 41°C. By M&E subcontractor.	
	Door and wall grab rails: NRS Healthcare Plastic Fluted Grab Rail - White - 600mm, contrasting colour. Complete Care Ref: F19480	
	NRS Healthcare Plastic Fluted Grab Rail - Blue - 600mm, contrasting colour. Complete Care Ref: L30519	3
	Please refer to door detail information	



Location	Finish	Image / Product
Fixtures, Fittings & Ironmongery, continued	Pull Handles – A-Spec 22mm Bolt Fix Pull Handle - 250mm Centres - 316 Satin Stainless Steel, installed 1500mm from FFL to centre of handle. Ironmongery Direct Ref: 849641 Butt Hinges – Enduro Radius twin ball bearing c/w hinge plates, satin stainless steel, 3 x 76 x 102mm, Ironmongery Direct ref: 298935	
	Overhead Closer – Rutland TS9205 satin nickel, Ironmongery Direct ref: 448049	
	Kick Plates – Satin Anodised Aluminium, 900mm, Ironmongery Direct, Ref: 170098 (to both sides)	
	Door Stop – Oval satin anodised aluminium, TP Ref: 802541	
	Push Plate – Satin anodised aluminium, 300 x 73mm, TP Ref: 802531	PUSH
	Please refer to door detail information.	
	Indicator bolt, satin, TP Ref: 726435	
	Lever Handles – Round bar rose latch handle, satin stainless steel 19mm, TP Ref: 274397	



Location	Finish	Image / Product
Fixtures, Fittings & Ironmongery, continued	Ladies Toilet Sign, satin anodised aluminium, 75mm dia., Direct Signs Ref: PA2-SAA, or similar and approved.	
	Fire Door Keep Shut sign, satin anodised aluminium, 75mm dia., Wickes Ref: 229112	Fire door keep shut
	Fire Door Keep Clear sign, satin anodised aluminium, 75mm dia., Direct Signs, Ref: PA11-SAA, or similar and approved.	Fire door Keep clear
	3 no. TORK SmartOne Toilet roll dispenser, Consortium	# ** ** ** ** ** ** ** ** ** ** ** ** **
	3 no. Consortium Soap Dispensers	



Location	Finish	Image / Product
Walls	15mm British Gypsum Wallboard TEN and skim where indicated. Moisture resistant boards to be used.	
	Glasroc H Tilebacker board.	
	Solus 'Revolution' range porcelain tiles - to cover full height of all walls. Colour 'Evolutionary'. 300 x 600 x 9mm Natural R10 Product code: 2KAN102.	
	Tile edgings to be Durosol Aluminium Natural tile edging.	7775
	Grout colour to be white	
	IPS Panelling: Duct panel and frame set, to be full height. By Cubicle Systems, Premier Full Height (SGL) Access panels: SGL 13mm, with routered edges and black core.	
	Colours to be: Cloud, VEN351 LRV 58 Pacific, VEN353 LRV 20	
	Surrounds: SGL 13mm, , with routered edges and black core.	
Floor		
	Polyflor Safety - Polysafe Quattro PUR. Colour: 'Coastal Flint'. Colour subject to client agreement.	
	Internal and external corners to be mitred.	
	With a mastic sealant finish, colour to match sheet flooring	
	Gradus SO 100 skirting or similar. Colour Colour: 'Coastal Flint'. subject to client agreement – must have 30pt colour contrast.	



Location	Finish	Image / Product
Ceiling	15mm British Gypsum Wallboard TEN and skim where indicated. Moisture resistant boards to be used. All boards to have taped and filled joints ready to receive decoration. One mist and two full coats matt emulsion paint; Pure brilliant white (1013V) - colour subject to client agreement.	
Doors, continued	Premdor solid core ash veneered faced flush doors, hardwood lippings, stainless steel ball race butt hinges. MDF door frame and stop. to meet door fire certificate requirement.	
	Frame and stop finished with one coat primer, two coats undercoat and one coat high gloss Gris Perle RAL 7040 (BS 18 B 19). ICI Dulux Paint.	
	Please refer to project door schedule.	
Joinery	Architraves: 70 x 18mm MDF architraves with round edge profile. Architraves and trims are to be sanded down, knot, stop. Finished with with one coat primer, two coats undercoat and one coat high gloss Gris Perle RAL 7040 (BS 18 B 19). ICI Dulux Paint.	
	Please note that all internal and external joints are to be mitred	
Fixtures, Fittings & Ironmongery	700x450mm acrylic mirrors with chrome dome headed screws above each wash hand basin.	
	1 no Pro Coat Hook per cubicle, satin anodised aluminium, by Ironmongery Direct or similar and approved, Ref: 357529	

16



Location	Finish	Image / Product
Fixtures, Fittings & Ironmongery continued	Biodryer Biolite Eco hand dryer – Colour: White. By M&E subcontractor.	
	i.life A Back To Wall Toilet With RimLS+ Technology, Ideal Standard Ref: E2474(01) (white)	
	Palm push button pneumatic, stainless steel for 31mm maximum thickness partition	,
	Connect Air 54cm Short Projection Vanity Washbasin, 1 taphole with overflow. Ideal Standard Ref: E0296(01)	
	By M&E subcontractor.	
	Venesta HPL double vanity unit or similar	
	Taps - 2 no. SCBW113 Sanceram Thermostatic Mixing Valves Recommended safe hot water temperature for washbasin - maximum 41°C. By M&E subcontractor.	
	Door and wall grab rails: NRS Healthcare Plastic Fluted Grab Rail - White - 600mm, contrasting colour. Complete Care Ref: F19480	
	NRS Healthcare Plastic Fluted Grab Rail - Blue - 600mm, contrasting colour. Complete Care Ref: L30519	3
	Please refer to door detail information	



Location	Finish	Image / Product
Fixtures, Fittings & Ironmongery, continued	Sanura Bowl Urinal 50cm, Ideal Standard Ref: S6100(01) domed waste, trap, hangers, exposed spreader top inlet and urinal flushpipes for use with 2 no. urinals	
	Regal Exposed Auto Cistern, Ideal Standard Ref: \$1128/\$1154/\$1129 (to be sized by M&E contractor)	
	Armitage Shanks Urinal Division Vitreous China - Hanger & Screw S612001, PlumbNation Ref: 138891	
	Pull Handles – A-Spec 22mm Bolt Fix Pull Handle - 250mm Centres - 316 Satin Stainless Steel, installed 1500mm from FFL to centre of handle. Ironmongery Direct Ref: 849641	
	Butt Hinges – Enduro Radius twin ball bearing c/w hinge plates, satin stainless steel, 3 x 76 x 102mm, Ironmongery Direct ref: 298935	
	Overhead Closer – Rutland TS9205 satin nickel, Ironmongery Direct ref: 448049	
	Kick Plates – Satin Anodised Aluminium, 900mm, Ironmongery Direct, Ref: 170098 (to both sides)	



Location	Finish	Image / Product
Fixtures, Fittings & Ironmongery, continued	Door Stop – Oval satin anodised aluminium, TP Ref: 802541	
	Push Plate – Satin anodised aluminium, 300 x 73mm, TP Ref: 802531	PUSH
	Please refer to door detail information.	
	Indicator bolt, satin, TP Ref: 726435	
	Lever Handles – Round bar rose latch handle, satin stainless steel 19mm, TP Ref: 274397	
	Mens Toilet Sign, satin anodised aluminium, 75mm dia., Direct Signs Ref: PA1-SAA, or similar and approved.	
	Fire Door Keep Shut sign, satin anodised aluminium, 75mm dia., Wickes Ref: 229112	Fire door keep shut
	Fire Door Keep Clear sign, satin anodised aluminium, 75mm dia., Direct Signs, Ref: PA11-SAA, or similar and approved.	Fire door Keep clear



Location	Finish	Image / Product
Fixtures, Fittings & Ironmongery, continued	3 no. TORK SmartOne Toilet roll dispenser, Consortium	2
	3 no. Consortium Soap Dispensers	



Location	Finish	Image / Product
Walls	15mm British Gypsum Wallboard TEN and skim where indicated. Moisture resistant boards to be used. All boards to have taped and filled joints ready to receive decoration. One mist and two full coats matt emulsion paint; Pure brilliant white (1013V) - colour subject to client agreement.	
Floor	Polyflor Homogeneous PUR Classic Mystique 2.5mm vinyl. Colour: Quartz 1400 Internal and external corners to be mitred. With a mastic sealant finish, colour to match sheet flooring Gradus SO100 skirting or similar. Colour Colour: 'Quartz 1400'. subject to client agreement – must have 30pt colour contrast.	
Ceiling	15mm British Gypsum Wallboard TEN and skim where indicated. Moisture resistant boards to be used. All boards to have taped and filled joints ready to receive decoration. One mist and two full coats matt emulsion paint; Pure brilliant white (1013V) - colour subject to client agreement.	
Doors	Premdor solid core ash veneered faced flush doors, hardwood lippings, stainless steel ball race butt hinges. MDF door frame and stop. to meet door fire certificate requirement. Frame and stop finished with one coat primer, two coats undercoat and one coat high gloss Gris Perle RAL 7040 (BS 18 B 19). ICI Dulux Paint. Please refer to project door schedule.	



Location	Finish	Image / Product
Joinery	Architraves: 70 x 18mm MDF architraves with round edge profile. Architraves and trims are to be sanded down, knot, stop. Finished with with one coat primer, two coats undercoat and one coat high gloss white ICI Dulux Paint.	
	Please note that all internal and external joints are to be mitred	
Fixtures, Fittings & Ironmongery	700x450mm acrylic mirrors with chrome dome headed screws above each wash hand basin.	
	1 no Pro Coat Hook per cubicle, satin anodised aluminium, by Ironmongery Direct or similar and approved, Ref: 357529	
	Biodryer Biolite Eco hand dryer – Colour: White. By M&E subcontractor.	Comma
	SanCeram Close Coupled WC Doc M Pack – Right handed pack (Includes Close coupled WC pan and cistern, WC seat, Single tap hole wash hand basin, Strainer waste, Bottle trap, TMV3 sequential mixer tap, 5 x Straight grab rails, 1 x Hinged grab rail). Colour white – subject to client agreement.	
	Consideration should be given to safe hot water delivery and the use of an appropriate temperature reduction device.	
	Iflo Cascada wash hand basin, 550 x 450mm, 2 tap holes. Ref: 685887. By M&E subcontractor.	
	tap holes. Ref: 685887. By M&E subcontractor.	



Location	Finish	Image / Product
Fixtures, Fittings & Ironmongery continued	Horizontal wall-mounted baby changing unit MH42, magrini.co.uk Door Stop – Oval satin anodised aluminium, TP Ref: 802541	
	Equality Act & BS8300 compliant lock and indicator bolt. Ironmongery Direct, Ref: 897694, or similar and approved.	
	Inclusive Toilet Sign, satin anodised aluminium, 75mm dia., Direct Signs, Ref: PA4-SAA, or similar and approved.	· L
	Unisex Toilet Sign, satin anodised aluminium, 75mm dia., Direct Signs, Ref: PA3-SAA, or similar and approved.	
	Baby Change Sign, satin anodised aluminium, 75mm dia., Direct Signs, Ref: PA13-SAA, or similar and approved.	₹ <u>.</u>
	Door grab rail, Rothley J404BW, 610mm, contrasting colour.	



Location	Finish	Image / Product
Fixtures, Fittings & Ironmongery continued	Fire Door Keep Shut sign, satin anodised aluminium, 75mm dia., Wickes Ref: 229112	Fire door keep shut
	Fire Door Keep Clear sign, satin anodised aluminium, 75mm dia., Direct Signs, Ref: PA11-SAA, or similar and approved.	Fire door Keep clear
	1 no. TORK SmartOne Toilet roll dispenser, Consortium	<u>a</u>
	2 no. Consortium Soap Dispensers	
	Pull Handles – A-Spec 22mm Bolt Fix Pull Handle - 250mm Centres - 316 Satin Stainless Steel, installed 1500mm from FFL to centre of handle. Ironmongery Direct Ref: 849641	
	Kick Plates – Satin Anodised Aluminium, 900mm, Ironmongery Direct, Ref: 170098 (to both sides)	
	Butt Hinges – Enduro Radius twin ball bearing c/w hinge plates, satin stainless steel, 3 x 76 x 102mm, Ironmongery Direct ref: 298935	



Location	Finish	Image / Product
Fixtures, Fittings & Ironmongery Continued	Push Plate – Satin anodised aluminium, 300 x 73mm, TP Ref: 802531	PUSH
	Overhead Closer – Rutland TS9205 satin nickel, Ironmongery Direct ref: 448049	



Store

Location	Finish	Image / Product
Walls	15mm British Gypsum Wallboard TEN and skim where indicated. Moisture resistant boards to be used.	
	All boards to have taped and filled joints ready to receive decoration.	
	One mist and two full coats matt emulsion paint; Pure brilliant white (1013V) - colour subject to client agreement.	
Floor	Polyflor Homogeneous PUR Classic Mystique 2.5mm vinyl. Colour: Quartz 1400	
Ceiling	15mm British Gypsum Wallboard TEN and skim where indicated. Moisture resistant boards to be used.	
	All boards to have taped and filled joints ready to receive decoration.	
	One mist and two full coats matt emulsion paint; Pure brilliant white (1013V) - colour subject to client agreement.	
Doors	Premdor solid core ash veneered faced flush doors, hardwood lippings, stainless steel ball race butt hinges. MDF door frame and stop. to meet door fire certificate requirement.	
	Frame and stop finished with one coat primer, two coats undercoat and one coat high gloss Gris Perle RAL 7040 (BS 18 B 19). ICI Dulux Paint.	
	Please refer to project door schedule.	
Joinery	Skirting: 100 x 19 MDF skirting with round edge profile. Finished with one coat primer, two coats undercoat and one coat high gloss white. ICI Dulux Paint.	
	Please note that all internal and external joints are to be mitred	



Store

Location	Finish	Image / Product
Joinery continued	Architraves: 70 x 18mm MDF architraves with round edge profile. Architraves and trims are to be sanded down, knot, stop. Finished with with one coat primer, two coats undercoat and one coat high gloss white ICI Dulux Paint. Please note that all internal and external joints are to be mitred	
Fixtures, Fittings & Ironmongery	Please refer to door detail information. Butt Hinges – Firestop Hinge 2ball bearing c/w hinge plates, satin steel, 3 x 76 x 102mm, TP Ref: 275010	
	Mortice lock 5 lever 64mm, satin stainless steel, TP Ref: 802504	
	Euro profile escutcheon, satin anodised aluminium, TP Ref: 274954	
	Lever Handles – Round bar rose latch handle, satin stainless steel 19mm, TP Ref: 274397	
	Overhead Closer – Rutland TS9205 satin nickel, Ironmongery Direct ref: 448049	
	Kick Plates – Satin Anodised Aluminium, 900mm, Ironmongery Direct, Ref: 170098 (to both sides)	
	Door Stop – Oval satin anodised aluminium, TP Ref: 802541	
	Fire Door Keep Locked sign, satin anodised aluminium 75mm. TP Ref: 274967	Fire Door Keep Locked



Electric Cupboard

Location	Finish	Image / Product
Walls	15mm British Gypsum Wallboard TEN and skim where indicated. Moisture resistant boards to be used. All boards to have taped and filled joints ready to receive decoration. One mist and two full coats matt emulsion paint; Pure	
	brilliant white (1013V) - colour subject to client agreement.	
Floor	Polyflor Homogeneous PUR Classic Mystique 2.5mm vinyl. Colour: Quartz 1400	
Ceiling	15mm British Gypsum Wallboard TEN and skim where indicated. Moisture resistant boards to be used.	
	All boards to have taped and filled joints ready to receive decoration. One mist and two full coats matt emulsion paint; Pure brilliant white (1013V) - colour subject to client	
	agreement.	
Doors	Premdor solid core ash veneered faced flush doors, hardwood lippings, stainless steel ball race butt hinges. MDF door frame and stop. to meet door fire certificate requirement.	
	Frame and stop finished with one coat primer, two coats undercoat and one coat high gloss Gris Perle RAL 7040 (BS 18 B 19). ICI Dulux Paint.	
	Please refer to project door schedule.	
Joinery	Skirting: 100 x 19 MDF skirting with round edge profile. Finished with one coat primer, two coats undercoat and one coat high gloss. ICI Dulux Paint.	
	Please note that all internal and external joints are to be mitred	



Electric Cupboard

Location	Finish	Image / Product
Joinery, continued	Architraves: 70 x 18mm MDF architraves with round edge profile. Architraves and trims are to be sanded down, knot, stop. Finished with with one coat primer, two coats undercoat and one coat high gloss white ICI Dulux Paint. Please note that all internal and external joints	
	are to be mitred	
	Window Board: Painted MDF with round edge profile. Size to suit opening on site. Finished with one coat primer, two coats undercoat and one coat high gloss white. ICI Dulux Paint.	
Fixtures, Fittings & Ironmongery	Please refer to door detail information.	
a worm longery	Butt Hinges – Firestop Hinge 2ball bearing c/w hinge plates, satin steel, 3 x 76 x 102mm, TP Ref: 275010	
	Handle & digital lock to be interlinked with fire alarm system.	
	Overhead Closer – Rutland TS9205 satin nickel, Ironmongery Direct ref: 448049	
	Kick Plates – Satin Anodised Aluminium, 900mm, Ironmongery Direct, Ref: 170098 (to both sides)	
1	Push Plate – Satin anodised aluminium, 300 x 73mm, TP Ref: 802531	PUSH



Electric Cupboard

Location	Finish	Image / Product
Fixtures, Fittings & Ironmongery continued	Fire Door Keep Locked sign, satin anodised aluminium 75mm. TP Ref: 274967	Fire Door Keep Locked
	Fire Door Keep Clear sign, satin anodised aluminium, 75mm dia., Direct Signs, Ref: PA11-SAA, or similar and approved.	Fire door Keep clear
	Door Stop – Oval satin anodised aluminium, TP Ref: 802541	



Club Room

Location	Finish	Image / Product
Walls	15mm British Gypsum Wallboard TEN and skim where indicated. Moisture resistant boards to be used. All boards to have taped and filled joints ready to receive decoration. One mist and two full coats matt emulsion paint; Pure brilliant white (1013V) - colour subject to client agreement.	
Floor	Polyflor Expona Control Wood PUR Weathered Country Plank Ref: 6504	
Ceiling	15mm British Gypsum Wallboard TEN and skim where indicated. Moisture resistant boards to be used. All boards to have taped and filled joints ready to receive decoration. One mist and two full coats matt emulsion paint; Pure brilliant white (1013V) - colour subject to client agreement.	
Doors	Premdor solid core ash veneered faced flush doors, hardwood lippings, stainless steel ball race but hinges. MDF door frame and stop. to meet door fire certificate requirement. Frame and stop finished with one coat primer, two coats undercoat and one coat high gloss Gris Perle RAL 7040 (BS 18 B 19). ICI Dulux Paint. Please refer to project door schedule.	
Joinery	Skirting: 100 x 19 MDF skirting with round edge profile. Finished with one coat primer, two coats undercoat and one coat high gloss white. ICI Dulux Paint. Please note that all internal and external joints are to be mitred	



Club Room

Location	Finish	Image / Product
Joinery continued	Architraves: 70 x 18mm MDF architraves with round edge profile. Architraves and trims are to be sanded down, knot, stop. Finished with with one coat primer, two coats undercoat and one coat high gloss.	
	Please note that all internal and external joints are to be mitred	
	Window Board: Painted MDF with round edge profile. Size to suit opening on site. Finished with one coat primer, two coats undercoat and one coat high gloss white. ICI Dulux Paint.	
_	Please refer to door detail information	
& Ironmongery	Pull Handles – A-Spec 22mm Bolt Fix Pull Handle - 250mm Centres - 316 Satin Stainless Steel, installed 1500mm from FFL to centre of handle. Ironmongery Direct Ref: 849641	
	Butt Hinges – Enduro Radius twin ball bearing c/w hinge plates, satin stainless steel, 3 x 76 x 102mm, Ironmongery Direct ref: 298935	
	Overhead Closer – Rutland TS9205 satin nickel, Ironmongery Direct ref: 448049	
	Kick Plates – Satin Anodised Aluminium, 900mm, Ironmongery Direct, Ref: 170098 (to both sides)	



Club Room

Location	Finish	Image / Product
Fixtures, Fittings & Ironmongery continued	Push Plate – Satin anodised aluminium, 300 x 73mm, TP Ref: 802531	PUSH
	Fire Door Keep Shut sign, satin anodised aluminium, 75mm dia., Wickes Ref: 229112	Fire door keep shut
	Fire Door Keep Clear sign, satin anodised aluminium, 75mm dia., Direct Signs, Ref: PA11-SAA, or similar and approved.	Fire door Keep clear
	Kick Plates – Satin Anodised Aluminium, 825mm, TP Ref: 523494 (to be determined by door schedule)	
	Door Stop – Oval satin anodised aluminium, TP Ref: 802541	O.J.



Plant Room External

Location	Finish	Image / Product
Walls	Paint grade blockwork with flush pointing up to skirting level, allow for redecoration to existing walls.	
	One mist and two full coats matt emulsion paint; Pure brilliant white (1013V) - colour subject to client agreement.	
Floor	Floor slab to be consistent in colour and without localised deviations or patchiness in either colour of surface finish, no rippling or lipping to joints or score marks from the power float finish procedures. The floor slab is to finish inline with the roller shutter door thresholds and the yard slab should be laid to fall away from this threshold to prevent water ponding in front of the roller shutter door. Floor to be polished and sealed	
Doors	Please refer to project door schedule.	
Joinery	N/A	
Fixtures, Fittings & Ironmongery		



Plant Room Internal

Location	Finish	Image / Product
Walls	All boards to have taped and filled joints ready to receive decoration. New walls Plastered/dry lined and fully sealed, Existing walls new skim coat. Paint all walls, including services and fittings with two coats vinyl matt emulsion and one mist coat on suitable undercoat / sealer. Colour: TBC by client ICI Dulux Paints.	
Floor	Polyflor Polysafe Hydro PUR R11 2mm vinyl. Colour: H4940 Tempered steel Coved Skirtings 100mm upstand to match floor.	
	Internal and external corners to be mitred.	
	With a mastic sealant finish, colour to match sheet flooring	
	Gradus Esplanade 8500 barrier matting with black double wipers and	
	black anodised aluminium scraper linking strips to Player access (1240W x 1500 L) Public Access (1700 W x 1380 L) Supplied with edging strips, spacer strips and divider bars sized to suite.	
	ELAR950 transition profile colour Lead (LRV: 12.77) refer gradus.com/elar950	
Ceiling	15mm British Gypsum Wallboard TEN and skim where indicated. Moisture resistant boards to be used.	
	All boards to have taped and filled joints ready to receive decoration.	
	One mist and two full coats matt emulsion paint; Allow for redecoration where corridor meets new lobby Pure brilliant white (1013V) - colour subject to client agreement.	



Plant Room Internal

Location	Finish	Image / Product
Door	Premdor solid core ash veneered faced flush doors, hardwood lippings, stainless steel ball race butt hinges. MDF door frame and stop. to meet door fire certificate requirement. Frame and stop finished with one coat primer, two coats undercoat and one coat high gloss white, ICI Dulux Paint. Please refer to project door schedule.	
Joinery	Skirting: 100 x 19 MDF skirting with round edge profile. Finished with one coat primer, two coats undercoat and one coat high gloss white. ICI Dulux Paint.	
	Please note that all internal and external joints are to be mitred	
	Architraves: 70 x 18mm MDF architraves with round edge profile. Architraves and trims are to be sanded down, knot, stop. Finished with with one coat primer, two coats undercoat and one coat high gloss white ICI Dulux Paint.	
	Please note that all internal and external joints are to be mitred	
	Window Board: Painted MDF with round edge profile. Size to suit opening on site. Finished with one coat primer, two coats undercoat and one coat high gloss white. ICI Dulux Paint.	
Fixtures, Fittings		
& Ironmongery	Pull Handles – A-Spec 22mm Bolt Fix Pull Handle - 250mm Centres - 316 Satin Stainless Steel, installed 1500mm from FFL to centre of handle. Ironmongery Direct Ref: 849641	
	Butt Hinges – Enduro Radius twin ball bearing c/w hinge plates, satin stainless steel, 3 x 76 x 102mm, Ironmongery Direct ref: 298935	



Plant Room Internal

Location	Finish	Image / Product
Fixtures, Fittings & Ironmongery continued		
	Kick Plates – Satin Anodised Aluminium, 825mm (to both sides), TP Ref: 523494	
	Push Plate – Satin anodised aluminium, 300 x 73mm, TP Ref: 802531	PUSH
	Fire Door Keep Shut sign, satin anodised aluminium, 75mm dia., Wickes Ref: 229112	Fire door keep shut
	Fire Door Keep Clear sign, satin anodised aluminium, 75mm dia., Direct Signs, Ref: PA11-SAA, or similar and approved.	Fire door Keep clear
	Door Stop – Oval satin anodised aluminium, TP Ref: 802541	O.J.



Location	Finish	Image / Product
Walls	15mm British Gypsum Wallboard TEN and skim where indicated. Moisture resistant boards to be used.	
	Glasroc H Tilebacker board.	
	Solus 'Revolution' range porcelain tiles - to cover full height of all walls. Colour 'Evolutionary'. 300 x 600 x 9mm Natural R10 Product code: 2KAN102.	
	Tile edgings to be Durosol Aluminium Natural tile edging.	7775
	Grout colour to be white	
	IPS Panelling: Duct panel and frame set, to be full height. By Cubicle Systems, Premier Full Height (SGL) Access panels: SGL 13mm, with routered edges and black core.	
	Colours to be: Cloud, VEN351 LRV 58 Pacific, VEN353 LRV 20	
	Surrounds: SGL 13mm, , with routered edges and black core.	
Floor		
	Polyflor Safety - Polysafe Quattro PUR. Colour: 'Coastal Flint'. Colour subject to client agreement.	
	Internal and external corners to be mitred.	
	With a mastic sealant finish, colour to match sheet flooring	
	Gradus SO 100 skirting or similar. Colour Colour: 'Coastal Flint'. subject to client agreement – must have 30pt colour contrast.	



Location	Finish	Image / Product
Ceiling	15mm British Gypsum Wallboard TEN and skim where indicated. Moisture resistant boards to be used. All boards to have taped and filled joints ready to receive decoration. One mist and two full coats matt emulsion paint; Pure brilliant white (1013V) - colour subject to client agreement.	
Doors, continued	Premdor solid core ash veneered faced flush doors, hardwood lippings, stainless steel ball race butt hinges. MDF door frame and stop. to meet door fire certificate requirement.	
	Frame and stop finished with one coat primer, two coats undercoat and one coat high gloss Gris Perle RAL 7040 (BS 18 B 19). ICI Dulux Paint. Please refer to project door schedule.	
Joinery	Architraves: 70 x 18mm MDF architraves with round edge profile. Architraves and trims are to be sanded down, knot, stop. Finished with with one coat primer, two coats undercoat and one coat high gloss Gris Perle RAL 7040 (BS 18 B 19). ICI Dulux Paint. Please note that all internal and external joints are to be mitred	
Fixtures, Fittings & Ironmongery	700x450mm acrylic mirrors with chrome dome headed screws above each wash hand basin.	
	1 no Pro Coat Hook per cubicle, satin anodised aluminium, by Ironmongery Direct or similar and approved, Ref: 357529	



Location	Finish	Image / Product
Fixtures, Fittings & Ironmongery continued	Biodryer Biolite Eco hand dryer – Colour: White. By M&E subcontractor.	
	i.life A Back To Wall Toilet With RimLS+ Technology, Ideal Standard Ref: E2474(01) (white)	
	Palm push button pneumatic, stainless steel for 31mm maximum thickness partition	,
	Connect Air 54cm Short Projection Vanity Washbasin, 1 taphole with overflow. Ideal Standard Ref: E0296(01)	
	By M&E subcontractor.	
	Venesta HPL double vanity unit or similar	
	Taps - 2 no. SCBW113 Sanceram Thermostatic Mixing Valves Recommended safe hot water temperature for washbasin - maximum 41°C. By M&E subcontractor.	
	Door and wall grab rails: NRS Healthcare Plastic Fluted Grab Rail - White - 600mm, contrasting colour. Complete Care Ref: F19480	
	NRS Healthcare Plastic Fluted Grab Rail - Blue - 600mm, contrasting colour. Complete Care Ref: L30519	3
	Please refer to door detail information	



Location	Finish	Image / Product
Fixtures, Fittings & Ironmongery continued	Shower Cubicles by Cubicle Systems, Premier Commercial Washroom Range – Colour: White partitions / pilaster, solid grey laminate grey doors. Include heavy duty fittings (SSA) hinges, legs, angle head rail and pilaster lock. One cubicle to provide contrasting grab rail with an outward opening door. Include for white panels to divide the urinal space. Wet & Dry Application Delabie sporting 2 time flow shower panel (model 714700). By M&E subcontractor.	
	Delabie premix Comfort 55 fail-safe group shower mixing valve TMV3 type. By M&E subcontractor.	
	Bench seats – 32mm thick, Steamed Beech seating 3 slats mounted on galvanised steel.	
	Colour : Natural Beech slats with black brackets – 1200mm Long – TBC	TI
	Pull Handles – A-Spec 22mm Bolt Fix Pull Handle - 250mm Centres - 316 Satin Stainless Steel, installed 1500mm from FFL to centre of handle. Ironmongery Direct Ref: 849641	
	Butt Hinges – Enduro Radius twin ball bearing c/w hinge plates, satin stainless steel, 3 x 76 x 102mm, Ironmongery Direct ref: 298935	
	Overhead Closer – Rutland TS9205 satin nickel, Ironmongery Direct ref: 448049	
	Kick Plates – Satin Anodised Aluminium, 900mm, Ironmongery Direct, Ref: 170098 (to both sides)	



Location	Finish	Image / Product
Fixtures, Fittings & Ironmongery, continued	Door Stop – Oval satin anodised aluminium, TP Ref: 802541	
	Push Plate – Satin anodised aluminium, 300 x 73mm, TP Ref: 802531	PUSH
	Please refer to door detail information.	
	Indicator bolt, satin, TP Ref: 726435	
	Lever Handles – Round bar rose latch handle, satin stainless steel 19mm, TP Ref: 274397	
	Unisex Toilet Sign, satin anodised aluminium, 75mm dia., Direct Signs, Ref: PA3-SAA, or similar and approved.	
	Fire Door Keep Shut sign, satin anodised aluminium, 75mm dia., Wickes Ref: 229112	Fire door keep shut
	Fire Door Keep Clear sign, satin anodised aluminium, 75mm dia., Direct Signs, Ref: PA11-SAA, or similar and approved.	Fire door Keep clear



Location	Finish	Image / Product
Fixtures, Fittings & Ironmongery, continued	3 no. TORK SmartOne Toilet roll dispenser, Consortium	
	3 no. Consortium Soap Dispensers	



Location	Finish	Image / Product
Walls	15mm British Gypsum Wallboard TEN and skim where indicated. Moisture resistant boards to be used.	
	Glasroc H Tilebacker board.	
	Solus 'Revolution' range porcelain tiles - to cover full height of all walls. Colour 'Evolutionary'. 300 x 600 x 9mm Natural R10 Product code: 2KAN102.	
	Tile edgings to be Durosol Aluminium Natural tile edging.	7775
	Grout colour to be white	
	IPS Panelling: Duct panel and frame set, to be full height. By Cubicle Systems, Premier Full Height (SGL) Access panels: SGL 13mm, with routered edges and black core.	
	Colours to be: Cloud, VEN351 LRV 58 Pacific, VEN353 LRV 20	
	Surrounds: SGL 13mm, , with routered edges and black core.	
Floor		
	Polyflor Safety - Polysafe Quattro PUR. Colour: 'Coastal Flint'. Colour subject to client agreement.	
	Internal and external corners to be mitred.	
	With a mastic sealant finish, colour to match sheet flooring	
	Gradus SO 100 skirting or similar. Colour Colour: 'Coastal Flint'. subject to client agreement – must have 30pt colour contrast.	



Location	Finish	Image / Product
Ceiling	15mm British Gypsum Wallboard TEN and skim where indicated. Moisture resistant boards to be used. All boards to have taped and filled joints ready to receive decoration. One mist and two full coats matt emulsion paint; Pure brilliant white (1013V) - colour subject to client agreement.	
Doors, continued	Premdor solid core ash veneered faced flush doors, hardwood lippings, stainless steel ball race butt hinges. MDF door frame and stop. to meet door fire certificate requirement. Frame and stop finished with one coat	
	primer, two coats undercoat and one coat high gloss Gris Perle RAL 7040 (BS 18 B 19). ICI Dulux Paint.	
	Please refer to project door schedule.	
Joinery	Architraves: 70 x 18mm MDF architraves with round edge profile. Architraves and trims are to be sanded down, knot, stop. Finished with with one coat primer, two coats undercoat and one coat high gloss Gris Perle RAL 7040 (BS 18 B 19). ICI Dulux Paint.	
	Please note that all internal and external joints are to be mitred	
Fixtures, Fittings & Ironmongery	700x450mm acrylic mirrors with chrome dome headed screws above each wash hand basin.	
	1 no Pro Coat Hook per cubicle, satin anodised aluminium, by Ironmongery Direct or similar and approved, Ref: 357529	



Location	Finish	Image / Product
Fixtures, Fittings & Ironmongery continued	Biodryer Biolite Eco hand dryer – Colour: White. By M&E subcontractor.	
	i.life A Back To Wall Toilet With RimLS+ Technology, Ideal Standard Ref: E2474(01) (white)	
	Palm push button pneumatic, stainless steel for 31mm maximum thickness partition	,
	Connect Air 54cm Short Projection Vanity Washbasin, 1 taphole with overflow. Ideal Standard Ref: E0296(01)	
	By M&E subcontractor.	
	Venesta HPL double vanity unit or similar	
	Taps - 2 no. SCBW113 Sanceram Thermostatic Mixing Valves Recommended safe hot water temperature for washbasin - maximum 41°C. By M&E subcontractor.	
	Door and wall grab rails: NRS Healthcare Plastic Fluted Grab Rail - White - 600mm, contrasting colour. Complete Care Ref: F19480	
	NRS Healthcare Plastic Fluted Grab Rail - Blue - 600mm, contrasting colour. Complete Care Ref: L30519	3
	Please refer to door detail information	



Location	Finish	Image / Product
Fixtures, Fittings & Ironmongery continued	iflo Abs Capped Slimline Stone Shower Tray 800 x 800 x 45, TP Ref: 719344. By M&E Subcontractor	
	iflo Shower Tray Quad Panel and Leg Pack to suite	
	Kubo 800mm pivot door with Ideal clean clear glass - bright silver finish Ref: T7373 By M&E subcontractor.	
	Iflo electric shower 8.5kW, colour: White, TP Ref: 602377. By M&E subcontractor.	
	Bench seats – 32mm thick, Steamed Beech seating 3 slats mounted on galvanised steel.	
	Colour : Natural Beech slats with black brackets – 1200mm Long – TBC	
	Pull Handles – A-Spec 22mm Bolt Fix Pull Handle - 250mm Centres - 316 Satin Stainless Steel, installed 1500mm from FFL to centre of handle. Ironmongery Direct Ref: 849641	
	Butt Hinges – Enduro Radius twin ball bearing c/w hinge plates, satin stainless steel, 3 x 76 x 102mm, Ironmongery Direct ref: 298935	
	Overhead Closer – Rutland TS9205 satin nickel, Ironmongery Direct ref: 448049	47



Location	Finish	Image / Product
Fixtures, Fittings & Ironmongery,	Kick Plates – Satin Anodised Aluminium, 900mm, Ironmongery Direct, Ref: 170098 (to both sides)	
continued	Door Stop – Oval satin anodised aluminium, TP Ref: 802541	
	Push Plate – Satin anodised aluminium, 300 x 73mm, TP Ref: 802531	PUSH
	Please refer to door detail information.	1
	Indicator bolt, satin, TP Ref: 726435	
	Lever Handles – Round bar rose latch handle, satin stainless steel 19mm, TP Ref: 274397	
	Unisex Toilet Sign, satin anodised aluminium, 75mm dia., Direct Signs, Ref: PA3-SAA, or similar and approved.	
	Fire Door Keep Shut sign, satin anodised aluminium, 75mm dia., Wickes Ref: 229112	Fire door keep shut
	Fire Door Keep Clear sign, satin anodised aluminium, 75mm dia., Direct Signs, Ref: PA11-SAA, or similar and approved.	Fire door Keep clear



Location	Finish	Image / Product
Fixtures, Fittings & Ironmongery, continued	3 no. TORK SmartOne Toilet roll dispenser, Consortium	
	3 no. Consortium Soap Dispensers	



Location	Finish	Image / Product
Walls	15mm British Gypsum Wallboard TEN and skim where indicated. Moisture resistant boards to be used. Glasroc H Tilebacker board. Solus 'Revolution' range porcelain tiles - to cover full height of all walls. Colour 'Evolutionary'. 300 x 600 x 9mm Natural R10 Product code: 2KAN102. Tile edgings to be Durosol Aluminium Natural tile edging. Grout colour to be white	
Floor	Polyflor Safety - Polysafe Quattro PUR. Colour: 'Coastal Flint'. Colour subject to client agreement. Internal and external corners to be mitred. With a mastic sealant finish, colour to match sheet flooring Gradus SO100 skirting or similar. Colour Colour: 'Coastal Flint'. subject to client agreement – must have 30pt colour contrast.	
Ceiling	15mm British Gypsum Wallboard TEN and skim where indicated. Moisture resistant boards to be used. All boards to have taped and filled joints ready to receive decoration. One mist and two full coats matt emulsion paint; Pure brilliant white (1013V) - colour subject to client agreement.	



Location	Finish	Image / Product
Doors, continued	Premdor solid core ash veneered faced flush doors, hardwood lippings, stainless steel ball race butt hinges. MDF door frame and stop. to meet door fire certificate requirement.	
	Frame and stop finished with one coat primer, two coats undercoat and one coat high gloss Gris Perle RAL 7040 (BS 18 B 19). ICI Dulux Paint.	
	Please refer to project door schedule.	
Joinery	Architraves: 70 x 18mm MDF architraves with round edge profile. Architraves and trims are to be sanded down, knot, stop. Finished with with one coat primer, two coats undercoat and one coat high gloss Gris Perle RAL 7040 (BS 18 B 19). ICI Dulux Paint.	
	Please note that all internal and external joints are to be mitred	
Fixtures, Fittings & Ironmongery	700x450mm acrylic mirrors with chrome dome headed screws above each wash hand basin.	
	1 no Pro Coat Hook per cubicle, satin anodised aluminium, by Ironmongery Direct or similar and approved, Ref: 357529	



Location	Finish	Image / Product
Fixtures, Fittings & Ironmongery continued	AirRise200hoistunittobefittedwithintheChanging- Placesroom Hoist track: AirGlide360 H frame system within the Changing Places room giving full room coverage	
	Peninsular wc to give access on both sides for carers - 480mm seat height	
	Wall Mounted Changing Bench 3000 - Electric height adjustment	
	Height adjustable wash basin with vertical track adjustment	
	Wall mounted, folding privacy screen	
	Electric Shower	
	Drop down grab rails for beside w/c x 2 (1 to include toilet roll holder)	
	Vertical grab rails 600mm x 5	
	20" Wide paper roll dispenser	
	Hand towel dispenser	
	Soap dispenser	
	Colostomy shelf	
	Full height mirror, 1000mm x 600mm	
	Coat hooks x 3	
	-General waste bin	
	Large sanitary bin	
	Electric hand dryer	
	Instruction Wall Mounted Plaques	



Location	Finish	Image / Product
Fixtures, Fittings & Ironmongery continued	Pull Handles – A-Spec 22mm Bolt Fix Pull Handle - 250mm Centres - 316 Satin Stainless Steel, installed 1500mm from FFL to centre of handle. Ironmongery Direct Ref: 849641	
	Butt Hinges – Enduro Radius twin ball bearing c/w hinge plates, satin stainless steel, 3 x 76 x 102mm, Ironmongery Direct ref: 298935	
	Overhead Closer – Rutland TS9205 satin nickel, Ironmongery Direct ref: 448049	
	Kick Plates – Satin Anodised Aluminium, 900mm, Ironmongery Direct, Ref: 170098 (to both sides)	
	Door Stop – Oval satin anodised aluminium, TP Ref: 802541	
	Push Plate – Satin anodised aluminium, 300 x 73mm, TP Ref: 802531	PUSH
	Please refer to door detail information.	
	Equality Act & BS8300 compliant lock and indicator bolt. Ironmongery Direct, Ref: 897694, or similar and approved.	



Location	Finish	Image / Product
Fixtures, Fittings & Ironmongery, continued	Unisex Toilet Sign, satin anodised aluminium, 75mm dia., Direct Signs, Ref: PA3-SAA, or similar and approved.	
	Inclusive Toilet Sign, satin anodised aluminium, 75mm dia., Direct Signs, Ref: PA4-SAA, or similar and approved.	E
	Changing places sign – N&C Phlexicare.	É
	Fire Door Keep Shut sign, satin anodised aluminium, 75mm dia., Wickes Ref: 229112	Fire door keep shut
	Fire Door Keep Clear sign, satin anodised aluminium, 75mm dia., Direct Signs, Ref: PA11-SAA, or similar and approved.	Fire door Keep clear
	3 no. TORK SmartOne Toilet roll dispenser, Consortium	*
	3 no. Consortium Soap Dispensers	
	note: changing places facility will require commissioning and registration prior to use	