

Security shutters Specifications



Search Able Shutters

Go

- [About Able Shutters](#)
- [Security Products](#)
- [Contact Us](#)
- [Enquiry Form](#)
- [Policies/Statements](#)
- [Web Links Resources](#)
- [Site Map](#)

Able Shutter Services Limited

Telephone: 020 8885 5332 Fax: 020 8885 6786

Electric and manual roller shutter specification

<p>Box B</p> <p>Shutter Screen Height A</p>	<p>Able security roller shutter, ideal for shops, warehouses, offices and garages.</p>			
		<p>Shutter Screen (A) Height in meters</p>		<p>Shutter Box Size (square) (B)</p>
		From	To	mm
		1m	2m	205mm
		2m	3m	300mm
		3m	4m	355mm
		4m	5m+	380mm
<p>Note: maximum height & width of manual shutters 3m x 3m before they need to be electric.</p>				

Electric roller shutter - Specification

<p>Shutter Screen</p>	<p>75mm steel rolled sections of traditional pattern, galvanised and fitted with steel end-lock to insure the screen does not move from side to side. Available from 1m to 5M+ any width.</p>
<p>Electric Motor</p>	<p>100mm steel tube section fitted with 240volt single phase motor, using a maximum 3 amp per run. Motor comes complete with internal limit switch adjustments in up and down mode set by Able engineers on installation.</p>
<p>Brackets and guides</p>	<p>Fabricated in 3mm rolled sections of steel, U-Channel/Guides available in 40/50/75/100mm deep, 25mm wide, bracket end plates (boxes) available in 205/300/355/380mm square.</p>
<p>Coil covers</p>	<p>20 gauge pressed galvanised steel sections</p>
<p>Colours</p>	<p>Any BS or RAL numbers required at an additional cost</p>
<p>Key Switch Lock</p>	<p>Rocker Switch</p>
<p>Remote Control</p>	<p>Operation Electric security key switch inside and out, rocker switch inside, but if required outside the switch must be housed in</p>

			a galvanised lockable steel box or optionally switch can be operated with a remote control unit.
Guarantee	All Able Shutter Services Limited products carry a standard 12 month warranty on parts and labor Click here to request a quote Click here to view security shutters		
Manual roller shutter - Specification			
 Shutter Screen	75mm steel rolled sections of traditional pattern, galvanised and fitted with steel end-lock to insure the screen does not move from side to side.		
Manual operation push up/push down	100mm steel tube section fitted with internal helical spring, balanced on installation by Able engineers for ease of operation.		
Brackets and guides	Fabricated in 3mm rolled sections of steel, U-Channel/Guides available in 40/50/75/100mm deep, 25mm wide, bracket end plates (boxes) available in 205/300/355/380mm square.		
Coil covers	20 gauge pressed galvanised steel sections.		
Colours	Any BS or RAL numbers required at an additional cost.		
Locks	 Bullet Lock	 Shutter Lock	Bullet locks, fitted as standard, solid steel body welded to face of guide. Locking pin is made of hardened steel for excellent security, locks can be keyed alike, each lock is supplied with two keys, we

			<p>advise that two locks are supplied for each individual shutter. Optional Shutter screen lock can be supplied if required.</p>
<p>Guarantee</p>	<p>All Able Shutter Services Limited products carry a standard 12 month warranty on parts and labor. Click here to request a quote Click here to view security shutters</p>		
<p>[About Able Shutters] [Security Products] [Contact Us] [Enquiry Form] [Policies/Statements] [Web Links Resources] [Site-Map]</p>			
<p style="text-align: center;">Able Shutter Services Limited Able House, 10 Fairview Close, Benfleet, Essex, SS7 4JS, England UK Tel: 020 8885 5332 copyright©Able Shutter Services Limited 2002 -2011</p>			