

Notes

First floor to be limited to a maximum of 60 occupants due to existing door swing direction at base of stairs on escape route.

Ground Floor to be limited to a maximum of 60 occupants due to doors D0.09/01 and D0.02/01 opening direction on escape route.

Proposed Key

----- Structural Element Above

Proposed Works

First Floor

23. Existing internal window to be infilled with dense blockwork. One skin to either side. Blockwork to be tied into existing wall cheeks with wall ties as required. 12.5mm plaster board on dot and dab to line through with existing once skimmed, mesh to be applied across joint with existing prior to skin coat.

24. Disabled refuge to be located in front of lift doors. Size required 900x1400mm.

25. Lift lobby floor to be cut back as required. Joist sizes and directions to be specified by SE.

26. Lift shaft to be ventilated by at high level. Fire dampener required.

27. New door D1.06/01 to be installed

28. Allow provisional sum for new toilet seats to be installed to both WCs on first floor

29. Replace 1 no. low level obscured window pane to match other. See window schedule

Note:

Finishes required as per Floor Finishes Plan 1228/160 and Reflected Ceiling Plan 1228/171



The title, copyright and confidential information in this document belongs to Orme Limited, all rights reserved. This drawing is to be read in conjunction with other documents issued by the Architect. Only figured dimensions to be used. Contractors not to scale from this drawing and must check all dimensions before proceeding. Any discrepancies reported to the Architect immediately.

orme

Street Parish Rooms

revision	revision date	title	Proposed First Floor GA
A - Preparation for Public Consultation	11.10.19	date	09.10.19
B - BC issue for comment	22.10.19	scale	1:50 @ A1
C - maximum occupation note added	31.10.19	drg	1228/121 ^{REV} D
D - Replacement of male WC door			