



Not to scale - for illustrative purposes only

**TREATMENT KEY:**

- 50mm inlay TSCS (Do Min)
- Fill and overbanding repair system for crack exceeding 5mm but not exceeding 10mm wide (Do Min)
- Deep repair/ inlay (Do Something)

**Notes**

- 1) Dimensions are approximate and have been based on the most up-to-date AVIS video data
- 2) Only overhead power lines shown on the treatment plans. For other utilities please refer to the C2 plans for the area
- 3) Due to the potential inaccuracy of AVIS data regarding exact chainages, where Core locations are within the vicinity of a Gully, coring Contractor to adjust the location to avoid potential coring into/through carrier pipes

LOCATION:  
M5 J25-24 NB MP 201.7-196.6

DRAWING No:  
583 Defect Treatment Plan Sheet 1 of 6

DRAWN: FS DATE: 22/06/2020

DESIGN: FS DATE: 22/06/2020

CHECKED: CC DATE: 25/06/2020

Notes:

DEFECTS KEY		TREATMENTS		DEFECTS		TREATMENTS	
Core crack depth(mm)	Photo	Open long. joint	Const. joint	Rutting	Pothole	Core location (tar)	Core location (No Tar)
Transverse crack minor	Plug joint	Patch	Failed patch	Mechanical joint	Nodes	Settlement	Trafficked Lane
Transverse crack major	Loops	Mud pumping	Minor fretting	Mud pumping	Gully	Site to be cored	Existing HFS
Long. crack minor	Fattening	Minor crazing	Major crazing	Minor crazing	Ironwork	New HFS	SCRIM Deficiency
Long. crack major		Major crazing		Major crazing	Structure/ Bridge		Texture < 0.8mm