# **%**International

Where legislation does not explicitly restrict or limit the use of lead containing coatings it is the responsibility of the client to inform International Paint in writing of their specific requirements



Goodall, M.

Telephone : +44 (0)1489775060 Fax : +44 (0)1489785867 E-Mail : Matthew.Goodall@akzonobel.com

Marine Coatings



Unless otherwise agreed in writing, all products supplied and technical advice given by us are subject to our standard terms and conditions of sale. Please note that a surcharge may be applied to the prices listed, in which case this will be notified to you by your International Paint representative. In the event that supplies are made and technical advice is given by one of our associated companies then such supplies and technical advice shall be subject to the standard terms of sale of that company, a copy of which is available upon request

UFG03238

11-Apr-2016 1

## Interspec

# **%International**

# Interspec

Main Schemes		
Area	Description	Area m²
	A national finish Interthene 000	400 m 3
Superstructure	A polyurethane finish, Interthane 990.	126m <sup>2</sup>
Topsides	A polyurethane finish, Interthane 990.	30m²
Underwater Hull	An Intergard 5000 tar free, high solids epoxy anticorrosive scheme with Intergard 263 as an epoxy tiecoat to the subsequent antifouling scheme.	67m²
Jets		7m²
Thinners		

Marine Coatings



Unless otherwise agreed in writing, all products supplied and technical advice given by us are subject to our standard terms and conditions of sale. Please note that a surcharge may be applied to the prices listed, in which case this will be notified to you by your International Paint representative. In the event that supplies are made and technical advice is given by one of our associated companies then such supplies and technical advice shall be subject to the standard terms of sale of that company, a copy of which is available upon request

11-Apr-2016 2

UFG03238

# **XInternational**

### Superstructure [126m<sup>2</sup>]

#### A polyurethane finish, Interthane 990.

#### Surface Preparations

Where necessary remove all weld splatter, smooth weld seams and sharp edges. Fresh water wash to remove all dirt and contamination, as necessary. Degrease according to SSPC-SP1 solvent cleaning. Ensure area is clean and dry prior to application. Abrade intact surfaces to produce a mechanical key. Remove all dust and surface contamination. Ensure all surfaces are clean, dry and free of contamination prior to the application of each coat of the specified paint system.

Product	Colour	Coats	DFT	WFT	PSR	Touch	Hard Dry	Overcoa	ting 25°C	Pot Life	Thinner	Cleaner	Volume It
			Microns	Microns	(m²/lt)	Dry	25°C	Min	Max	25°C			
Intergard 5000	Aluminium	10% TU	100	122	5.74	3.5hrs	7hrs	7hrs	14days	75mins	GTA220	GTA220	2.2
Interthane 990	Lt Wthr wrk Grey	FC	50	88	6.84	1.5hrs	6hrs	6hrs	ext		GTA056, GTA713, GTA733	GTA056, GTA713, GTA733	18.4
Interthane 990	Lt Wthr wrk Grey	FC	50	88	6.84	1.5hrs	6hrs	6hrs	ext		GTA056, GTA713, GTA733	GTA056, GTA713, GTA733	18.4
			200	298									39.0

Marine Coatings



Interspec

Unless otherwise agreed in writing, all products supplied and technical advice given by us are subject to our standard terms and conditions of sale. Please note that a surcharge may be applied to the prices listed, in which case this will be notified to you by your International Paint representative. In the event that supplies are made and technical advice is given by one of our associated companies then such supplies and technical advice shall be subject to the standard terms of sale of that company, a copy of which is available upon request

11-Apr-2016 3

UFG03238

# **X.International**

### Topsides [30m<sup>2</sup>]

#### A polyurethane finish, Interthane 990.

#### Surface Preparations

Where necessary remove all weld splatter, smooth weld seams and sharp edges. Fresh water wash to remove all dirt and contamination, as necessary. Degrease according to SSPC-SP1 solvent cleaning. Ensure area is clean and dry prior to application. Abrade intact surfaces to produce a mechanical key. Remove all dust and surface contamination.

Ensure all surfaces are clean, dry and free of contamination prior to the application of each coat of the specified paint system.

Product	Colour	Coats	DFT	WFT	PSR	Touch	Hard Dry	Overcoa	ting 25°C	Pot Life	Thinner	Cleaner	Volume It
			Microns	Microns	(m²/lt)	Dry	25°C	Min	Max	25°C			
Intergard 5000	Aluminium	10% TU	100	122	5.74	3.5hrs	7hrs	7hrs	14days	75mins	GTA220	GTA220	0.5
Interthane 990	Lt Wthr wrk Grey	FC	50	88	6.84	1.5hrs	6hrs	6hrs	ext		GTA713,	GTA056, GTA713, GTA733	4.4
Interthane 990	Lt Wthr wrk Grey	FC	50	88	6.84	1.5hrs	6hrs	6hrs	ext		GTA713,	GTA056, GTA713, GTA733	4.4
			200	298									9.3

### Underwater Hull [67m<sup>2</sup>]

An Intergard 5000 tar free, high solids epoxy anticorrosive scheme with Intergard 263 as an epoxy tiecoat to the subsequent antifouling scheme.

### Surface Preparations

Where necessary remove all weld splatter, smooth weld seams and sharp edges. Fresh water wash to remove all dirt and contamination, as necessary. Degrease according to SSPC-SP1 solvent cleaning. Ensure area is clean and dry prior to application. Abrade intact surfaces to produce a mechanical key. Remove all dust and surface contamination. Ensure all surfaces are clean, dry and free of contamination prior to the application of each coat of the specified paint system.

Product	Colour	Coats	DFT	WFT	PSR	Touch	Hard Dry	Overcoa	ting 25°C	Pot Life	Thinner	Cleaner	Volume It
			Microns	Microns	(m²/lt)	Dry	25°C	Min	Max	25°C			
Intergard 5000	Aluminium	10% TU	150	183	3.83	3.5hrs	7hrs	7hrs	2mths	75mins	GTA220	GTA220	1.7
Intergard 263	Light Grey	10% TU	100	175	3.99	6hrs	16hrs	8hrs	5days	6hrs		GTA220 <u>,</u> GTA822	1.7
Interspeed 6400	Black	FC	100	167	4.20	2hrs		6hrs	6mths		GTA007	GTA007	16.0
			350	525									19.4

### Marine Coatings

Unless otherwise agreed in writing, all products supplied and technical advice given by us are subject to our standard terms and conditions of sale. Please note that a surcharge may be applied to the prices listed, in which case this will be notified to you by your International Paint representative. In the event that supplies are made and technical advice is given by one of our associated companies then such supplies and technical advice shall be subject to the standard terms of sale of that company, a copy of which is available upon request



Interspec

# **%International**

### Jets [7m<sup>2</sup>]

#### Surface Preparations

High pressure fresh water wash at 204+bar (3,000+psi) using a fan jet lance holding the tip 150mm from and perpendicular to the surface overlapping the passes 30% removing salt and other surface contamination leaving a clean "water breakfree" surface and allow to dry. Where the surface shows signs of beading the surface should be degreased IAW AS1627.1 - 2003. Degrease in accordance with AS1627.1 - 2003 using a non-ionic detergent as directed and rinse thoroughly.Spot mechanically prepare the surface using an aluminium oxide abrasive disk (24-30 grit) to give a heavily scored surface profile of 50-75 microns (2-3 mils). Ensure the area is clean and dry and apply initial coat within 6-8 hours.Remove all dust and surface contamination using clean dry compressed air or agreed method.Ensure all surfaces are clean, dry and free of contamination prior to the application of each coat of the specified paint scheme.

Product	Colour	Coats	DFT	WFT	PSR	Touch	Hard Dry	Overcoa	ting 25°C	Pot Life	Thinner	Cleaner	Volume It
			Microns	Microns	(m²/lt)	Dry	25°C	Min	Max	25°C			
Intergard 5000	Aluminium	10% TU	150	183	3.83	3.5hrs	7hrs	7hrs	2mths	75mins	GTA220	GTA220	0.2
Intergard 263	Light Grey	10% TU	100	175	3.99	6hrs	16hrs	8hrs	5days	6hrs	GTA220	GTA220, GTA822	0.2
Trilux 33	Black	FC	100	222	3.15	3hrs		6hrs	4wks		GTA007	GTA007	2.2
			350	580									2.6

### Marine Coatings

AkzoNobel

Interspec

Unless otherwise agreed in writing, all products supplied and technical advice given by us are subject to our standard terms and conditions of sale. Please note that a surcharge may be applied to the prices listed, in which case this will be notified to you by your International Paint representative. In the event that supplies are made and technical advice is given by one of our associated companies then such supplies and technical advice shall be subject to the standard terms of sale of that company, a copy of which is available upon request

11-Apr-2016 5

UFG03238

# **KInternational**

## Interspec

Thinners											
Product	Colour	Sales Code	Volume It								
International		GTA220	5.0								
International		GTA713	5.0								
International		GTA007	5.0								
			15.0								

Marine Coatings



Unless otherwise agreed in writing, all products supplied and technical advice given by us are subject to our standard terms and conditions of sale. Please note that a surcharge may be applied to the prices listed, in which case this will be notified to you by your International Paint representative. In the event that supplies are made and technical advice is given by one of our associated companies then such supplies and technical advice shall be subject to the standard terms of sale of that company, a copy of which is available upon request

11-Apr-2016 6

UFG03238

# **KInternational**

# Interspec

Product List												
Product	Colour	Sales Code	Volume Solids (%)	Volume (lt )								
Intergard 263	Light Grey	FAJ034/A	57	20.0								
		KBA501/A	82	5.0								
Interspeed 6400	Black	BQA649	60	20.0								
Interthane 990	Lt Wthr wrk Grey	PHZ684/A	57	50.0								
Trilux 33	Black	YBA067	45	2.5								

Product List - Thinners											
Product	Colour	Sales Code	Volume Solids (%)	Volume (It )							
International		GTA007	0	5.0							
International		GTA220	0	5.0							
International		GTA713	0	5.0							

## Marine Coatings

AkzoNobel

Unless otherwise agreed in writing, all products supplied and technical advice given by us are subject to our standard terms and conditions of sale. Please note that a surcharge may be applied to the prices listed, in which case this will be notified to you by your International Paint representative. In the event that supplies are made and technical advice is given by one of our associated companies then such supplies and technical advice shall be subject to the standard terms of sale of that company, a copy of which is available upon request

7 19m GRP PATROL CRAFT

UFG03238

11-Apr-2016



Interspec

**Application Notes** 

### Marine Coatings



Unless otherwise agreed in writing, all products supplied and technical advice given by us are subject to our standard terms and conditions of sale. Please note that a surcharge may be applied to the prices listed, in which case this will be notified to you by your International Paint representative. In the event that supplies are made and technical advice is given by one of our associated companies then such supplies and technical advice shall be subject to the standard terms of sale of that company, a copy of which is available upon request

8

UFG03238

11-Apr-2016



## Interspec

#### **Terms and Conditions**

This confidential document is for the use of the above named client and its contents should not be reproduced or transmitted without prior written permission from International Paint. The information is given in good faith and attention to the following statement :

The information given in this report is not intended to be exhaustive and any person using any products for any purpose other than that specifically recommended in this report without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. Any warranty, if given, or specific Terms & Conditions of Sale are contained in International Paints Terms and Conditions of Sale, a copy of which can be obtained on request. Whilst we endeavour to ensure that all advice we give about the product (whether in this report or otherwise) is correct we have no control over either the quality or condition of the substrate or the many factors affecting the use and application of this product. Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever for howsoever arising for the performance of our products or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of the product. The information contained in this report is liable to modification from time to time in the light of experience and our policy of continuous product development.

It is the user's responsibility to check that upto date product data sheets are obtained prior to using the products and that local environmental controls that may be in force are observed when using any of our products.

#### Health & Safety

Products referred to in this report are intended for use only by professional applicators in industrial situations in accordance with the advice given on our Technical Datasheetst, the Material Safety Data Sheet and the container(s), and should not be used without reference to the Material Safety Data Sheet (MSDS).

All work involving the application and use of this product should be performed in compliance with all relevant national Health, Safety & Environment standards and regulations.

In the event welding or flame cutting is performed on metal coated with this product, dust and fumes will be emitted which will require the use of appropriate personal protective equipment and adequate local exhaust ventilation.

If in doubt regarding the suitability of use of this product, consult International Paint for further advice.

### Marine Coatings



Unless otherwise agreed in writing, all products supplied and technical advice given by us are subject to our standard terms and conditions of sale. Please note that a surcharge may be applied to the prices listed, in which case this will be notified to you by your International Paint representative. In the event that supplies are made and technical advice is given by one of our associated companies then such supplies and technical advice shall be subject to the standard terms of sale of that company, a copy of which is available upon request

9

UFG03238

11-Apr-2016