

Tile Pattern of Flooring in existing Lodge 97x97x7mm Suitable for exterior use as frost and moisture resistant.



Example of Entrance Mat



| 15 mm | Brush | UV-Resistant Dark Green

2 Marmoleum Marmoleum Concrete Orange Shimmer 3712 Concrete Pine Forest 3750

Forbo Marmoleum Flooring in new Radio extension

2 3 3

Marmoleum Concrete Green Shimmer 3736

MDF Architrave

around Doors and Windows on the inside 18mm x 69mm



Inside To paint blockwork and breezeblocks internally, you should: Dust off the surface to make sure its free from any dirt Use one coat of Dulux Trade Blockfiller Plus on the bare surface This can be left on it's own as the finish, or will act as a primer for another topcoat (Dulux Trade Vinyl Matt or Dulux Trade Diamond Matt) for example.









Internal Finishes









Architrave Cafe doors only



Decka Plank New Hampshire	
Colour	Traditional Oak
Finishes	Brushed, Natural Oiled, Prefinished
Grade	Character
Length	1900mm
Thickness	14mm
Underfloor Heating	Suitable
Width	190mm

Treatment Osmo Hard Wax Oil Polyx

Timber Flooring in Cafe





Design Risks & Hazards: Please inspect the site and study all drawings before any work is carried out. There are services round and pipes in the ground. Any work on an existing operty should have an asbethos survey. The site is located thin a park with many visitors.

cale for construction purposes from this drawing and all dimensions are to be checked pancy, error or omission is to be reported to the architect. This drawing shall be read in

