

## MODEL CWU 01 CLASSIC URINAL

## SPECIFICATION SHEET

### INSTALLATION

The CWU\_01 pod urinal is designed for surface mounting with rear entry services & wall fixings. Three M10 fixing points are provided with 175mm long bolts suitable for a 150mm thickness wall panel.

### WASTE

The urinal is supplied with a 32mm nominal ID pipe tail, 250mm long. This should be connected to a deep seal waste trap suitable for 1 1/4" (32mm) waste pipe. A range of traps are available from Wallgate.

### WATER

A chrome finish spreader is supplied which has a 1/2" BSP male thread connection. The supply feed must be fed from behind the urinal & through the wall.

### CISTERN

Mount the cistern 1.37m from its base to the top of the urinal lip.

Number of urinals per cistern:

Bowls: Cistern size (Litres):

- 1-2 4.5
- 3 9.0
- 4-5 13.6

### DIMENSIONS

Weight: 14kg

Size: H435 x W310 x D270mm

### APPROVALS

Flammability rating:

BS476-6 Fire propagation index = 4 (sub-index max = 4.2)

BS476-7 Class 1

Building Regulations 2010 Approved Document B: 2019 edition Class B-s3, d2 (formerly known as Class 0).

ISO EN 19712-3-2007 rated 5 for durability, stain resistance, cigarette burns etc.



### OPTIONS (contact Wallgate sales for details).

1. Divider panel as shown on drawing below P/N CWD\_01.
2. Cisterns for concealed or exposed installations.
3. Flush pipes for concealed or exposed installations.
4. Waste traps.

