

**National Asset Delivery
Technical Surveys and Testing**

**Scope for
570124 M5 J26 NB MP217.0 FHS
Topographical Survey**

CONTENTS AMENDMENT SHEET

Amend. No.	Revision No.	Amendments	Initials	Date
0	0	Original version issued with tender	LY	11/02/21

TABLE OF CONTENTS

1	PURPOSE OF THE <i>SERVICES</i>	4
2	EXISTING INFORMATION	5
3	CONSTRAINTS ON HOW THE CONSULTANT PROVIDES THE SERVICES ...	6
4	REQUIREMENTS FOR THE PROGRAMME	8
5	SERVICES AND OTHER THINGS PROVIDED BY THE <i>CLIENT</i>	9
6	SPECIFICATION FOR THE <i>SERVICES</i>	10

LIST OF ANNEXES

Appendix 1 **Supplementary Constraints**

FOR INFORMATION ONLY
DO NOT COMPLETE AT THIS STAGE

1 PURPOSE OF THE SERVICES

1.1 Project objectives

1.1.1 The principle objective of this project is to carry out a Topographical Survey of a section of the eastbound carriageway. The Topographical Survey of a section of the eastbound carriageway required is shown on HE570124-KIER-VTO-M5_MP218.6-216.5-DR-VT-0100_02.

1.1.2 The specification that applies to the *services* is included in Section 6

1.2 Scope of services

1.2.1 The *services* to be provided under this contract are:

- (1) Topographical Survey to be carried out of a section of the eastbound carriageway as shown on drawings HE570124-KIER-VTO-M5_MP218.6-216.5-DR-VT-0100_02.

1.3 Deliverables

1.3.1 The *Consultant* is required to produce the following deliverables:

- (1) Topographical Survey as shown on drawings HE570124-KIER-VTO-M5_MP218.6-216.5-DR-VT-0100_02, survey data to be provided in PDF and drawing (.dwg) file formats. Electronic drawing files to be to ordnance datum and include 2 and 3-dimensional versions.

2 EXISTING INFORMATION

- 2.1.1 The C2 statutory information has been obtained and enclosed with this document, all overhead power lines are shown on drawing HE570124-KIER-VTO-M5_MP218.6-216.5-DR-VT-0100_02.
- 2.1.2 The Drawings listed below apply to this contract. Refer to the site information for details of existing site conditions including ground conditions, limitation on access, position of existing structures etc.

Drawing Number	Title	Revision / Date
HE570124-KIER-GEN-M5_MP218.6-MP216.5-DR-CD-0000_01	Location Plan	C1/ October 2020
HE570124-KIER-VTO-M5_MP218.6-216.5-DR-VT-0100_02	Topographical Survey Location Plan	C1/ October 2020

3 CONSTRAINTS ON HOW THE CONSULTANT PROVIDES THE SERVICES

3.1 General

- 3.1.1 The *Consultant* Provides the Services in such manner as to minimise the risk of damage or disturbance to or destruction of third party property.
- 3.1.2 The *Consultant* complies with the constraints and meets with the requirements outlined in Appendix 1.
- 3.1.3 The *Consultant* submits information detailing how the *Consultant* will provide the Services to the *Client* prior to the *services* commencing. This information will include any lifting plans, risk assessments, method statements, the *Consultant's* staff training information and any other relevant Health and Safety requirements.

3.2 Working hours & site specific constraints

- 3.2.1 The *Consultant's* working hours for site works shall be 22:00 – 05:00.
- 3.2.2 *Consultant* to remain within the Highways Boundaries for the duration of the works, except where agreed with both the *Employer* and the land owner in advance, as per clause **Error! Reference source not found..**
- 3.2.3 Access to the site will be via the M5 carriageway traffic management. It is anticipated that lane closures will be required as part of the traffic management. TM requirements are to be confirmed by the Consultant.

3.3 Health, Safety and Environment & Risk Management

Health and Safety requirements

- 3.3.1 In Providing the Services the *Consultant* meets the requirements of Annex 2 of the supplementary constraints relation to health and safety duties.
- 3.3.2 When implemented, the *Consultant* shall comply with the requirements of Highways England's safety passport scheme and ensure that all of his employees, and any of his subConsultant's, are registered in accordance with the implementation of the scheme.
- 3.3.3 For details of the CDM duty holders, refer to the pre-construction information which can be found within 570124_ PCI and 570124_ FRM_ Hazard Identification Topographical Survey.
- 3.3.4 Before commencing the construction phase of the *services*, the *Consultant* confirms to the *Client* that adequate welfare facilities are in place. Where the facilities detailed in section 5 are not deemed adequate, the *Consultant* provides all necessary facilities to Provide the Services and to comply with the minimum requirements set out in HSE guidance document L153.

Environmental requirements

- 3.3.5 In Providing the Services the *Consultant* meets the requirements of Annex 2 of the supplementary constraints in relation to environmental duties.

Risk Management

- 3.3.6 The *Consultant* identifies, manages and mitigates risks in accordance with the principles of ISO31000.
- 3.3.7 The *Consultant* submits a risk register, which captures all risks associated with the delivery of the services including those identified by the *Client*, with his tender and maintains it for the contract period.

FOR INFORMATION ONLY
DO NOT COMPLETE AT THIS STAGE

4 REQUIREMENTS FOR THE PROGRAMME

- 4.1.1 The *Consultant* submits programme to the *Client* with his tender.
- 4.1.2 The *Consultant* Provides the Services taking into account the following programme constraints:
- (i) the *starting date* and *completion date* and any post site works, reporting and review period
 - (ii) The services and other things provided by *Client* (see Section 5)
- 4.1.3 The programme should be in the form of an activity and time related bar chart, produced as a result of a critical path analysis.
- 4.1.4 The programme should preferably be provided in either a PDF or MS Excel format and cover the full contract period including post site activities. Activities should be clearly defined and named and the programme should detail the following:
- (i) dates and times associated with the project, including the *starting date*, *completion date* & *Consultant's* planned completion, and any other dates or times that will specifically impact the delivery of the project
 - (ii) activities associated with delivering the project
 - (iii) for each activity, the proposed resources (plant & labour) expected to deliver the activity should be shown on the programme;
 - (iv) review periods for any reporting requirements;
 - (v) key dates for the Employer to provide 'services and other things';
 - (vi) key dates for co-ordination with Others.
- 4.1.5 The *Consultant* should provide details of the proposed resources (plant, labour, subConsultants etc.) expected to deliver each activity. This information can either be shown on the programme itself or provided in an associated resource statement included in the Proposal for Providing the Services.
- 4.1.6 The *Consultant* updates the programme every 2 weeks. The *Consultant* submits an updated programme to the *Client* upon request.

5 SERVICES AND OTHER THINGS PROVIDED BY THE *CLIENT*

5.1.1 The following temporary traffic management will be provided by the *Client* to allow the *Consultant* to Provide the Works:

- (1) The traffic management is anticipated to consist of a lane closures and is to be installed after 22:00 and removed before 05:00. TM requirements are to be confirmed by the Consultant.

5.1.2 The other things that will be provided by the *Client* are as follows:

- (1) Not Used

FOR INFORMATION ONLY
DO NOT COMPLETE AT THIS STAGE

6 SPECIFICATION FOR THE SERVICES

- 6.1.1 The *Consultant* shall Provide the Services in accordance with: drawings with the specified area shown on drawing; HE570124-KIER-VTO-M5_MP218.6-216.5-DR-VT-0100_02.
- 6.1.2 The *Consultant* must provide the *works* under a quality management system which is certified to ISO 9001 & BS 11000 and Environmental management system which works to ISO14001.
- 6.1.3 The Topographical Survey is to be carried out in accordance with the Design Manual for Roads and Bridges, Volume 5 Contract Documents for Specialist Activities, Section 1 Geodetic Surveys, Part 2 Specification for Geodetic Surveying Services.
- 6.1.4 Topographical Survey to be carried out to National Grid reference & levels.
- 6.1.5 Permanent control stations shall be established on site, these shall be clearly marked, on both the ground and the completed drawings. These control stations shall be properly installed, x, y and z coordinates recorded and in a position such that they may be used to control future works.
- 6.1.6 Topographical Survey to include: -
- Highway furniture – type, dimensions, offset (e.g. marker posts, steps, guardrails, cabinets etc).
 - Kerb channel level and top of kerb level to be recorded at 10m intervals.
 - Carriageway edges i.e. edge of surfacing to be recorded at 10m intervals.
 - Carriageway road markings to be recorded at 10m intervals as follows:
 - i) Rib line marking between hard strip/ lane 1 – record traffic side of line.
 - ii) Double white lines marking between the eastbound and westbound lanes – record centre of lines.
 - Carriageway levels to be recorded longitudinally at 10m centres along carriageway markings (+/- 2mm).
 - Carriageway edge levels to be recorded longitudinally at 10m centres along back of hard strip (+/- 2mm).
 - Type, level and location (front and back) of any carriageway drainage feature at 10m intervals (levels +/- 2mm), e.g. drainage channel.
 - Traffic face of safety barrier in central reserve and verge to be recorded.

- Level of top of safety barriers to be recorded.
- Ground level adjacent to front of safety barrier to be recorded.
- Type of barrier to be recorded, i.e. steel OBB/TCB or concrete.
- Unless otherwise specified, symbols and annotation in topographic survey drawings shall be suitable for presentation at 1:500 scale.
- Where the objects surveyed extend up or down from ground level, separate layers shall be provided for the ground level lines and the other vertical extent. For example, the tops of walls, fences, ditches shall be in separate layers from their bases.
- Features at ground level shall not cross except at a common point.
- Features that represent closed boundaries shall be geometrically closed.
- Property information relating to point assets (spot levels, references etc) shall be provided as linked attributes, not as unrelated text. Within AutoCAD the association shall be achieved through attributed blocks and within Microstation through tags.
- ADMM codes to be used for Survey Asset Coding.

6.1.7 Output Specification:

- Output data to be in accordance with IAN 184/16 (Highways England Data & CAD Standard).
- Layer naming convention to be added to survey drawings.
- Note/hatching to be added to drawings detailing any problematic areas identified during survey e.g. areas where access was difficult to obtain.
- Control Station coordinates list in suitable format (e.g. Word).