



TECHNICAL PAINT SERVICES

AP91 OIL BASED NON-LEAD WOOD PRIMER

Features:

A high quality, oil bound wood primer which contains no lead pigment. Suitable for application to hard wood, soft wood, plywood, MDF and hardboard. Can be over-painted with any oil or alkyd based system.

Availability:

White, Grey and Pink in 5 and 2.5 Litre containers. Please note our products are made to order and it may take 5-7 days before shipping.

Volume Solids:

48% \pm 3% (BS 3900 Part A10).

Preparation:

The substrate must be thoroughly clean, dry and free from dust and grease.

Application:

By brush or roller. Supplied ready for use for brushing. Use White Spirit for cleaning.

Coverage:

Approximately 50 sq metres per 5 Litres.

Drying:

Touch dry:	1 hour @ 20°C.
Hard dry:	4 hours @ 20°C.
Recoatable:	16 hours.

Health & Safety: Please see MSDS sheet 100D4.

Note: For internal work, maximum ventilation is required. To assist drying if the air flow is insufficient, fans or other mechanical methods of circulating air should be adopted. Precautions must be taken to prevent operators from inhaling the vapours during application.

The foregoing information is given in good faith, based upon tests and experience. It should be noted that recommendations are made without guarantee, as the use of this product is beyond our control. See Standard Conditions of Sale.

The majority of our products are for professional and trade/contractor use only and are not intended for DIY application. Before using any product, please read the appropriate Material Safety Data Sheet and carry out a full risk assessment for the intended use and method of application.

AP91 04 14

FOR PROFESSIONAL USE ONLY. READ DATA BEFORE USE.

27 SOUTHCOTE ROAD BOURNEMOUTH BH1 3SH Tel 01202 295 570 Fax 0845 230 1255
Email enquiries@technicalpaintservices.co.uk www.technicalpaintservices.co.uk

Technical Paint Services is the trading name of Neatcross Ltd. Registered Office as above. Company No: 1570359.