

SSL-I Market Engagement Feb 2022 Clarification Question Responses

Question	Response	Response Date
<p>KUR 3 a. Side ramp or quarter ramp must have a weight capacity of at least 83T.'</p> <p>Do you mean Side ramp, stern ramp or quarter ramp must have a weight capacity of at least 83T?</p>	<p>Apologies there was a mistake in the weight listed previously. The primary means of ramp ingress/egress of the ship must be capable of safely accomodating 75T of load whilst 'self supporting' (ie loading to/from a barge) and 150T whilst 'supported' (ie loading to/from a suitable berth).</p>	14/01/2022
<p>KUR 3 b. Ramps must be self-supporting.'</p> <p>a. What is the weight capacity required for operation in the self-support mode (typically it is 50% of Maximum).</p> <p>b. Do you require 'all' or 'at least one' ramp to be capable of self-supporting?</p>	<p>a. Apologies there was a mistake in the weight listed previously. The primary means of ramp ingress/egress of the ship must be capable of safely accomodating 75T of load whilst 'self supporting' (ie loading to/from a barge) and 150T whilst 'supported' (ie loading to/from a suitable berth).</p> <p>b. As a minimum the Ships shall be capable of un/loading their entire inventory via a single self supporting ramp.</p>	14/01/2022