


## 307685 - HORNIMAN MUSEUM SECURITY CONTROL ROOM

**Luminaire Schedule** 

P01

October 2021



## **Document Revision Control**

Revisions	Date	Reason for Issue	Ву	Approved
P01	15.10.2021	FOR INFORMATION	IH	AJ

Project No: 307685	Project: Horniman	Museum Securi	ty Control Ro	oom			
Luminaire Ref: C1	Engineer: IH	Rev: F	01	<b>Date:</b> 15.10.2021			
General Description	600x600mm LED	modular fitting.					
Location	Refer to Lighting I	ayout drawings f	or specific lo	cation.			
Mounting	Surface mounted	within 600x600 C	Ceiling grid.				
Dimensions / Weight	596 x 596 x 65mm	1					
Lamp Package	46W	46W					
Control Gear	Dimmable N/	A DALI	N/A	DSI N/A	1-10v N/A		
Ingress Protection	-						
Performance	Lumens per Circuit Watt: 100 lm/W Minimum LOR -						
	Colour Rendering	Index	-				
	Colour Temperatu	ire	4000K				
Integral Emergency	Y	DURATION	3hrs	REFERENCE	C1/E		
Manufacturer / Range	Formation Lighting	9	ProForm 600				
Product Web Link	http://www.formati	onlighting.com/p	roduct/profo	<u>rm-600/</u>			
Contact Details	Joe Koch	07710	0563933	http://www.formatio	nlighting.com/		

https://colorconfidence.com/



Manufacturers Web Link

Notes / Special Requirements



Adjusted Driver mA output to be 4000lm output.


Final Finish to be confirmed by Architects.

Revisions		

Project No: 307685	Project: Hornim	Project: Horniman Museum Security Control Room						
Luminaire Ref: DL1	Engineer: IH	Rev: F	<b>P01 Date:</b> 15.10.2021					
General Description	Recessed LED	downlight.						
Location	Refer to Lightin	Refer to Lighting layout drawings for specific location.						
Mounting	Recessed.							
Dimensions / Weight	98 x 183Ø mm,	0.5kg						
Lamp Package	10W							
Control Gear	Dimmable	N/A DALI	N/A	DSI N/A	1-10v	N/A		
Ingress Protection	IP64							
Performance	Lumens per Cir	cuit Watt:	105 lm/W	l				
	Minimum LOR Colour Renderii	na Index	80					
	Colour Tempera		3000K					
Integral Emergency	Y	DURATION	3hrs	REFERENCE	DL1	/E		
Manufacturer / Range	Fagerhult		Pleiad	d G4 165				
Product Web Link	-	erhult.com/Product	s/pleiad-g4/p	oleiad-g4-165/				
Manufacturers Web Link	https://www.fagerhult.com/							
				·				




Notes / Special Requirements




Final Finish to be confirmed by Architects.

Wide Beam light distribution.




Revisions		

Project No: 307685	Project: Horniman Museum Security Control Room						
Luminaire Ref: \$1	Engineer: IH	Engineer:         IH         Rev: P01         Date: 15.10.2021					
General Description	Linear LED lum	inaire.					
Location	Refer to Lightin	g layout drawings	for specific lo	ocation.			
Mounting	Ceiling mounte	d.					
Dimensions / Weight	1700L x 55W m	ım, 1.8kg					
Lamp Package	48W, 5700 lm						
Control Gear	Dimmable	N/A <b>DAL</b>	I N/A	DSI N/A	1-10v N/A		
Ingress Protection	IP20						
Performance	Lumens per Cir	Lumens per Circuit Watt: 112 lm/W					
	Minimum LOR	Minimum LOR		-			
	Colour Renderi	ng Index	80	80			
	Colour Tempera	ature	4000K	4000K			
Integral Emergency	Y	DURATION	3hrs	REFERENCE	S1/E		
Manufacturer / Range	Formation Lighting Strong 55						
Product Web Link	http://www.form	ationlighting.com	/product/s55/				
Manufacturers Web Link	· ·	ationlighting.com					
Notes / Special Requirements	rements Final Finish to be confirmed by Architects.						



Revisions		

Project No: 30768	35	Project: Horniman Museum Security Control Room							
Luminaire Ref:	WL1	Engineer: II	4	Rev: P	01				
General Description	on	Wall surface	mounted LE	D luminair	e.				
Location		Refer to Light	ting layout d	rawings fo	r specific lo	ocation.			
Mounting		Wall mounted	d.						
Dimensions / Weig	ght	250L x 134W	mm x 42D ı	mm, 1.2kg					
Lamp Package		32W, 3337 Im	32W, 3337 lm						
Control Gear		Dimmable	N/A	DALI	N/A	DSI N/A	1-10v	N/A	
Ingress Protection	1	IP20							
Performance		Lumens per (	Lumens per Circuit Watt:			106 lm/W			
		Minimum LO	Minimum LOR			-			
		Colour Rende	Colour Rendering Index			90			
		Colour Temperature			3000K				
Integral Emergence	cy .	N	DURA	TION		REFERENCE			
Manufacturer / Ra		Delta Light			Gala XL HP 930 DIM1				
	_	https://www.deltalight.com/en/products/detail/gala-xl-hp-930-dim1-275-162-93-ed1							



https://www.deltalight.com/en

Final Finish to be confirmed by Architects.

Revisions		

Manufacturers Web Link


Notes / Special Requirements


Project No: 3076	85	Project: Horniman Museum Security Control Room		
Luminaire Ref:	LED1	Engineer: IH	Rev: P01	<b>Date:</b> 15.10.2021

General Description	Decorative LED tape.					
	= ==================================					
Location	Refer to Lighting layout draw	rings for specific lo	cation.			
Mounting	Surface mounted					
Dimensions / Weight	33.3mm					
Lamp Package	13.2W, 900lm					
Lamp r dokago	10.244, 000111					
Control Gear	Dimmable Y I	DALI N/A	DSI N/A	<b>1-10v</b> N/A		
Ingress Protection	IP20					
ingress i rotection	11 20					
Performance	Lumens per Circuit Watt :	-				
	Minimum LOR	-				
	Colour Rendering Index	-				
	Colour Temperature	3000K				
Integral Emergency	N DURATIO		REFERENCE	N/A		
Manufacturer / Range	Formation Lighting	PRO	STRIP LINEAR			
Draduat Wab Link	http://www.formerticulishting.com/product/proteins/					

Integral Emergency	N DUR	ATION	N/A	REFERENCE	N/A	
Manufacturer / Range	Formation Lighting		PROSTRIP LINEAR			
Product Web Link	http://www.formationlighting.com/product/prostrip-led/					
Contact Details	Joe Koch 07710563933		63933	http://www.formatio	nlighting.com/	
Manufacturers Web Link	http://www.formationlighting.com/					
Notes / Special Requirements	Opal Diffuser to be utilised.					







Revisions		

Project No: 307685		Project: Horniman Museum Security Control Room								
Luminaire Ref:	uminaire Ref: <b>EXIT</b>		er: IH	Rev: P	01	Date: 1	Date: 15.10.2021			
General Description	Er	Emergency exit luminaire sign for use over final exits and proposed areas.								
Location		Refer to Lighting layout drawings for specific location.								
Mounting		Surface mounted to ceiling.								
Dimensions / Weight		310mm x 160mm x 20mm								
Lamp Package		-								
Control Gear	Di	immable	N/A	DALI	N/A	DSI	N/A	1-10v	N/A	
Ingress Protection -										
Performance		Lumens per Circuit Watt :			-					
		Minimum LOR			-					
		Colour Rendering Index			-					
		Colour Temperature			-					
Integral Emergency		Υ	DUI	RATION	3hrs	R	EFERENCE	EXI	Т	
Manufacturer / Range		Zumtobel Puresign								
Product Web Link		https://www.zumtobel.com/gb-en/products/pure_comsign.html?&GUID=E0662701-020B-4A46-A647-9C973C88AB34								
Manufacturers Web Link	<u>ht</u>	https://www.zumtobel.com/gb-en/index.html								
Notes / Special Requiren		Ceiling attachment required								
	-	3-Hour version (All finishes to be confirmed with client/architects prior to ordering)								



Revisions		



## The Multi-disciplinary Engineering Consultancy

\_\_\_

London | Glasgow | Edinburgh

## Contact

Ground Floor 45 Great Guildford Street London, SE1 0ES enquiries@harleyhaddow.com