

## **Powick Pavillion Internal, External Door & Window Schedule**

Produced By: Jason Yarwood

Revision: A 14/02/2020

Tender Issue

Door No	Location	Lining & Architrave	Door Size	Style	Furniture
D1	Store	32mm Softwood door lining, 69mm softwood square edge architrave. All cut edges to be sealed before fixing in place.	838 x 1981mm	FD30 Oak Veneer door - Any edges trimmed to be sealed on completion	New 1 & 1/2 pairs of 100 x 75 x 3mm twin ball bearing stainless fire door hinges, Intumescent hinge liners, Intumescent seals to Frame, FD30 Satin Stainless overhead closer, 19mm dia satin stainless 300mm D handle. Satin stainless push plate, Euro cylinder with thumb turn, Satin stainless escutcheons, Satin stainless Store sign, Satin stainless kickplates, Stainless fixings to all ironmongery.
D2	Electrics Cupboard	32mm Softwood door lining, 69mm softwood square edge architrave. All cut edges to be sealed before fixing in place.	838 x 1981mm	FD30 Oak Veneer door - Any edges trimmed to be sealed on completion	New 1 & 1/2 pairs of 100 x 75 x 3mm twin ball bearing stainless fire door hinges, Intumescent hinge liners, Intumescent seals to Frame, FD30 Satin Stainless overhead closer, 19mm dia satin stainless 300mm D handle. Satin stainless push plate, Euro cylinder with thumb turn, Satin stainless escutcheons, Stainless fire door keep shut sign, Satin stainless kickplates, Stainless fixings to all ironmongery.
D3	Kitchen	32mm Softwood door lining, 69mm softwood square edge architrave. All cut edges to be sealed before fixing in place.	838 x 1981mm	16G clear glass FD30 Oak Veneer door - Any edges trimmed to be sealed on completion	1 & 1/2 pairs of Heavy duty satin stainless FD30 150mm double action spring hinges, Intumescent hinge liners, Intumescent seals to Frame, Satin stainless push plates, Stainless fire door sign, Satin stainless kickplates, Stainless fixings to all ironmongery.
D4	W.C	32mm Softwood door lining, 69mm softwood square edge architrave. All cut edges to be sealed before fixing in place.	838 x 1981mm	FD30 Oak Veneer door - Any edges trimmed to be sealed on completion	New 1 & 1/2 pairs of 100 x 75 x 3mm twin ball bearing stainless fire door hinges, FD30 Satin stainless overhead closer, 19mm dia satin stainless 300mm D handle. Satin stainless push plate, Satin Stainless DDA Compliant Thumb Turn/ Release with Indicator, Satin stainless kickplates, Stainless w.c sign, Stainless fixings to all ironmongery.
D5	W.C	32mm Softwood door lining, 69mm softwood square edge architrave. All cut edges to be sealed before fixing in place.	838 x 1981mm	FD30 Oak Veneer door - Any edges trimmed to be sealed on completion	New 1 & 1/2 pairs of 100 x 75 x 3mm twin ball bearing stainless fire door hinges, FD30 Satin stainless overhead closer, 19mm dia satin stainless 300mm D handle. Satin stainless push plate, Satin Stainless DDA Compliant Thumb Turn/ Release with Indicator, Satin stainless kickplates, Stainless w.c sign, Stainless fixings to all ironmongery.

D6	DDA W.C	32mm Softwood door lining, 69mm softwood square edge architrave. All cut edges to be sealed before fixing in place.	914 x 1981mm	FD30 Oak Veneer door - Any edges trimmed to be sealed on completion	New 1 & 1/2 pairs of 100 x 75 x 3mm twin ball bearing stainless fire door hinges, FD30 Satin stainless overhead closer, 19mm dia satin stainless 300mm D handle. Satin stainless push plate, Satin Stainless DDA Compliant Thumb Turn/ Release with Indicator, Satin stainless kickplates, Stainless w.c sign, Stainless fixings to all ironmongery.
D7	To Changing Room Corridor	32mm Softwood door lining, 69mm softwood square edge architrave. All cut edges to be sealed before fixing in place.	838 x 1981mm	16G clear glass FD30 Oak Veneer door - Any edges trimmed to be sealed on completion	New 1 & 1/2 pairs of 100 x 75 x 3mm twin ball bearing stainless fire door hinges, Intumescent hinge liners, Intumescent seals to Frame, FD30 Satin Stainless overhead closer, 19mm dia satin stainless 300mm D handle. Satin stainless push plate, Satin stainless kickplates, Stainless fixings to all ironmongery.
D8	Referee Changing Room	32mm Softwood door lining, 69mm softwood square edge architrave. All cut edges to be sealed before fixing in place.	838 x 1981mm	FD30 Oak Veneer door - Any edges trimmed to be sealed on completion	New 1 & 1/2 pairs of 100 x 75 x 3mm twin ball bearing stainless fire door hinges, Intumescent hinge liners, Intumescent seals to Frame, FD30 Satin Stainless overhead closer, 19mm dia satin stainless 300mm D handle. Satin stainless push plate, Euro cylinder with thumb turn, Satin stainless escutcheons, Satin stainless Referee sign, Satin stainless kickplates, Stainless fixings to all ironmongery.
D9	Referee Shower	12mm solid grade laminate pilasters fixed to blockwork opening with anodised brackets	Structral Opening: 800 x 2025mm	12mm solid grade laminate cubicle door with 100mm gap top and bottom	12mm solid grade laminate cubicle door with anodised aluminium door latch and exterior indicator with nylon bolt fixed to 100mm pilasters either side, secured to blockwork opening. Door to have safe edge anti finger trap gap between door and vertical frame section.
D10	Referee W.C	32mm Softwood door lining, 69mm softwood square edge architrave. All cut edges to be sealed before fixing in place.	726 x 1981mm	FD30 Oak Veneer door Allow 10mm gap under door - Any edges trimmed to be sealed on completion	New 1 & 1/2 pairs of 100 x 75 x 3mm twin ball bearing stainless fire door hinges, FD30 Satin stainless overhead closer, 19mm dia satin stainless 300mm D handle. Satin stainless push plate, Satin Stainless DDA Compliant Thumb Turn/ Release with Indicator, Satin stainless kickplates, Stainless fixings to all ironmongery.
D11	Changing Room 2	32mm Softwood door lining, 69mm softwood square edge architrave. All cut edges to be sealed before fixing in place.	838 x 1981	FD30 Oak Veneer door - Any edges trimmed to be sealed on completion	New 1 & 1/2 pairs of 100 x 75 x 3mm twin ball bearing stainless fire door hinges, Intumescent seals to Frame, FD30 Satin Stainless overhead closer, 19mm dia satin stainless 300mm D handle. Satin stainless push plate, Euro cylinder with thumb turn, Satin stainless escutcheons, Satin stainless Changing Room 1 sign, Satin stainless kickplates, Stainless fixings to all ironmongery.

D12	Changing Room 2 Lobby	32mm Softwood door lining, 69mm softwood square edge architrave. All cut edges to be sealed before fixing in place.	838 x 1981	FD30 Oak Veneer door - Any edges trimmed to be sealed on completion	New 1 & 1/2 pairs of 100 x 75 x 3mm twin ball bearing stainless fire door hinges, Intumescent hinge liners, Intumescent seals to Frame, FD30 Satin Stainless overhead closer, 19mm dia satin stainless 300mm D handle. Satin stainless push plate, Satin stainless kickplates, Stainless fixings to all ironmongery.
D13	Changing Room 2 W.C	12mm solid grade laminate pilasters fixed to blockwork opening with anodised brackets	Structral Opening: 850 x 2025mm	12mm solid grade laminate cubicle door with 100mm gap top and bottom	12mm solid grade laminate cubicle door with anodised aluminium door latch and exterior indicator with nylon bolt fixed to 100mm pilasters either side, secured to blockwork opening. Door to have safe edge anti finger trap gap between door and vertical frame section. 1no. nylon coat hook fixed to back of the door.
D14	Changing Room 2 W.C	12mm solid grade laminate pilasters fixed to blockwork opening with anodised brackets	Structral Opening: 850 x 2025mm	12mm solid grade laminate cubicle door with 100mm gap top and bottom	12mm solid grade laminate cubicle door with anodised aluminium door latch and exterior indicator with nylon bolt fixed to 100mm pilasters either side, secured to blockwork opening. Door to have safe edge anti finger trap gap between door and vertical frame section. 1no. nylon coat hook fixed to back of the door.
D15	Changing Room 1	32mm Softwood door lining, 69mm softwood square edge architrave. All cut edges to be sealed before fixing in place.	838 x 1981mm	FD30 Oak Veneer door - Any edges trimmed to be sealed on completion	New 1 & 1/2 pairs of 100 x 75 x 3mm twin ball bearing stainless fire door hinges, Intumescent hinge liners, Intumescent seals to Frame, FD30 Satin Stainless overhead closer, 19mm dia satin stainless 300mm D handle. Satin stainless push plate, Euro cylinder with thumb turn, Satin stainless escutcheons, Satin stainless Changing Room 1 sign, Satin stainless kickplates, Stainless fixings to all ironmongery.
D16	Changing Room 1 Lobby	32mm Softwood door lining, 69mm softwood square edge architrave. All cut edges to be sealed before fixing in place.	838 x 1981mm	FD30 Oak Veneer door - Any edges trimmed to be sealed on completion	New 1 & 1/2 pairs of 100 x 75 x 3mm twin ball bearing stainless fire door hinges, Intumescent hinge liners, Intumescent seals to Frame, FD30 Satin Stainless overhead closer, 19mm dia satin stainless 300mm D handle. Satin stainless push plate, Satin stainless kickplates, Stainless fixings to all ironmongery.
D17	Changing Room 1 W.C	12mm solid grade laminate pilasters fixed to blockwork opening with anodised brackets	Structral Opening: 850 x 2025mm	12mm solid grade laminate cubicle door with 100mm gap top and bottom	12mm solid grade laminate cubicle door with anodised aluminium door latch and exterior indicator with nylon bolt fixed to 100mm pilasters either side, secured to blockwork opening. Door to have safe edge anti finger trap gap between door and vertical frame section. 1no. nylon coat hook fixed to back of the door.

D18	Changing Room 1 W.C	12mm solid grade laminate pilasters fixed to blockwork opening with anodised brackets	Structral Opening: 850 x 2025mm	12mm solid grade laminate cubicle door with 100mm gap top and bottom	12mm solid grade laminate cubicle door with anodised aluminium door latch and exterior indicator with nylon bolt fixed to 100mm pilasters either side, secured to blockwork opening. Door to have safe edge anti finger trap gap between door and vertical frame section. 1no. nylon coat hook fixed to back of the door.
ED1	Social Space	Part of the door manufacturing	Structral Opening: 4000 x 2100mm high	Powder coated RAL7016 Anthracite thermally broken bifold doors with 28mm clear toughened glass, low-e argon filled & warm edge spacer units top and bottom with aluminium level threshold cill	silver hardware, Lever handle, euro cylinder with thumb turn.
ED2	Social Space Corridor	Part of the door manufacturing	Structral Opening: 1600 x 2100mm high	Powder coated RAL7016 Anthracite thermally broken double doors with 28mm clear toughened glass, low-e argon filled & warm edge spacer units top and bottom with aluminium level threshold cill	silver hardware, Lever handle with escape push pad internally & flush bolts.
ED3	Changing Room Corridor	Part of the door manufacturing	Structral Opening: 1600 x 2100mm high	Powder coated RAL7016 Anthracite thermally broken double doors with 28mm clear toughened glass, low-e argon filled & warm edge spacer units top and bottom with aluminium level threshold cill	silver hardware, Lever handle with escape push pad internally & flush bolts.
ED4	Store 2	Part of the door manufacturing	Structral Opening: 1600 x 2100mm high	Design & Supply or similar powder coated RAL7016 Anthracite, 1.5mm zintec steel double doors with a Rocksilk 45 core with aluminium level threshold cill	Stays to prevent opening past 90 degrees, euro cylinder turn and pull handle & flush bolts.
ED5	Plant Room	Part of the door manufacturing	Structral Opening: 1100 x 2100mm high	Design & Supply or similar powder coated RAL7016 Anthracite, 1.5mm zintec steel door with a louvered top panel with fly mesh and lower Rocksilk 45 core panel with aluminium level threshold cill.	Stays to prevent opening past 90 degrees, euro cylinder turn and pull handle.
ED6	Bin Store	Part of the door manufacturing	Structral Opening: 1360 x 2100mm high	Design & Supply or similar powder coated RAL7016 Anthracite, 1.5mm zintec steel 1&1/2 doors with a Rocksilk 45 core with aluminium level threshold cill	Stays to prevent opening past 90 degrees, euro cylinder with thumb turn, satin stainless pull handle, flush bolts to half leaf.

W1	Social Space	Part of the window manufacturing	Structral Opening: 3000 x 2100mm high	Powder coated RAL7016 Anthracite thermally broken window with 28mm clear toughened glass, low-e argon filled with warm edge spacer & trickle vents	No Ironmongery required as a fixed casement
W2	Kitchen	Part of the window manufacturing	Structral Opening: 1800mm x1200mm high	Horizontally sliding powder coated RAL7016 Anthracite thermally broken window with 28mm clear toughened glass, low-e argon filled with warm edge spacer & trickle vents	Silver lockable fitch catch