



Ministry
of Defence

Defence Standard 68-284 Part 04

Issue 1

Date: 28 October 2020

Breathing Gases for Non-Medicinal Life-Support Applications

Part: 04 : Breathing Gas Mixtures

Section 1

Foreword

Defence Standard Structure

Section 1 (Generated by the StanMIS toolset)

- Revision Note
- Historical Record
- Warning
- Standard Clauses

Section 2 (Technical information provided by Subject Matter Expert)

- Title
- Introduction (optional)
- Table of Contents
- Scope
- Technical Information to include Tables and Figures
- Annexes (as required)

Section 3 (Generated by StanMIS toolset)

- Normative References
- Definitions
- Abbreviation

REVISION NOTE

A long overdue revision to keep the Def Stan aligned with applicable civil / military standards to keep it up-to-date and relevant. Defence Standard 68-284 has been re-issued in 4 new Parts.

HISTORICAL RECORD

This standard supersedes the following:

Def Stan 68-284 Issue 3 Dated 03 April 2009;

Def Stan 68-284 Issue 2 Dated 8 November 2002;

Def Stan 68-284 Issue 1 Dated 12 October 2001;

Def Stan 68-75 Issue 3 Dated 30 June 1995;

Def Stan 68-75 Issue 2 Dated 23 April 1993;

Def Stan 16-8 Issue 4 Dated 19 February 1993;

Def Stan 16-1 Issue 3 Dated 16 October 1992;

Def Stan 68-75 Issue 1 Dated 31 March 1983;

Def Stan 16-8 Issue 3 Dated 31 May 1977;

Def Stan 16-1 Issue 2 Dated 18 July 1972;

Def Stan 16-8 Issue 2 Dated 10 February 1972;

DEF STAN 68-284 Part 04 Issue 1

WARNING

The Ministry of Defence (MOD), like its contractors, is subject to both United Kingdom and European laws regarding Health and Safety at Work. Many Defence Standards set out processes and procedures that could be injurious to health if adequate precautions are not taken. Adherence to those processes and procedures in no way absolves users from complying with legal requirements relating to Health and Safety at Work.

STANDARD CLAUSES

- a) This standard has been published on behalf of the Ministry of Defence (MOD) by UK Defence Standardization (DStan).
- b) This standard has been reached following broad consensus amongst the authorities concerned with its use and is intended to be used whenever relevant in all future designs, contracts, orders etc. and whenever practicable by amendment to those already in existence. If any difficulty arises which prevents application of the Defence Standard, DStan shall be informed so that a remedy may be sought.
- c) Please address any enquiries regarding the use of this standard in relation to an invitation to tender or to a contract in which it is incorporated, to the responsible technical or supervising authority named in the invitation to tender or contract.
- d) Compliance with this Defence Standard shall not in itself relieve any person from any legal obligations imposed upon them.
- e) This standard has been devised solely for the use of the MOD and its contractors in the execution of contracts for the MOD. To the extent permitted by law, the MOD hereby excludes all liability whatsoever and howsoever arising (including, but without limitation, liability resulting from negligence) for any loss or damage however caused when the standard is used for any other purpose.

Section 2

Breathing Gases for Non-Medicinal Life-Support Applications

Part 04: Breathing Gas Mixtures

Introduction

The Defence Standard (Def Stan) aims to provide a unified gas standard to encompass non-medicinal breathing gases procured or in-situ produced for use in Ministry of Defence (MOD) aircraft, diving and marine life-support applications. It provides specifications for, including purity requirements and contaminant limits, breathing gases procured or in-situ produced for aircraft, diving and marine non-medicinal life-support applications. It includes compressed natural breathing air (CNBA), oxygen / helium mixtures (Heliox), oxygen / nitrogen mixtures (Nitrox), oxygen / nitrogen / helium mixtures (Trimix), molecular sieve oxygen concentrating system (MSOCS) product gas, and breathing oxygen (in liquid and gaseous forms), for use by the MOD.

It is arranged in four parts as follows:

- Part 01: Supply Requirements
- Part 02: Breathing Oxygen
- Part 03: Compressed Natural Breathing Air
- Part 04: Breathing Gas Mixtures

The technical authority of this Def Stan is the Defence Strategic Fuels Authority, MOD Abbey Wood, Bristol BS34 8JH, United Kingdom. The Def Stan is produced on behalf of the MOD operating communities.

Scope

This part of the Def Stan specifies the requirements for non-medicinal breathing gas mixtures procured for marine / diving life-support and hyperbaric applications on board HM ships and submarines, and provides reference methods of test.

- These breathing gas mixtures are oxygen / helium mixtures (Heliox), oxygen / nitrogen mixtures (Nitrox) and oxygen / helium / nitrogen mixtures (Trimix).
- Medicinal breathing gas mixtures are excluded as they are covered by the European Pharmacopoeia monograph, however, where breathing gas mixtures are to be used for therapeutic purposes at pressure, ie. during recompression treatments and hyperbaric therapy, they should comply with the requirements of this part of the Def Stan.
- Reference methods of test are provided to give guidance on testing. They are not prescriptive, and alternative methods (AMs), which have been demonstrated in specific cases to DSFA's satisfaction to produce results adequate for the measurand, are acceptable.

List of Contents

Section 2..... 2-1

Introduction 2-1

Scope..... 2-1

Technical Content..... 2-3

1. Breathing Oxygen / Helium Mixtures (Heliox)..... 2-3

 1.1. Requirements 2-3

 1.2. Production Method 2-3

 1.3. Supply..... 2-3

 1.4. Label..... 2-3

 1.5. Quality Assurance – Procured..... 2-3

 1.6. Pre-Use Testing..... 2-3

2. Breathing Oxygen / Nitrogen Mixtures (Nitrox) 2-3

 2.1. Requirements 2-3

 2.2. Production Method 2-3

 2.3. Supply..... 2-3

 2.4. Label..... 2-3

 2.5. Quality Assurance – Procured..... 2-4

 2.6. Pre-Use Testing..... 2-4

3. Breathing Oxygen / Helium / Nitrogen Mixtures (Trimix) 2-4

 3.1. Requirements 2-4

 3.2. Production Method 2-4

 3.3. Supply..... 2-4

 3.4. Label..... 2-4

 3.5. Quality Assurance – Procured..... 2-4

 3.6. Pre-Use Testing..... 2-4

Table 1 Purity requirements for breathing oxygen / helium mixtures (Heliox) 2-5

Table 2 Purity requirements for breathing oxygen / nitrogen mixtures (Nitrox)..... 2-6

Table 3 Purity requirements for breathing oxygen / helium / nitrogen mixtures (Trimix) 2-7

Technical Content

1. Breathing Oxygen / Helium Mixtures (Heliox)

1.1. Requirements

Requirements for breathing oxygen / helium mixtures (Heliox) procured are aligned with requirements specified in NATO STANAG 1458 and BS EN 12021, and shall comply with the requirements of Table 1 in respect of purity and moisture. The required nominal oxygen content shall be specified in the relevant contract between the purchaser and the supplier.

1.2. Production Method

The standard method of production of Heliox shall be by mixing appropriate proportions of applicable gases.

1.3. Supply

Cylinders and manifolded cylinder packs (MCPs) for Heliox shall be supplied to the MOD in accordance with Part 1 of the Def Stan.

1.4. Label

Cylinders and MCPs are to be marked as conforming to the Def Stan shall have the marking "Def Stan 68-284 Heliox ϕ " suitably annotated on the cylinder shoulders for cylinders and on the frames for MCPs. Here " ϕ " indicates the nominal oxygen content, eg "Def Stan 68-284 Heliox 14" for 14%(v) nominal oxygen content.

1.5. Quality Assurance – Procured

1.5.1. Certification. Suppliers shall provide a Certificate of Conformity (CoC) to the requirements with each delivery of Heliox.

1.5.2. Receipt. If the product being delivered does not have a valid CoC, or any damage to the cylinders and MCPs is evident, the whole delivery shall be rejected.

1.6. Pre-Use Testing

Users shall carry out odour and moisture tests on a representative selection of Heliox cylinders and MCPs before they are put into service. Cylinders and MCPs that fail to meet the odour or moisture requirement specified in Table 1 should be declared unserviceable and returned in accordance with Defence Logistic Framework (DLF). Refer to JSP 319 Part 2 for details.

2. Breathing Oxygen / Nitrogen Mixtures (Nitrox)

2.1. Requirements

Requirements for breathing oxygen / nitrogen mixtures (Nitrox) procured are aligned with requirements specified in NATO STANAG 1458 and BS EN 12021, and shall comply with the requirements of Table 2 in respect of purity and moisture. The required nominal oxygen content shall be specified in the relevant contract between the purchaser and the supplier.

2.2. Production Method

The standard method of production of Nitrox shall be by mixing appropriate proportions of applicable gases.

2.3. Supply

Cylinders and manifolded cylinder packs (MCPs) for Nitrox shall be supplied to the MOD in accordance with Part 1 of the Def Stan.

2.4. Label

Cylinders and MCPs are to be marked as conforming to the Def Stan shall have the marking "Def Stan 68-284 Nitrox ϕ " suitably annotated on the cylinder shoulders for cylinders and on the frames for MCPs. Here " ϕ " indicates the nominal oxygen content, eg "Def Stan 68-284 Nitrox 14" for 14%(v) nominal oxygen content.

2.5. Quality Assurance – Procured

2.5.1. *Certification.* Suppliers shall provide a Certificate of Conformity (CoC) to the requirements with each delivery of Nitrox.

2.5.2. *Receipt.* If the product being delivered does not have a valid CoC, or any damage to the cylinders and MCPs is evident, the whole delivery shall be rejected.

2.6. Pre-Use Testing

Users shall carry out odour and moisture tests on a representative selection of Nitrox cylinders and MCPs before they are put into service. Cylinders and MCPs that fail to meet the odour or moisture requirement specified in Table 2 should be declared unserviceable and returned in accordance with Defence Logistic Framework (DLF). Refer to JSP 319 Part 2 for details.

3. Breathing Oxygen / Helium / Nitrogen Mixtures (Trimix)

3.1. Requirements

Requirements for breathing oxygen / helium / nitrogen mixtures (Trimix) procured are aligned with requirements specified in NATO STANAG 1458 and BS EN 12021, and shall comply with the requirements of Table 3 in respect of purity and moisture. The required nominal oxygen content and helium content shall be specified in the relevant contract between the purchaser and the supplier.

3.2. Production Method

The standard method of production of Trimix shall be by mixing appropriate proportions of applicable gases.

3.3. Supply

Cylinders and manifolded cylinder packs (MCPs) for Trimix shall be supplied to the MOD in accordance with Part 1 of the Def Stan.

3.4. Label

Cylinders and MCPs are to be marked as conforming to the Def Stan shall have the marking "Def Stan 68-284 Trimix ϕ/λ " suitably annotated on the cylinder shoulders for cylinders and on the frames for MCPs. Here " ϕ " and " λ " indicate the nominal oxygen content and helium content, respectively, eg "Def Stan 68-284 Trimix 16/40" for 16%(v) nominal oxygen content and 40%(v) nominal helium content.

3.5. Quality Assurance – Procured

3.5.1. *Certification.* Suppliers shall provide a Certificate of Conformity (CoC) to the requirements with each delivery of Trimix.

3.5.2. *Receipt.* If the product being delivered does not have a valid CoC, or any damage to the cylinders and MCPs is evident, the whole delivery shall be rejected.

3.6. Pre-Use Testing

Users shall carry out odour and moisture tests on a representative selection of Trimix cylinders and MCPs before they are put into service. Cylinders and MCPs that fail to meet the odour or moisture requirement specified in Table 3 should be declared unserviceable and returned in accordance with Defence Logistic Framework (DLF). Refer to JSP 319 Pt 2 for details.

DEF STAN 68-284 Part 04 Issue 1

Table 1 Purity requirements for breathing oxygen / helium mixtures (Heliox).

Contaminant / Constituent / Property		Limit	Test Method	Note
Odour		Free from unacceptable odour	BS EN 12021 NA.5	1a, & 2
Moisture (dew point)		-64°C max	BS ISO 8573-3 Table 2, 4 or 6	1b
Oxygen (O ₂)	$\phi \leq 10\%(v)$	$\phi \pm 0.25\%(v)$	BS EN 12021 NA.11	1a, & 6
	$10\%(v) < \phi \leq 20\%(v)$	$\phi \pm 0.5\%(v)$		
	$\phi > 20\%(v)$	$\phi \pm 1.0\%(v)$		
Carbon Dioxide (CO ₂)		5 ppm(v) max	BS EN 12021 NA.7 or 8	1a
Carbon Monoxide (CO)		1 ppm(v) max	BS EN 12021 NA.7 or 8	1b
Oil		0.1 mg/m ³ max	BS EN 12021 NA.15	3, & 9
Total volatile hydrocarbons (vapour or gas) as Methane (CH ₄) equivalent		30 ppm(v) max	BS EN 12021 NA.7 or 8	1a
Hydrogen (H ₂)		10 ppm(v) max	BS EN 12021 NA.12	1a
Total non-toxic gases (exclude Helium (He))	$\phi \leq 10\%(v)$	0.1%(v) max	BS EN 12021 NA.10	1b, 4, & 6
	$10\%(v) < \phi \leq 20\%(v)$	0.2%(v) max		
	$\phi > 20\%(v)$	0.5%(v) max		1a, 4, & 6
Other toxic / irritating substance (each substance)		TBA	BS EN 12021 NA.7	5, 7, & 8

Note:

1. No change from Def Stan 68-284 Issue 3.
 - a. The limit is the same as that specified in NATO STANAG 1458 and BS EN 12021.
 - b. The limit is the same as that specified in NATO STANAG 1458 and is a more restrictive limit than that specified in BS EN 12021.
2. Free from unacceptable odour that may have an adverse effect on the user or breathing apparatus.
3. Oil may be present due to previous contamination, use of oil lubricated compressor or use of gases with oil vapour present.
4. These gases include nitrogen (N₂), argon (Ar) and all other noble gases, but exclude helium (He).
5. Where substances other than those listed are found, the substances shall be identified and reported to the applicable authority for determination of maximum limits and appropriate test methods based on the sensitivity and specificity of the methods.
6. Nominal oxygen content (ϕ) as specified in the relevant contract between the purchaser and the supplier.
7. It should be noted that the limit should not be greater than one tenth (1/10) of the 8-hour time weighted average Workplace Exposure Limit (WEL) given in the Health & Safety Executive publication, Workplace Exposure Limits (EH40).
8. Where the gaseous trace contaminants are detected by FTIR analysis but cannot fully identified, they shall be quantified using gas chromatography - mass spectrometry (GC-MS) or other alternative methods (AMs). This approach is the same as that given in Def Stan 68-284 Issue 3 A.6 Method for the Determination of Other Trace Contaminants.
9. The limit 0.01 mg/m³ specified in Def Stan 68-284 Issue 3 is believed to be a typo error. This is corrected to 0.1 mg/m³ aligning it to the same as that specified in NATO STANAG 1458 and BS EN 12021.

DEF STAN 68-284 Part 04 Issue 1

Table 2 Purity requirements for breathing oxygen / nitrogen mixtures (Nitrox).

Contaminant / Constituent / Property	Limit	Test Method	Note
Odour	Free from unacceptable odour	BS EN 12021 NA.5	1a, & 2
Moisture (dew point)	-64°C max	BS ISO 8573-3 Table 2, 4 or 6	1b
Oxygen (O ₂)	$\phi \pm 0.5\%(v)$	BS EN 12021 NA.11	1c, 5, & 10
Carbon Dioxide (CO ₂)	5 ppm(v) max	BS EN 12021 NA.7 or 8	1a
Carbon Monoxide (CO)	1 ppm(v) max	BS EN 12021 NA.7 or 8	1b
Oil	0.1 mg/m ³ max	BS EN 12021 NA.15	3, & 9
Total volatile hydrocarbons (vapour or gas) as Methane (CH ₄) equivalent	30 ppm(v) max	BS EN 12021 NA.7 or 8	1a
Total non-toxic gases (exclude Nitrogen (N ₂))	0.5%(v) max	BS EN 12021 NA.10	1b, & 4
Other toxic / irritating substance (Each Substance)	TBA	BS EN 12021 NA.7	6, 7, & 8

Note:

1. No change from Def Stan 68-284 Issue 3.
 - a. The limit is the same as that specified in NATO STANAG 1458 and BS EN 12021.
 - b. The limit is the same as that specified in NATO STANAG 1458 and is a more restrictive limit than that specified in BS EN 12021.
 - c. The limit for oxygen content less than 40% is unchanged. It is the same as that specified in NATO STANAG 1458, and same as that specified in BS EN 12021 for oxygen content up to 20%(v).
2. Free from unacceptable odour that may have an adverse effect on the user or breathing apparatus.
3. Oil may be present due to previous contamination, use of oil lubricated compressor or use of gases with oil vapour present.
4. These gases include argon (Ar), helium (He) and all other noble gases, but exclude nitrogen (N₂).
5. Nominal oxygen content (ϕ) as specified in the relevant contract between the purchaser and the supplier.
6. Where substances other than those listed are found, the substances shall be identified and reported to the applicable authority for determination of maximum limits and appropriate test methods based on the sensitivity and specificity of the methods.
7. It should be noted that the limit should not be greater than one tenth (1/10) of the 8-hour time weighted average Workplace Exposure Limit (WEL) given in the Health & Safety Executive publication, Workplace Exposure Limits (EH40).
8. Where the gaseous trace contaminants are detected by FTIR analysis but cannot fully identified, they shall be quantified using gas chromatography - mass spectrometry (GC-MS) or other alternative methods (AMs). This approach is the same as that given in Def Stan 68-284 Issue 3 A.6 Method for the Determination of Other Trace Contaminants.
9. The limit 0.01 mg/m³ specified in Def Stan 68-284 Issue 3 is believed to be a typo error. This is corrected to 0.1 mg/m³ aligning it to the same as that specified in NATO SATNAG 1458 and BS EN 12021.
10. The limit for oxygen content above 40% specified in Def Stan 68-284 Issue 3 is revised to align with that specified in NATO STANAG 1458. It is a more restrictive limit than that specified in in Def Stan 68-284 Issue 3 and BS EN 12021.

DEF STAN 68-284 Part 04 Issue 1

Table 3 Purity requirements for breathing oxygen / helium / nitrogen mixtures (Trimix).

Contaminant / Constituent / Property		Limit	Test Method	Note
Odour		Free from unacceptable odour	BS EN 12021 NA.5	1a, & 2
Moisture (dew point)		-64°C max	BS ISO 8573-3 Table 2, 4 or 6	1b
Oxygen (O ₂)	$\phi \leq 10\%(v)$	$\phi \pm 0.25\%(v)$	BS EN 12021 NA.11	1a, & 5
	$10\%(v) < \phi \leq 20\%(v)$	$\phi \pm 0.5\%(v)$		
	$\phi > 20\%(v)$	$\phi \pm 1.0\%(v)$		
Helium (He)	$\lambda \leq 20\%(v)$	$\lambda \pm 0.5\%(v)$	BS EN 12021 NA.14	1b, 5, & 6
	$\lambda > 20\%(v)$	$\lambda \pm 1.0\%(v)$		1a, & 5
Carbon Dioxide (CO ₂)		5 ppm(v) max	BS EN 12021 NA.7 or 8	1a
Carbon Monoxide (CO)		1 ppm(v) max	BS EN 12021 NA.7 or 8	1b
Oil		0.1 mg/m ³ max	BS EN 12021 NA.15	3, & 10
Total volatile hydrocarbons (vapour or gas) as Methane (CH ₄) equivalent		25 ppm(v) max	BS EN 12021 NA.7 or 8	1b
Hydrogen (H ₂)		10 ppm(v) max	BS EN 12021 NA.12	1a
Total non-toxic gases (exclude Helium (He) & Nitrogen (N ₂))	$\phi \leq 10\%(v)$	0.1%(v) max	BS EN 12021 NA.10	1b, & 4
	$10\%(v) < \phi \leq 20\%(v)$	0.2%(v) max		
	$\phi > 20\%(v)$	0.5%(v) max		
Other toxic / irritating substance (each substance)		TBA	BS EN 12021 NA.7	7, 8, & 9
<p>Note:</p> <ol style="list-style-type: none"> No change from Def Stan 68-284 Issue 3. <ol style="list-style-type: none"> The limit is the same as that specified in NATO STANAG 1458 and BS EN 12021. The limit is the same as that specified in NATO STANAG 1458 and is a more restrictive limit than that specified in BS EN 12021. Free from unacceptable odour that may have an adverse effect on the user or breathing apparatus. Oil may be present due to previous contamination, use of oil lubricated compressor or use of gases with oil vapour present. These gases include argon (Ar) and all other noble gases, but exclude helium (He) and nitrogen (N₂). Nominal oxygen content (ϕ) and helium content (λ) as specified in the relevant contract between the purchaser and the supplier. There is a gap in the tolerance specification for helium (He) in Def Stan 68-284 Issue 3. No tolerance is specified for helium content λ, $10\%(v) < \lambda \leq 20\%(v)$. A more restrictive limit used for $\lambda \leq 10\%(v)$ in Def Stan 68-284 Issue 3 is thereby extended to $\lambda \leq 20\%(v)$ to cover the gap in the Def Stan. Where substances other than those listed are found, the substances shall be identified and reported to the applicable authority for determination of maximum limits and appropriate test methods based on the sensitivity and specificity of the methods. It should be noted that the limit should not be greater than one tenth (1/10) of the 8-hour time weighted average Workplace Exposure Limit (WEL) given in the Health & Safety Executive publication, Workplace Exposure Limits (EH40). 				

DEF STAN 68-284 Part 04 Issue 1

9. Where the gaseous trace contaminants are detected by FTIR analysis but cannot fully identified, they shall be quantified using gas chromatography - mass spectrometry (GC-MS) or other alternative methods (AMs). This approach is the same as that given in Def Stan 68-284 Issue 3 A.6 Method for the Determination of Other Trace Contaminants.
10. The limit 0.01 mg/m³ specified in Def Stan 68-284 Issue 3 Table 5 is believed to be a typo error. This is corrected to 0.1 mg/m³ aligning it to the same as that specified in NATO STANAG 1458 and BS EN 12021.

Section 3

Normative References

1 The publications shown below are referred to in the text of this standard. Publications are grouped and listed in alpha-numeric order.

Note: Def Stan's can be downloaded free of charge from the DStan web site by visiting <<http://dstan.uwh.dif.r.mil.uk>> for those with RLI access or <<https://www.dstan.mod.uk>> for all other users. All referenced standards were correct at the time of publication of this standard (see 2, 3 & 4 below for further guidance), if you are having difficulty obtaining any referenced standard please contact the DStan Helpdesk in the first instance.

Def Stans

Number	Title
01-005, Iss 18	Fuels, Lubricants and Associated Products
68-284, Pt 01, Iss 01	Breathing Gases for Non-Medicinal Life-Support Applications - Supply Requirements

STANAGs

Number	Title
1458 Edition 2	DIVING GAS QUALITY - ADivP-04 EDITION A

Allied Publications

Number	Title
ADivP-04 Edition A Version 1	DIVING GAS QUALITY

Other References

Standard Type	Standard Name
BS / BS EN / BS ISO Standards	BS EN 12021, Respiratory Equipment – Compressed Gases for Breathing Apparatus
BS / BS EN / BS ISO Standards	BS ISO 8573-3, Compressed Air – Part 3: Test Methods for Measurement of Humidity
Other Civilian/Industry Standards	HSE EH40, Health & Safety Executive, Workplace Exposure Limits – Containing the List of Workplace Exposure Limits for Use with the Control of Substances Hazardous to Health Regulations (as amended)

DEF STAN 68-284 Part 04 Issue 1

Other Civilian/Industry Standards	JSP 319, Ministry of Defence, Joint Service Safety Regulations for the Storage & Handling of Gases
---	---

2 Reference in this Standard to any normative references means in any Invitation to Tender or contract the edition and all amendments current at the date of such tender or contract unless a specific edition is indicated. Care should be taken when referring out to specific portions of other standards to ensure that they remain easily identifiable where subsequent amendments and supersession's might be made. For some standards the most recent editions shall always apply due to safety and regulatory requirements.

3 In consideration of clause 2 above, users shall be fully aware of the issue, amendment status and application of all normative references, particularly when forming part of an Invitation to Tender or contract. Correct identification of standards is as defined in the ITT or contract.

4 DStan can advise regarding where to obtain normative referenced documents. Requests for such information can be made to the DStan Helpdesk. Details of how to contact the helpdesk are shown on the outside rear cover of Defence Standards.

Definitions

For the purpose of this standard, ISO/IEC Guide 2 ‘Standardization and Related Activities – General Vocabulary’ and the definitions shown below apply.

Definition	Description
Absolute Micron Rating	It expresses the ability of the filter to remove at least 98.7% of a specific size particle. For instance, an absolute rating of 10µm simply means that filter captures at least 98.7% of contaminants 10µm in size.
Alternative Method	Measurement method which is not a reference method but has been demonstrated in specific cases to applicable authority’s satisfaction to produce results adequate for the measurand.
Compressed Natural Breathing Air	Compressed air that meets breathing air quality criteria, and the air is taken directly from the atmosphere without additional gaseous additives however some filtering / processing may be necessary.
Contaminant	Refer to impurity.
Could	The verb describes an activity that is a good practice but recognises that there are other methods available to the practitioner that provide an equally satisfactory good outcome.
Dew Point	Defined as the temperature at which dew or condensation, forms on cooling a gas. It is a measurement taken at normal atmospheric pressure (1,013mbar absolute, 20°C). NOTE: For temperatures below 0°C, the term Frost Point should strictly be used, but the term Dew Point is often used to include Frost Points (as does this Def Stan).
Heliox	Diving gas mixture, comprising a specified mixture of oxygen and helium, capable of supporting life under defined diving or hyperbaric conditions.
Impurity	Any constituent other than the main constituents.
In-Situ Produced	Commodity / product produced at MOD facility.
Must	The verb describes an activity that is mandatory, and descends directly from national legislation.
Nitrox	Diving gas mixture, comprising a specified mixture of oxygen and nitrogen, capable of supporting human life under defined diving or hyperbaric conditions. NOTE: Compressed breathing air made from a mixture of liquefied gases may be considered as Nitrox if it conforms to the Nitrox requirements.
Normal Atmospheric Pressure	1,013mbar absolute, 20°C.

DEF STAN 68-284 Part 04 Issue 1

Oil	<p>Defined as a mixture of hydrocarbons and other organic compounds composed of six or more carbon atoms (C6+).</p> <p>NOTE 1: It may exist as oil aerosol (ie liquid oil suspended in a gaseous medium), oil liquid and as oil vapour.</p> <p>NOTE 2: Oil may arise from the use of an oil-lubricated compressor.</p> <p>NOTE 3: This definition mirrors that defined in BS EN 12021 and encompasses all types of oils. It includes synthetic oils based on silicone fluids, phosphate ester fluids, mineral oils and etc (refer to Def Stan 01-005).</p>
Procured	Commodity / product from manufacturer or value-added re-seller.
Purity	Concentrations of the main constituents, ie concentrations of nitrogen and oxygen in a sample of Nitrox, concentrations of helium and oxygen in a sample of Heliox, and concentrations of nitrogen, helium and oxygen in a sample of Trimix.
Reference Method	Measurement method taken as a reference by convention, which gives the accepted reference value of the measurand.
Shall	The verb describes an activity that is mandatory, but stems from defence regulations in the absence of national legislation.
Should	The verb describes an activity that is the best practice. If the activity is followed, then this will be considered sufficient to demonstrate compliance with a regulation. However, alternative approaches may be utilised where this produces an outcome as good as required by the Regulation.
Trimix	Diving gas mixture, comprising a specified mixture of oxygen, helium and nitrogen, capable of supporting human life under diving or hyperbaric conditions.

Abbreviations

Abbreviation	Description
%(v)	Percent by volume (dry gas) at normal atmospheric pressure (1,013mbar absolute, 20°C)
µm	Micrometre
AM	Alternative Method
AMR	Absolute Micron Rating
BS EN	British Standard European
BS ISO	British Standard International Standard Organisation
CFC	Chlorofluorocarbon
CNBA	Compressed Natural Breathing Air
CoC	Certificate of Conformity
Def Stan	Defence Standard
DLF	Defence Logistics Framework
DSFA	Defence Strategic Fuels Authority
DStan	UK Defence Standardization
EH	A numbered series of HSE publications: Guidance Notes, Environmental Hygiene
FTIR	Fourier Transform Infrared
GC-MS	Gas Chromatography – Mass Spectrometry
HCFC	Hydrochlorofluorocarbon
Heliox	Helium and oxygen gas mixture (Refer to Definitions for details)
HM	Her Majesty's
HSE	Health and Safety Executive
JSP	Joint Services Publication
MCP	Manifolded cylinder pack
MOD	Ministry of Defence
MSOCS	Molecular Sieve Oxygen Concentrating System

DEF STAN 68-284 Part 04 Issue 1

Nitrox	Nitrogen and oxygen gas mixture (Refer to Definitions for details)
ppm(v)	Parts per million by volume (dry gas) at normal atmospheric pressure (1,013mbar absolute, 20°C)
TBA	To Be Advised
Trimix	Oxygen, helium and nitrogen gas mixture (Refer to Definitions for details)
TWA	Time-Weighted Average
WEL	Workplace Exposure Limit
λ	Nominal helium content percentage by volume at normal atmospheric pressure (1,013mbar absolute, 20°C)
ϕ	Nominal oxygen content percentage by volume at normal atmospheric pressure (1,013mbar absolute, 20°C)

©Crown Copyright 2020

Copying Only as Agreed with DStan

Defence Standards are published by and obtainable from:

Defence Equipment and Support

UK Defence Standardization

Kentigern House

65 Brown Street

GLASGOW

G2 8EX

DStan Helpdesk

Tel: +44 (0) 141 224 2531

Internet e-mail: enquiries@dstan.mod.uk

File Reference

The DStan file reference relating to work on this standard is 68/284/4.

Contract Requirements

When Defence Standards are incorporated into contracts, users are responsible for their correct application and for complying with contractual and statutory requirements. Compliance with a Defence Standard does not in itself confer immunity from legal obligations.

Revision of Defence Standards

Defence Standards are revised as necessary by an up-issue or amendment. It is important that users of Defence Standards ensure that they are in possession of the latest issue or amendment. Information on all Defence Standards can be found on the DStan Websites <https://www.dstan.mod.uk> and <http://dstan.uwh.diif.r.mil.uk/>, updated weekly. Any person who, when making use of a Defence Standard, encounters an inaccuracy or ambiguity is encouraged to notify UK Defence Standardization (DStan) without delay in order that the matter may be investigated and appropriate action taken.