Redevelopment of the Children's Play Area - Downsview Recreation

Ground. Wicksteed Rocking Horse – Surfacing.

- Excavate grass and soil over an area 24.0 m2, (4m x 6m), dispose waste off site.
- Supply and install PCC edging, weed and root resistant membrane and MOT Type 1 stone basework, level and heavily compact.
- Supply and install 24.0 m2 of BLACK with MULTI-COLOURED FLECK Wet Pour RubberSafer Surfacing to a depth of 40 mm. C.F.H. 1.20 metres.
- Clear all waste and leave site ready for play.

Spinning Cup Roundabout – Surfacing.

- Excavate grass and soil over an area 16.0 m2, (4m x 4m), dispose waste off site.
- Supply and install PCC edging, weed and root resistant membrane and MOT Type 1 stone basework, level and heavily compact.
- Supply and install 16 m2 of BLACK with MULTI-COLOURED FLECK Wet Pour Rubber SaferSurfacing to a depth of 40 mm. C.F.H. 1.20 metres.
- Clear all waste and leave site ready for play.

Record Infant Multi-Play – Surfacing.

- Excavate grass and soil over an area 54.0 m2, (9m x 6m), dispose waste off site.
- Supply and install PCC edging, weed and root resistant membrane and MOT Type 1 stone basework, level and heavily compact.
- Supply and install 54.0 m2 of BLACK with MULTI-COLOURED FLECK Wet Pour RubberSafer Surfacing to a depth of 50 mm. C.F.H. 1.50 metres.
- Clear all waste and leave site ready for play.

New Pole Climber Unit C & Wet Pour Rubber Safer Surfacing.

- Breakout and remove from site the central Wicksteed Multi-Play, the rubber mulch surface is toremain in-situ and have some remedial concrete repairs carried out to remove the damaged sections.
- Supply and install Pole Climber C fitted with Galvanised steel post shoes.
- Supply and install 34.0 linear metres of PCC edging to form new retaining edge, install weed androot resistant membrane and secure to the existing Rubber Mulch Surface with Polyurethane adhesive.
- Supply and install 72.0 m2 of BLACK with MULTI-COLOURED FLECK Wet Pour RubberSafer Surfacing to a depth of 50 mm. C.F.H. 1.50 metres.

• Clear all waste and leave site ready for play.

New 2 Bay Junior Swing Unit & Wet Pour Rubber Safer Surfacing Repairs.

- Breakout and remove from site the existing Wicksteed Junior Swing Unit.
- Supply and install new timber 2 bay Junior Swing Unit with Stainless Steel chain assemblies and Galvanised steel post shoes.
- Supply and install coloured Wet Pour Rubber Safer Surfacing patch repairs to full depth to re-instate the existing Wet Pour Safer Surfacing.
- Clear all waste and leave site ready for play.

New 2 Bay Infant Swing Unit & Wet Pour Rubber Safer Surfacing Repairs.

- Breakout and remove from site the existing Wicksteed Infant Swing Unit.
- Supply and install new timber 2 bay Infant Swing Unit with Stainless Steel chain assemblies and Galvanised steel post shoes.
- Supply and install coloured Wet Pour Rubber Safer Surfacing patch repairs to full depth to re-instate the existing Wet Pour Safer Surfacing.
- Clear all waste and leave site ready for play.

New Springer Unit & Wet Pour Rubber Safer Surfacing Repairs.

- Breakout and remove from site the existing ground anchor system.
- Supply and install a new Springer Animal, set on new in-ground anchor assembly.
- Supply and install coloured Wet Pour Rubber Safer Surfacing patch repairs to full depth to re-instate the existing Wet Pour Safer Surfacing.
- Clear all waste and leave site ready for play.