



Create consulting

Shrub end clinic garage

Project reference: 1080202

Contact: Darren Read

Email: darren.read@whitecroftlight.com

Telephone: 07831392222



Optional project information	3
A ACL Industry	4
AEQ ACL Industry	5
B Kolo IP65	6
C Euroflood MidiLED	7
2CS Command Evo Switching	8
Ceiling Compatibiity Matrix	9



Project reference:

A

Part number:

ACH44K
ACH44KEM

Product description:

LED IP65 anti-corrosive luminaire with GRP body with high impact polycarbonate injection moulded opal diffuser. High quality seamless gasket for extreme durability – as Whitecroft Lighting ACL INDUSTRY



Light source

Light source:

LED

Colour temperature:

4000K

Colour render index:

>80

Colour consistency:

MacAdam 3 SDCM

Control gear:

Fixed Output

Integral control:

N/A

Luminaire performance

LL/CW:

140.3

Circuit watts:

33

Light output ratio:

100%


Emergency

N/A


Finish

Grey

Dimensions & Weight



Polar Curve (Indicative Only)



VERSION	L	W	H	KG	KG(EM)	FC
2800, 3900, 4600, 6400 lumen	1282	145	101	2.8	3.3	800
7500, 9500 lumen	1578	145	101	3.4	3.9	800

Project reference:

AEQ

Part number:

ACQ5H44K

Product description:

LED IP65 anti-corrosive luminaire with GRP body with high impact polycarbonate injection moulded opal diffuser. High quality seamless gasket for extreme durability – as Whitecroft Lighting ACL INDUSTRY



Light source

Light source:

LED

Colour temperature:

4000K

Colour render index:

>80

Colour consistency:

MacAdam 3 SDCM

Control gear:

Fixed Output

Integral control:

COM5 (NO SETBACK)

Luminaire performance

LL/CW:

140.3

Circuit watts:

33

Light output ratio:

100%


Emergency

N/A


Finish

Grey

Dimensions & Weight



Polar Curve (Indicative Only)



VERSION	L	W	H	KG	KG(EM)	FC
2800, 3900, 4600, 6400 lumen	1282	145	101	2.8	3.3	800
7500, 9500 lumen	1578	145	101	3.4	3.9	800

Kolo IP65



Project reference:

B

Part number:

K6H4274KSEM
K6Q54274KSEM

Product description:

Surface mounted circular IP65 LED bulkhead luminaire in 300 or 400mm diameter. Polycarbonate opal diffuser. Trim ring and grill front attachments available. Optional integrated microwave presence detector with ON/OFF or set-back functionality - as Whitecroft Lighting KOLO IP65



Light source

Light source:

LED

Colour temperature:

4000K

Colour render index:

>80

Colour consistency:

MacAdam 3 SDCM

Control gear:

Fixed Output

Integral control:

N/A

Luminaire performance

LL/CW:

96.61

Circuit watts:

28

Light output ratio:

100%


Emergency

3hr Maint


Finish

Silver

Dimensions & Weight



Polar Curve (Indicative Only)



VERSION	H	KG	KG(EM)	Ø
300mm surface	95	2.1	2.5	300
400mm surface	95	3.5	3.9	400

Euroflood MidiLED



Project reference:

C

Part number:

EFLH24KG

Product description:

IP66 slimline asymmetric floodlight with die cast body and 5mm thick thermal shock and impact resistant glass. High quality, efficient LED light engine with a range of light outputs to suit a wide variety of applications – as Whitecroft Lighting EUROFLOOD MIDILED



Light source

Light source:

LED

Colour temperature:

4000K

Colour render index:

>80

Colour consistency:

MacAdam 3 SDCM

Control gear:

Fixed Output

Integral control:

N/A

Luminaire performance

LL/CW:

105.28

Circuit watts:

81

Light output ratio:

100%


Emergency

N/A


Finish

Grey

Dimensions & Weight



Polar Curve (Indicative Only)



L	W	H	KG	Windage (m2)
333	85	568	6.3	0.15

Command Evo Switching



Project reference:
2CS

Part number:
EVHSM

Product description:

Recessed or surface mounted switching programmable PIR presence/ absence detector – as Whitecroft Lighting COMMAND EVO SWITCHING



Light source

Light source:

Colour temperature:

Colour render index:

Colour consistency:

Control gear:

N/A

Integral control:

N/A

Luminaire performance

LL/CW:

0

Circuit watts:

None

Light output ratio:

None


Emergency

N/A

Finish

N/A

Dimensions & Weight



VERSION	H	KG	Ø1	Ø2	CAØ
Recessed	92.6	0.14	87		73
Surface	107.6	0.16	87	93	

Ceiling compatibility matrix

[illegible][illegible]